Technical Specifications For 125 mm - Traffic Light

No.	Item	Specifications
1	**Brand**	**Nucleonics traffic equipmentts**
2	**Model**	**NTE10055**
3	**Technology**	LED based 5mm oval type
4	**Dimension**	300mm x 150mm x50 mm
5	**Led retrofit dia.**	125mm (±10%) full round
6	**Aspect diameter**	125mm
7	**PCB**	Green masking Pads- Tin plated Conformal coating for moisture protection
8	**Aspect Color**	Red and Pure Green
9	**Type of signal**	Ball type
10	**Luminance**	Red-265cd
11	**Wavelength**	625nm for Red
		505nm for Green
12	**Aspect Color**	Red and Pure Green
13	**Interface**	230V/AC switching from potential free devices
14	**Visibility**	>200mtrs
15	**Viewing Angle**	< 23 degrees
16	**Cables**	Power Cable
17	**LED Type**	Super Bright Day visible
		12000 - 14000 mcd at 20 mA, 30˚ viewing angle for Red
		21000 - 24000 mcd at 20 mA, 30˚ viewing angle for GREEN
18	**Weight**	< 5 Kg
19	**Operating Voltage**	220-270VAc /50-60 Hz

20	**Power Consumption**	6W max
21	**Controls**	two inputs to receive potential free signals to activate / deactivate either of the lights
22	**Installation**	Bolting Arrangement to the Traffic Pole
23	**Environment Conditions**	Operating Temp : -10°C to 60°C
		Humidity : 0 to 90%
24	**Reliability**	MBTF: 50,000 hours
		MTTR: 0.20 hrs
25	**Access For maintenance**	Front Door Access for Easy Maintenance
26	**Protection**	IP65 compatiable
27	**Operating Temperature -**	5 ºC to 65 ºC
28	**Housing Material**	Mild Steel 1 mm thick