Date : 21.05.2019

Project Name : MI - ACO Kitchen Drainage Product Specification

			Total Qty in Set
1.00		Plumbing & Drainage Works:	
	G.	Providing and fixing Providing and fixing of customised channel with graiting of 50mm/80mm deep (CH-1 To CH-19) Refer the drawing for channel details) ACO Hygienic Channel Drainage Systems Drainage fulfils stringent hygienic requirements to prevent harmful bacterial contamination Under EHEDG Guidelines We apply the relevant hygienic design principles reserved for food contact surfaces EN 1672, EN ISO 14159 ACO channel hygienic features: □ Fully drainable □ Internal radius equal or larger than 3 mm □ Hygienic joints □ Edge infill □ Stainless steel grade min. AISI 304 □ Fully pickled and passivated	
	a)	**ACO Hygienic Gully - 200MM x 200MM - 1 to 35 Nos**	35.00
		Supply & Installation of ACO hygienic gully 142 fixed height As per EN 1672, EN ISO 14159 W200 L200 D110 horizontal with FAT, FHD, EN1253, 1.4301 with ACO mesh grating W168 L168 H25 antislip, LC L15, EN1253, 1.4301 and ACO silt basket for horizontal gully 142, EN1253, 1.4301, Inclusive of material, labour, transportation, leads, lift & shift etc. complete.	
	b)	**For CH 01 - Channel Dimension W400/370 L5030/5000**	1.00
		ACO Hygienic Box Channel ACO hygienic channel W400/370 L5030/5000 H80/50 E30.5, D125 F45, standard edge, FHD, EN1253, 1.4301 with ACO mesh grating W368 L499,5 E30, mesh 25x25 bar 30x2, LC L15, EN1253, 1.4301 ACO hygienic gully 142 telescopic D110 horizontal location flange with FAT, FHD, EN1253, 1.4301 along ACO gully 142 telescopic silt basket, EN1253,1.4301	
	C)	**For CH 02/03/13/14 -Channel Dimension W400/370 L830/800**	4.00
		ACO Hygienic Box Channel ACO hygienic channel W400/370 L830/800 H80/50 E30.5, D125 F45, standard edge, FHD, EN1253, 1.4301 with ACO Mesh grating W368 L499,55 E30, mesh 25x25 bar 30x2, LC L15, EN1253, 1.4301 ACO hygienic gully 142 telescopic D110 horizontal location flange with FAT, FHD, EN1253, 1.4301 along ACO gully 142 telescopic silt basket, EN1253,1.4301	
	D)	**For CH 04/07/08/15/16 -Channel Dimension W800/770 L830/800**	5.00
		ACO Hygienic Box Channel ACO hygienic channel W800/770 L830/800 H80/50 E30.5, D125 F45, standard edge, FHD, EN1253, 1.4301 with ACO Mesh grating W768 L398 E30, mesh 25x25 bar 30x2, LC L15, EN1253, 1.4301 ACO hygienic gully 142 telescopic D110 horizontal location flange with FAT, FHD, EN1253, 1.4301 along ACO gully 142 telescopic silt basket, EN1253,1.4301	
	D)	**For CH 05/06/11 -Channel Dimension W400/370 L1530/1500**	3.00
		ACO Hygienic Box Channel ACO hygienic channel W400/370 L1530/1500 H80/50 E30.5, D125 F45, standard edge, FHD, EN1253, 1.4301 with ACO Mesh grating W368 L499 E30, mesh 25x25 bar 30x2, LC L15, EN1253, 1.4301 ACO hygienic gully 142 telescopic D110 horizontal location flange with FAT, FHD, EN1253, 1.4301 along ACO gully 142 telescopic silt basket, EN1253,1.4301	

			Total Qty in Set
	E)	**For CH 09/10 -Channel Dimension W800/770 L1030/1000**	2.00
		ACO Hygienic Box Channel ACO hygienic channel W800/770 L1030/1000 H80/50 E30.5, D125 F45, standard edge, FHD, EN1253, 1.4301 with ACO Mesh grating W768 L398 E30, mesh 25x25 bar 30x2, LC L15, EN1253, 1.4301 ACO hygienic gully 142 telescopic D110 horizontal Location flange with FAT, FHD, EN1253, 1.4301 along ACO gully 142 telescopic silt basket, EN1253,1.4301	
	(F)	**For CH 12/19 -Channel Dimension W400/370 L2030/2000**	2.00
		ACO Hygienic Box Channel ACO hygienic channel W400/370 L2030/2000 H80/50 E30.5, D125 F45, standard edge, FHD, EN1253, 1.4301 with ACO Mesh grating W368 L499 E30, mesh 25x25 bar 30x2, LC L15, EN1253, 1.4301 ACO hygienic gully 142 telescopic D110 horizontal location flange with FAT, FHD, EN1253, 1.4301 along ACO gully 142 telescopic silt basket, EN1253,1.4301	
	(G)	**For CH 17/18 -Channel Dimension W400/370 L4030/4000**	2.00
		ACO Hygienic Box Channel ACO hygienic channel W400/370 L4030/4000 H80/50 E30.5, D125 F45, standard edge, FHD, EN1253, 1.4301 with ACO Mesh grating W368 L499 E30, mesh 25x25 bar 30x2, LC L15, EN1253, 1.4301 ACO hygienic gully 142 telescopic D110 horizontal location flange with FAT, FHD, EN1253, 1.4301 along ACO gully 142 telescopic silt basket, EN1253,1.4301	
	(H)	**Below Groud Grease Separator - Kitchen Outlet Line**	
		Supply & Installation of ACO Lipumax NS 10 Below Ground Grease separator plant as per DINEN 1825 and DIN 4040-100 ,Emptying and cleaning via shaft manhole cover Connections for inlet and outlet DN150 as per DIN 19534 and DIN 19537 Building Supervisory Authority approval Z-54.1-509 Total Capacity (in Litres) 2,170 With Sludge Trap - 1,005 Litres and Grease Trap 415 Litre Wi For underground installation Along with the Top Section for Grease Separator A 15 Load Class -Concrete frame with cast iron cover & odour Free when Closed. Inclusive of material, labour, transportation, leads, lift & shift etc. complete.	1 Qty Apporx Design for 1000 Meals **Note : you can send us exact Meals per day for Submission of ACO Grease Separator design**

For ACO Systems & Solutions Private Limited

Name: Durgesh Pissurelkar

Designation: Areas Manager

Telephone/Email: 7899932655 Email id durgesh@acosystems.in