NIHVA make Machine Protection Door

Sr. No	Description	Specifications
	CURTAIN DETAILS	
1	European Make- Most Innovative & Superior PVC Coated Fabrics for High Speed Doors	
2	Longer Life Span • High Tear Strength • Dimensional Stability • UV Resistant • Very Flexible	
3	Flame Retardant (Chemically Treated to Self-Extinguish)	
4	Resistant to Humid Environment	
5	Working Temperature Range: From -30°C to +85°C	
	DOOR STRUCTURE	
1	Front guide columns of the doors are made of Aluminium Matt finished clear Anodized of size 125 mm x 105 with wall thickness 5 mm.	
2	The curtain along with heavy bottom side is made by aluminium profile of 90 mm x 25 mm thick for better support & curtain movement.	
3	Door columns are with dual brush sealing which seals door columns and stops movement of air and pollutants positive wind resistance class - Din en 12424 - Class 3 with standard pressure difference - Delta 10 pascals.	
	Operation & Accessaries	
1	Basic Operation on Push Buttons from both the sides.	
2	Auto Close Function is Inbuilt	
3	Auto Close with variable hold open timer range can be set in between 1sec - 500 sec	
	Motor and Controller	
1	Motor	High Speed Servo Motor Make IDER, manufactured under European Standards, CE certified.
2	Speed	Normal Factory Set Speed is in between 500 mm / sec opening & closing. With Programming can be changed up to 2000 mm / sec.
3	Power Supply	3*AC 220V
4	IP Rating	lp65
	Safety Features & Accessories	
1	Photocell (Safety Sensor) - Dual Safety PE Sensor (Working range of 6m) is included.	
2	The Safety edge sensor, installed inside the bottom rubber, will reverse the door in case of any feather touch obstruction occurred between the door and floor is included.	
3	Light Curtains Mounted on Side Guide **(Inbuilt Light curtains of VEKO)**	