NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC,
Chinchwad.
Pune – 411019

An ISO 9001:2015 Certified Company

GST Pune : 27AAECN0437H1ZM

B) Technical Specification

High Speed door "NIHVA" Make (100% European component)

- Safe & for continous operations
- Self Supporting Construction with anti crash protection system for bottom profile
- Smooth & silent opening & closing
- Modular Interchaegable panels permit to replace worn & damged panels

Sr. No	Description	Specifications
1	Size	2400 x 5550 mm
2	Speed	Inverter Motion system to adjust different speeds, with progressive control of acceleration & deceleration during braking .
3	Opening speed	upto 3 m/s
4	Closing speed	0.8 m/s
5	Control Panel	4 Push Button operated
6	Security Features	EN 13241-1 Standard
7	Resistance to wind load	EN12424 upto class 2
8	Curtain	High tensile and tear strength PVC fabric thickness: 1.2 mm
9	Vision Panel	No. of vision panel: Total 2nos. each of atleast 900 mm height, 2 mm thickness and starting from approx. 1 Mtr from ground floor
10	Curtain Colour	Gray RAL 7035
11	Guide Material	Aluminum Anodised
12	Hood Cover	Galvanised with Silver paint
13	Motor Cover	Galvanised with Silver paint
14	Operator & Control	German Direct drive Motor
15	Connecting Voltage	230V , 1Ph , N
16	Open-Stop-Close Button	Standarad
17	Protection Category (Operator/Control)	IP 54 / IP 65
18	Power Consumption	0.75 kw Motor
19	Emergency Off Button	Standard
20	Safety	Optical Safety edge with wire (hide the spiral cable into the column) and 1 pair Safety Photocell
21	Emergency Opening	EMG opening through Crank Handle
22	Extra Accessories	Flashing Light with buzzer
		Button controls on both sides of door with key switch