

Motorized Cantilever Gate

- Noise-free movement of gate.
- No Track or concrete foundation required on the roadway.
- Obstacle free entry without any bumps.
- No risk of non-functioning of gate due to bending or wearing-tearing of bottom rail.
- Can be easily installed on uneven or sloped ground surface.
- Imported monolithic cantilever track & pair of heavy duty bottom carriages.

NIHVA Technologies Pvt.Ltd







NIHVA Cantilever Gate

Technical Specification	Description	
Product	Motorized Cantilever Gate	
Dimensions		
Width Min. /Max.	• Single Leaf : 1000/15000mm • Double Leaf :2000/30000mm	
Height Min. /Max.	• 1000/2500mm • Larger Dimension on request	
Opening	• Horizontal	
Mounting Location	• Inside/ Outside	
Material	• Stainless Steel, Hot dip Galvanized	
Sheets	• M.S/GI/Perforated /Aluminum sheets/Wood.	
Designs	• Standard or as per client design.	
Options Available (as per requirement)	• Spikes /Wicket gate/Side Gates Provisions.	
Automation		
Drive Unit	• Motorized / Manual	
Emergency Operation	• Manual release knob.	
Accessories (Optional)	**Operational** • Additional Push Button • Key switch • Remote Control with receiver • Magnetic Loop Detector	**Safety** • Safety Photocell • Vertical Safety • Edge Sensor • Flashing Light



Technologies Pvt. Ltd