ASSA ABLOY Sectional Door - Vertical Lift

Sr. No	Specification	ASSA ABLOY Sectional Door - Vertical Lift
1	Opening Direction & Mounting	Vertical Lift
2	Opening/Closing Speed	CDM9 0,28 m/s
3	Door Material	GI Steel
4	Panel Thickness	42 mm
5	Filling	CFC-free polyurethane
6	Panel colour	RAL 9002 Grey White Powder coated
7	Door sealent	All door sealants made of EPDM rubber, temperature resistant - 30/+70
8	Panel Flame Retardent standrad	Flame retardant polyurethane foam according DIN4102-class B2.
9	Water Penetration	EN 12425 class 3
10	Air Permealibity	EN12426 class 3
11	Wind Load	EN21424 class 3
12	Thermal Transittance	EN 12428 1.10W /m2K
13	Bottom sealing	Bottom of the door to be equiped with three lip sealing made of oil resistant EPDM rubber
14	Door saftey	Doors equiped with spring break device
15	Incase of Power failuer	Doors to be equiped with quick release fuction
16	Operator power conumption	Operator to have a maximum power consumption of 0,37kW and a standby consumption of Maximum 15W
17	Drive Unit & Mounting Type	Single phase 230V direct drive on shaft
18	Emergency Operation	by Disengagement rope manual
19	Operating Switch	Up/Down Keypad + stopbutton
20	Locks : Lock bolt	The Lock bolt locks the door from the inside, without the use of a key. The Lock bolt is not visible from the outside.
21	Environmental Green Product Declaration Certification	As per ISO 14025 and EN 15804