RapidRoll® 3000 Serie

High speed roll door for machine protection

ALBANY
ASSA ABLOY

Technical data sheet

ASSA ABLOY, the global leader
in door opening solutions



ASSA ABLOY Entrance Systems is a leading supplier of entrance automation solutions for efficient flow of goods and people. With a worldwide presence we offer products and services dedicated to satisfying end-user needs for safe, secure, convenient and sustainable operations. ASSA ABLOY Entrance Systems is a division within ASSA ABLOY.

ALBANY
ASSA ABLOY

www.assaabloyentrance.com **www.albanydoors.com**

Protection and Safety for Automated Processes.

RapidRoll® 3000 as Machine Protection Door e.g. used in laser applications

The RapidRoll® 3000 is, due to its combination of high speed, long life length and robust aluminium door curtain, well suited for machine protection applications. A nearly service free drive system and small mounting space is an other advantage.

The RapidRoll® 3000 is qualified as a laser protection door because of its double-walled panels and the design of the profiles which leads to an overlapping like a labyrinth of two profiles. As a result of this unique construction the laser beam can not burn through the door curtain.



ADVANTAGES OF ALBANY RAPIDROLL® 3000 MACHINE PROTECTION

- Suitable for universal use
- Labyrinth connections between the panels take care of a laser proof curtain
- Rapid opening and closing ensures a short cycle time
- Protection against flying sparks, dust, noice or welding sparks
- Personnel protection in danger zones of the machnine
- Safety limit switches according to EN ISO 13849-1 and EN 62061
- Doors conform to EN ISO 12100 and EN 1088
- Microprocessor control of the door allows individual programming to meet customer special needs
- Versions conforming to various company standards are possible
- High reliability even after years of high number of cycles (up to 4 cycles per minute or 1 cycle/15 s)





APPLICATION

- Laser facilities for e.g. welding and cutting
- Automatic welding systems
- Cutting systems
- Milling machines
- Painting systems
- Workpiece handling
- Tool handling
- Presses
- Conveyor systems
- Elevator and high-bay storage systems

PROTECTION

The door is tested by BG according to EN 60825-4 with a 4,6 kW laser and focus distance 2 and the laser beam didn‘t burn trough after 60 sec.



The door is certified according to EN 60825-4 with a 4,6 kW laser and focus distance 2.



Safety limit switch integrated in the side frames

CONNECTING TO THE MACHINE

- 2 potential-free safety contacts when the door is closed
- 1 output when the door ist opened
- 1 output when the door is closed
- 1 output for faults
- Controlling the door is accomplished by potential-free contacts

SAFETY LIMIT SWITCHES

- Safety limit switches: PL d/Kat. 3 und PL e/Kat. 4 (EN ISO13849-1), SIL 3 (EN 62061)
- Delivered with safety monitoring module as standard
- Alternatively, the system can be delivered without a safety monitoring module where the safety category then depends on the machines safety systems.

NOICE PROTECTION

The RapidRoll® 3000 allows a noice protection up to 25dB(A).

© ASSA ABLOY Entrance Systems AB. All rights reserved. Technical data subject to change without notice

64 05 R 0709/12/12 EN