

NIHVA make – Telescopic Conveyor

Description	Telescopic Conveyor
Size of Conveyor	21000 mm
Elongated length with no of boom	14000 mm
Collapsed length	7000 mm
Width of Belt	650mm
Speed of Conveyor	30 Mtr/min (Adjustable)
a) Max Speed	32 mtr/min
b) Min Speed	15 mtr/min
Speed of Conveyor (with load)	
a) Max Speed	286 RPM
b) Min Speed	160 RPM
Cycle Time (for Telescopic Operation)	**100 -150 Sec**
Cycle Time (for Telescopic collapsing operation)	100 -120 Sec
Capacity of Conveyor	30kg/mtr
Weight of Total System	750Kgs
Roller Guide with chain drive for telescopic operation	
Brake motor used in conveyor	4.25 hp, 2hp, 1.5hp
Motor Make	Hindustan Motor

91 8551096333 ☎ +91 20 66304033

Email: arjun.patil@nihva.com

Hydraulic Lifting arrangement for conveying height adjustment	
Rigid piping of Hydraulic connections	
Cable routing through Flexible conduit	
Belt Tightening arrangement to avoid slagging in Belt	
Led Light unit is mounted at front of boom to illuminate light in container	
Audible warning to alert operator of impending belt starts	
Anti-collision strip fitted at the front of the boom which causes the machine to retract / Stop	
Main Supply	415V, 20A
Control Voltage	24V DC
Belt Speed	15 Mtr/min
Forward & Retract Speed	6 Mtr/min
Power Pack	2.5 hp/ 15 ltr

91 8551096333 ☎ +91 20 66304033

Email: arjun.patil@nihva.com