NIHVA make – Motorized Telescopic Sliding Gate	
Door type	**Five Leaf Telescopic Motorised Sliding Gate (One Leaf will be fixed and Four Leafs will be Movable)**
Clear Opening gate dimension	Size (w) 7520 mm x (h) 2200 mm Size (w) 7200 mm x (h) 2200 mm
Opening Direction	**Horizontal - from left to right or reverse**
Mounting Location area	Inside area
Design Pattern	Standard Tubular Design Pattern
Outer Frame Tube Sizes	75 x 75 x 3.2 mm
Internal Vertical Tube Sizes	75 x 25 x 2 mm
Gap Between Tubes	125 mm C/C
Bottom Rail on ground	dia 20 mm round bright bar with heavy duty support ISMB 100 X 50 Beams
Bottom Rollers	Heavy Duty Bottom Wheel With both side Bearings (chorme plated)
Full Height Column sizes	75 x 75 x 3.2 mm
Guide Rollers supporter during Gate movement	**Nylon Rollers with Bearings both side mounted on column for support smooth movement of gate**
Painting	2 Coats of EPOXY polyamide based enamel finish of approved colour
El motor make	BFT – Italy (100% imported)
Emergency Operation	Manual after turn the switch
Telescopic Mechanism	Inbuilt with Gate
Operating Switch	Push Button from inside
Safety	Photocells, Flashing Light
Metal Rack	zinc plated metal rack
Installation Checks	need to be check = space requirements + substructure + Mounting access + Access in the event of power cut
Civil work	Client scope – client need to grout the I beam in concrete to create track for sliding gate