NIHVA	QUALITY ASSURANCE PLAN	Document No:- NIHVA - QA - F - 08 REVISION NO.:- 00 Revision date: _ Date of origin:- 01-01-2018

Product	Double wall Rolling Shutter

Sr. No.	Subject	Parameter	Checking Type	Checking Method	Inspection frequency
		G.I.Sheet	GI Material as per IS277 GP 250 standard	TC Verifying	100%
		Roller pipe	MS Material as per IS 1161 standard	TC Verifying	100%
		M.S. Sheet	MS Material as per IS 10748	TC Verifying	100%
		M.S. Sheet	MS Material as per IS 2062	TC Verifying	100%
2	Bought Out Material	Motor	Verification of manufacturer /Supplier T.C.	Visual	100%
3	Manufacturing Process				
3.1	Curtain	Curtain length	Dimensional	Steel tape	10%
		Curtain width		Steel tape	10%
		Dent/ Damage / Spin	Visual	No Dent/ Damage / Spin	100%
3.2	Hood cover	Hood cover Length	Dimensional	Steel tape	10%
		Hood cover width		Digital vernier	10%
		Hood cover thickness		Digital micrometer	10%
		Visual	Asthetically	Visual	100%
4	Fabrication Stage				
4.1	Guide	Guide Length	Dimensional	Steel tape	10%
		Guide Width	Dimensional	Steel tape	10%
4.2	Roller shaft	Length	Dimensional	Steel tape	10%
5	Assembly process				
5.1	Curtain assembly		As per drawing	Visual	10%
6	Surface finish		Matching shade with RAL pad	Visual	100%
		Coating Thickness	70 - 80 µ	DFT meter	10%

Prepared by: Maruti Yamgar

Approved by: Amit Kurhade

NIHVA TECHNOLOGIES PVT. LTD. PUNE