NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk,
MIDC, Chinchwad.
Pune – 411019

An ISO 9001:2015 Certified Company

GST Pune : 27AAECN0437H1ZM

NIHVA Sales Quotation

WANI PROJECTS & INFRA PVT LTD(HO)
401 A, PHOENIX EAST COURT
VIMAN NAGAR PUNE :- 411014.

Project, Location : ESR Palava

Date : 16.03.2021
Quote NO : SQT.20.21.3108
Kind Attn : Chintamani Ranbhor
Email Id : chintamani@wanigroup.com
Contact No: 9767213687

Subject : Quotation for Rolling Shutters, Dock Leveler, Metal Door and Fire Door.

Dear Sir,

Thank you for your opportunity and trust shown on "NIHVA" your preferred partner for innovative solutions.
This has reference to your above mentioned requirement, please find below our Solutions.

Sr. No	Description	Pages
A.	Commercial Offer	1
B.	Technical Specification	2
C.	General Conditions	3
D.	Terms & Condtions	3

A) Commercial Offer

Sr No	Description	Size		Qty	Supply Charges in INR		Installation Charges in INR	
		Clear Width (mm)	Clear Height (mm)	(Nos)	Unit Price	Total Amount	Unit Price	Total Amount
1	**Motorized Single Skin Rolling Shutter**	4000	5000	4	172,000	688,000	20,000	80,000
2	**Gear Operated Rolling Shutter**	3000	3000	2	80,000	160,000	20,000	40,000
3	**Dock Leveler - 5 Ton**	2000	2500	3	220,000	660,000	15,000	45,000
4	**Fire Door**	1200	2100	8	49,000	392,000	8,000	64,000
5	**Metal Door**	1200	2100	2	34,000	68,000	8,000	16,000
	Total			**9**		**1,968,000**		**245,000**
6	P&F Charges			3%		59,040		
	Total Without Taxes					2,027,040		245,000
	GST Extra @ 18%			18%		364,867.20		44,100
	Total With Taxes					**2,391,907**		**289,100**
7	Transportation Charges					Extra at atcual		
8	Unloading Charges @ Site					In Client Scope		

NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk,
MIDC, Chinchwad.
Pune – 411019

An ISO 9001:2015 Certified Company

GST Pune : 27AAECN0437H1ZM

B) Technical Specification

Motorized Rolling Shutter

Sr .No.	Specification	GI Motorized Rolling Shutter
1	**Description:**	Motorised Rolling Shutter with GI Slats with thickness of 1 mm.
2	**Mounting Location area**	Inside area / Outside area
3	**Mounting Surface**	Side Brackets: Optional = On Concrete /Steel & Side
4	**Curtain Panel**	The panel made of 1.0mm thick GI.
5	**Curtain panel size**	75mm wide
6	**Curtain Profile**	Curved
7	**Bottom Profile**	M. S. Plate 100 mm x 2.5 mm thick with angle stiffener
8	**Side Guide Profile**	M.S." U" Shaped profile 65 mm -150 mm x 3 mm thick.
9	**Roller Shaft**	M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Día -100 to 300 mm as per w x h
10	**Side Brackets**	MS Plate 3 mm to 10 mm thick, as per the opening dimension.
11	**Hood Cover**	Made of GI Sheet Thickness 0.9 mm GF mm
12	**Surface finish**	PU paint or Powder coated
13	**Drive Unit & Mounting Type**	Electric Motor - Indirect Mounting - Sprocket chain arrangement – IP54 Protection

Gear Operated Rolling Shutter

Sr .No.	Specification	GI Gear Operated Rolling Shutter
1	**Description**	Gear Operated Rolling Shutter with GI slats with thickness of 1 mm.
2	**Mounting Location area**	Inside area / Outside area
3	**Mounting Surface**	Side Brackets: Optional = On Concrete
4	**Curtain Panel**	The panel made of 1.0mm thick GI.
5	**Curtain panel size**	75mm wide
6	**Curtain Profile**	Curved
7	**Bottom Profile**	M. S. Plate 100 mm x 2.5 mm thick with angle stiffener
8	**Side Guide Profile**	M.S." T" Shaped profile 65 mm -150 mm x 3 mm thick.
9	**Roller Shaft**	M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Día -100 to 300 mm as per w x h
10	**Hood Cover**	Made of GI Sheet Thickness 0.9 mm GF mm
11	**Surface finish**	2 Coats (each coat of 35 microns DFT) of EPOXY polyamide-based enamel finish of approved color and make over a Coat (each one coat 25 microns DFT) of EPOXY polyamide based red oxide zinc phosphate primer
12	**Operation**	Gear Assembly.

NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk,
MIDC, Chinchwad.
Pune – 411019

An ISO 9001:2015 Certified Company

GST Pune : 27AAECN0437H1ZM

B) Technical Specification

Dock Leveler

Sr .No.	Specification	Dock Leveller
1	**Capacity**	5 Ton
2	**Dock operation mode**	AC power pack hydraulically operated
3	**Lip operation mode**	Hydraulic
4	**Operation control**	Through panel
5	**Loading platform height from**	1250mm
6	**Travel above & below dock level**	(+) 300 / (-) 250 mm
7	**Platform Size (W x L)**	2000 mm x 2500 mm
8	**Lip size (W x L)**	2000 x 400 mm
9	**Shut Height**	480 mm
10	**Overall length**	2000mm x 2500mm + Lip Length (400mm)
11	**Maximum slope can be achieved**	0.1
12	**Clear Pit dimensions (W x L x D)**	(W) 2050mm x (L) 2550 mm x (D)485 mm
13	**Hydraulic power pack**	Standard
14	**Driver type**	Direct by electric Motor
15	**Motor Ratings**	1 H.P
16	**Pump design flow**	2.5 LPM
17	**Pump pressure**	120 bar Operating 200 bar Max.
18	**Safety valve set pressure**	120 Kg/cm^2
19	**Pump Type**	Gear
20	**Volume of oil receiver**	7 Lit
21	**No Of Deck cylinder**	2 No
22	**Lip Cylinder**	1 No
23	**Yellow and Black Strips for Side**	Included
24	**Dock Bumper**	Pair of Dock Bumper
25	**Dock Bumper steel Gard**	Steel Support Plates
26	**Operation**	not stopping automatic while any truck movement

2 Hrs Fire rated Door

Sr. No	Description	2 Hrs Fire rated Door
1	Description	Fire Resistant Door Single Leaf Hinge Type (2 Hour Fire Rated) 1.20 mm thick G.I Sheet cladded 46mm thick shutter with infill Material Mineral Wool (Density – 96 Kg/M3) complete with G.I. frame (Single Ribet – Frame Profile 100 x 57mm) made from 1.60mm thick G.I. Sheet & Fixing arrangements AS PER BS 476 (PART- 20 &22); IS: 3614 (Part-II) for Integrity, Stability. Paint Finish.
2	Door Size	1200mm (W) x 2100mm (H)
3	Accessories	S.S. Ball Bearing Hinges - 04 nos
		Panic Bar Exit Device for Single Leaf Door - 01 Nos
		External Trim bar Panic Latch - 01 Nos
		Vision Panel with Fire Rated Glass of Size: 200 x 300mm (6mm Thick Clear Toughened Glass)
		Heavy Duty Door Closer – Dorma Make TS 68
		Concealed Flush Tower Bolt - 01 Nos

Single Leaf Steel Door without Panic Bar

Sr. No	Description	Steel Door
1	Description	General Purpose Steel (HMPS) Doors Single Leaf Hinge Type 0.80 mm thick M.S. Sheet cladded 40mm thick shutter infill material as Honeycomb complete with M.S. frame (Single Rebate – 100 x 57mm) made from 1.20mm thick M.S. Sheet & Fixing arrangements. Finish – Paint Finish.
2	Door Size	1200mm (W) x 2100mm (H)
3	Accessories	S.S. Ball Bearing Hinges - 04 nos
		S.S. 'D' Type Handle - 01 Nos
		Dead Lock with Cylinder - 01 Nos
		Vision Panel with Non - Fire Rated Glass of Size: 200 x 300mm (6mm Thick Clear Toughened Glass) - 01 Nos
		Heavy Duty Door Closer – Dorma Make TS 68

NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk,
MIDC, Chinchwad.
Pune – 411019

An ISO 9001:2015 Certified Company

GST Pune : 27AAECN0437H1ZM

C) General Conditions

1 Installation will start after receiving of Site Readyness Photographs or written Email communication.

2 We will mobilize the Installation Team in 3 - 4 working days, after reciept of Site Readyness Confirmation

3 For any reason if we need to stop our Installation and demobilize the Team without completing the Work, then extra cost will be applicable for Remobilizing the Team.

4 If Lifting Equipements are in NIHVA Scope, then those will be used for Installation purpose only and not for any other works.

Note: Please find below List which are in Client Scope

Sr. No	Description
1	Secured and fully covered Store area to keep the material
2	Scaffolding/Hydra/Crane/Forklift Etc - Required for Installation at Site
3	Electrical Supply on the site single phase/three phase points at different places.
4	Any civil / masonry/structural work required
5	All structure support required
6	In Case of any changes in the layout as per site requirements after the shipment of material , the additional quantities and the wastage.
7	Conduits, Cables required

D) Terms & Conditions

Price : Ex Works Pune

Delivery : 8 - 9 weeks from the date of receipt of confirmed purchase order, Advance Payment & Drawing approval.

Payment : 80% Advance along with Confirmed Purchase Order & Balance before dispatch.

Validity : Validity of Offer is 15 days from the date of quotation

Warranty : 12 months from the date of supply.

Please feel free to Contact **Mr. Ravindra Kharat on 7410169333** For any further Clarification /Information in this Concern.

With Best Regards
Shailesh Bhoir
8551091333
For NIHVA Technologies Pvt Ltd