The modular Door Control System Albany MCC

ASSA ABLOY

ASSA ABLOY Entrance Systems

The global leader in door opening solutions



ASSA ABLOY, Besam, Crawford, Albany and Megadoor, as words and logos, are examples of trademarks owned by ASSA ABLOY Entrance Systems or companies within the ASSA ABLOY Group.

ASSA ABLOY Entrance Systems is a leading supplier of entrance automation solutions for efficient flow of goods and people. With our globally recognized product brands Besam, Crawford, Albany and Megadoor, we offer products and services dedicated to satisfying end-user needs for safe, secure, convenient and sustainable operations.
ASSA ABLOY Entrance Systems is a division within ASSA ABLOY.

assaabloyentrance.com

Albany MCC The innovative control system



MODULARITY
Unlimited expansion possibilities and a great scope for utilization. Extensive settings via the software parameters and the optional extension modules create a highly versatile adaption of the control utilization.

VECTOR CONTROL
The revolutionary MCC control with vector contolled frequency converter ensures smooth optimal acceleration to top speed and optimal life time for every door type and size. That together with a power boost when starting the movement gives you an outstanding door performance.

CUSTOMISATION
Standard configurations for every door type allow for a fast and simple use of the control unit. Individual customer requirements can be met via the parameterization possibilities of most of the in- and outputs. Special functions, which are not included in the standard parameters, can be generated via the integrated PLC tool, creating an almost unlimited scope for functions.

EFFICIENT CONTROL PLATFORM
The MCC control unit is based on an efficient hardware and software platform, which provides the basics for the versatile use of the standard version of the control unit. This ensures permanent availability of the door and optimal spare part handling.

INTEGRATED DESIGN
The compact design, the usual installation near the drive unit and the option to integrate the MCC in many door types enable a visually appealing and optimal installation of the MCC on the door and provide electromagnetic compatibility.

POWERFUL USER INTERFACE
A user-friendly graphic display with plain text instructions supported by graphic symbols for the start-up, maintenance and troubleshooting. The user guide of the display is available in several languages or can be customised.

FREQUENCY CONVERTER ALBANY MCC	
Material for housing	Anodized aluminum
Size control box, excluding glands and endplates (W x H x T)	220 × 380 × 100
Supply voltage	3~ PE; 50 – 60 Hz 220 – 480 V -10% / +5% Transformer necessary for 220/230/500V
Temperature range for operation	-20°C – +40°C -20°C – +45°C machine protection doors
Protection	IP 55
Supplied fuse protection	10 – 16 A, B or C characteristic or comparable
Control voltage	24 V DC
Cross section mains connection	max. 2,5 mm²
Connections	pluggable
Control unit with graphical display and up/down/stopp keys	✓ • at machine protection (MP)
Potential-free contacts	•
Fieldbus interfaces	•
Emergency stop	✓
Airlock function	✓
Interlock function	✓
2. opening height	✓
Traffic light function	✓
Flashing light function	✓
Permanent opening function	✓
Accessoires	
MCC Extension box	• 220 × 165 × 100
Combi box: Plastic Plastic (at MP) Steel painted / Inox	 • 160 × 250 × 120 • 175 × 250 × 150 • 200 × 300 × 155
MCC in control box	• 500 × 500 × 210
Emergency power supply (UPS)	• 380 × 380 × 210 (Separate data sheet)

• Option ✓ Standard
Dimensions in mm

ASSA ABLOY Entrance Systems

info.aaes@assaabloy.com
assaabloyentrance.com

Follow us:

Please enter *ASSA ABLOY Entrance* in the channel's search field.

© ASSA ABLOY Entrance Systems AB PL.MAN/Albany MCC/DEU.EN-1.1/1603/64 05 R 0930 Technical data subject to change without notice