Tripod Turnstile



Tripod Turnstile

Tripod turnstiles are compact and cost-effective entrance solutions. Designing for smooth and silent operation, reducing power consumption, wear and tear. It is suitable for areas with a high traffic.

Our stainless steel compact version, offer high operating reliability in a small casework, ideal for sites where space is an issue. It has two passage channels in one casework, it is cost- effective for the application.

On receiving a signal from the access control system, or push button, it allows the passage of one person at a time. Passage in both directions is electronically controlled. Default mode is to lock the mechanism until a valid authorization signal is received. If you want to set one side free, you can have it by adjusting the mechanism. In case of emergency, the horizontal arm will drop to allow free passage.

Features



Reliability

- Alloy steel tripod hub prevents mechanical wear
- Casework and tripod arms manufactured in SS304 stainless steel
- Electromagnets for lock are used only when being activated. They are in standby mode when the device is idle.
- ZK patented compact mechanism ensures the long life of the lubricating oil inside.
- High quality electrical components






Safety and humanization design

- Drop arm designed for emergency purpose
- No exposed screws, safer for the user.
- Smooth operation designed for mas transit application
- The pictogram on the device indicating access permission and direction of movement
- Special designed case shape, user-friendly for passenger to punch card or finger.
- Anti-tailgate
- Well-designed electronic protection cover..

Easy integration

- Flexible reader installation plate. Customers can easily integrate with third party reader
- Standard electrical interface for third party device.
- By using compact mechanism, the turnstile has more space inside for integration





Specifications

Power Supply	AC 220V/110V, 50/60Hz
Operating Temperature	-28 °C- 60 °C
Operating Humidity	5%-85%
Working Environment	Indoor
Rated Power	60W
Flow Rate	25- 48 passage/minute
Casework Material	SUS304
Pictogram Indication	Yes
Control System	Input controlled by dry contact
Emergency Button Input	Yes
Dimension	60×98×33(CM) + arm length 50CM
Package Dimension	73×108×45(CM)
Net Weight	55KG
Gross Weight with Package	63KG
Optional Function	Alternative material or shape, third-party access control integration,
	ticket system integration, passage counter

Dimensions (mm)

