Sr No	Technical Specification for Double Wall Rolling Shutter
1	Thermal Insulation : Shutter infill of 20 mm PU rigid foam ensuring excellent thermal insulation
2	Side guide Protection : Black plastic strips on the edge of the side guides protect against abrasion and ensure longevity of shutters
3	Closing edge Safety device (only for Motorized) : Sensor controlled safety devices to monitor the bottom edge of the door. Instant stoppage and reversing on encountering any obstruction while closing .
4	• Fixing Material : Screw and Acncor Fastrener, GI Box Guide
5	• Sealing : Rubber seals are provided to reduce friction and sound, thereby ensuring a smooth door travel
6	• Door Curtain : GI PKP
7	• Support Brackets : MS
8	• Space Requirement (in mm) : Head room (S) = 500mm, 350 Motor INS. Hood Cover Bearing 150mm.
9	• Minimum requirement for Building Structure : Concrete = 140 mm (Min strength M10) , Steel = 5 mm, Brick work = 240 mm (Min strength 100 kg/cm2
10	• Side Guides : GI Guide with Rubber Brush
11	• Bottom Profile : MS with EPDM Gas Kit
12	• Seals : Bottom seal made of EPDM profile
13	Operator : Shaft operator, Ready to fit shaft operator, Power Input - 1 phase current 0.25 kW, Protection category IP65 (jet water protected)
14	Control : Integrated microprocessor control along with operator, Adjustable force limit and connection cable with CEE male plug in protection category IP 44, Push button on both side.
15	Standard accessories : With Crank Handle
16	Push Button : For Automatic Door