Aluminum High Performance Door

RapidRoll® 3000 ISO



Door type	RapidRoll® 3000 ISO	PL. indicate your requirement
Description	**Aluminum High Performance Door, opening in vertical direction, for interior and exterior use**	
Self-supporting side frames	**side frames** of edged galvanized steel profiles. springs for curtain tension and counterbalance in the side frame.	
Door curtain	**curtain** of ecru anodized double walled aluminium lamellas with additional insulation chamber made of PVC on the inner side of the door (colour RAL 7035), thermally separated, hingeless connected by means of flexible heavy belts, wear-less to wind up without to contact each other, each single lamella can be replaced easily, pre-fitted on the top roll.	
U value of the lamella	1.0 W/m^2K	
U value for the complete door	(e.g. 4 x 4 m) 2.1 W/m^2K	
Wind resistance	class 3-4 (EN 12424)	
Drive unit	gear motor, pluggable electrical connections	
Protection	IP 55	
Control system	MCCVectorControl, with vector control technology and boost function at start-up. Graphic display and foil keypad for easy guided operation. Easy access to all important information for operation and service	
control voltage	24 V DC	
Supply voltage	3L/(N)PE 380/400/415/440V; 50/60 Hz Transformator necessary for 230/480/500V; 50/60 Hz.	

Safety devices:	patented, contact-free pre-running safety photocell (transmitter/receiver) stationary safety photocell (transmitter/receiver) drop down protection by integrated balancing system	
Manual activation	by releasing the brake at ground level. Partly opening by means of the pre-stressed tension springs.	
Opening / closing speed	up to max. 2.0/0.6 m/s	
Size max.	(DW x DH): 6000 x 5000 mm	
Make	ALBANY RapidRoll® 3000 ISO	
Options:		
Covers	Top roll cover made of anodized aluminum Motor cover made of anodized aluminum	
Surface/material	Side frames with covers made of anodized aluminum Side frames coloured Aluminum lamellas coloured	
Miscellaneous	Aluminum lamellas with windows extended flexible seal Actuators Additional safety devices	
Delivery	**Installation incl. wiring**	