Opening doors
to business and life

ASSA ABLOY Entrance Systems

ASSA ABLOY
NIHVA
NIHVA Technologies Pvt. Ltd.
The global leader in door opening solutions

Project	**Renata Precision**
Location	**Pune**
Application	**Heavy Industry**
Our ref.no.	**220-076**
Calculated	**19-3-2020 16:21**
Notes	

System summary

Calc by	Ashish Nair
Version	V 9-3-2020 15:09:57 4623
Revision	
Identical doors	1
Total weight	2162 kg
Shipping weight	3106 kg
Shipping volume	19,95 m³
Environment	Megadoor Standard
Nominal current	8,3 A
Total power	3,8 kW
Hoist peak current	35,9 A
Voltage/Frequency	400 V 50 Hz
Control panel	none
Control panel	Basic Cabinet, 500x600x250 (9A nom.)

Options selected

- Back-up power switch
- Audible and visual alarm
- Beam clamps
- Allow different sizes

Door Lower & (1) options selected

- Shop-built door leaf
- Colored clamp strip on inside
- Colored clamp strip on outside

Door Lower & (1)

CW	8960 mm
CH	5769 mm
Depth	160 mm
Differential pressure	1 kPa (20,9 psf)
Leaf height	6850 mm
Top of crane rail	6750 mm
Total width	9200 mm
Guide shoe load	5,0 kN
Leaf fabric outside	Standard fabric, Colour TBC
Leaf fabric inside	Standard fabric, Colour TBC
Moving weight	667 kg
Total weight	778 kg
Bottom seal	EPDM Grey 400 mm

Door Upper & (2) options selected

3-phase breaker	auto-yes

- Metal trim motor side
- Colored clamp strip on inside
- Colored clamp strip on outside
- Forced profile 160

Door Upper & (2)

CW	10160 mm
CH	1981 mm
Depth	290 mm
Differential pressure	1 kPa (20,9 psf)
Leaf height	2893 mm
Total height	3363 mm
Total width	10400 mm
Guide shoe load	4,0 kN
Leaf fabric outside	Standard fabric, Colour TBC
Leaf fabric inside	Standard fabric, Colour TBC
Hoist	1 * SK 973.1Z-100LA/4
Open time	41 sec
Moving weight	1535 kg
Total weight	2162 kg
Bottom seal	EPDM Grey 600 mm