EQUIPMENT SPECIFICATION FOR HYDRAULIC SCISSORS LIFT

Hydraulic Scissor Lift Table with a Hydraulic Cylinder Having fully hard chrome plated with all PU seals with lifelong reliability: The Electro Hydraulic power pack consists of oil reservoir, oil level indicator, suction strainer, gear pump, electric motor DOL starter, Pressure relief valve and solenoid operated directional control valve flow control valve, on a common base.

Top & Bottom Frame Structure should be distortion free and scissor assembly made from heavy duty steel profile.

Dimensions of lift should be designed to meet the Tender drawing requirement and in such a way that the height requirement between 700mm to 1500 mm from FFL based on the carrier is also met.

TYPE	:	Hydraulic Scissors lift
CAPACITY	:	2000 Kgs
MOUNTING	:	Pit mounted
PLAT FORM SIZE	:	2500 L X 2500 W in mm
PIT SIZE AVAIABLE	:	2500 L X 2500 W in mm
CLOSED HEIGHT	:	*
TRAVEL HEIGHT	:	1.5 MTR from FFL. + 10% Extra height
TOTAL LIFT HEIGHT	:	*
NO OF STOPS	:	Inching feature required
CONTROL PANEL	:	To be provided
MOTOR	:	* (Non-flame proof)
LIMIT SWITCH	:	To be provided
HYDRAULIC POWER PACK	:	* Location to be submitted along with the BID
SAFETY FEATURES	:	All safety features related to scissors lift to be considered as a scope of supply. The vendor should provide the hydraulic hoses between the scissor lift and the hydraulic pack. The location of the hydraulic pack

should be indicated in the Tender drawing. The route and length of hose required to be specified including bends, vertical rise and drop along with GA drawing to be submitted with the BID. Hand rail guard to be provided for both sides of the platform. Loading lip required towards loading and unloading side. Loading pattern to be 180 degrees for loading and unloading side.

CIVIL REQUIRMENT : Civil requirement like pit details, foundation details to be provided by vendor.

Civil execution shall be done by civil contractor.

ELECTRICAL REQUIREMENT : 2 no's push buttons control stations both operated from top of lift and from remote for upward and download motion. All electrical accessories required for installation to be considered as vendor Scope of supply. Client shall provide only power at one single point. The vendor must indicate the power requirement along with input details.

Accessories like Lip welded assembly, All around removable/ retractable type railing.

QUANTITY : **4 Nos.**

All electrical accessories to be Non-flame proof.

'*' Vendors to provide information.

Note: ±10% Buffer to be considered for Travel height.