Sr. No	Description	Albany make Machine Protection Door RP300
1	**Door version:**	Vertical Rapid Roller Door for machine protection
2	**Side Frames:**	Aluminum anodized two parts, to have easy access to switches and service.
3	**Door blade:**	Curtain RollTex Original (silicone-free) without window, according to the following RAL colour- orange (2009)
4	**Bottom beam**	Aluminium anodized.
5	**Drive unit:**	Drive unit IP 55, LH side, with control cable (standard length = height of door)
6	**Opening / closing speed:**	Approx. max. 2,0 / 1,2 m/s
7	**Control system:**	MCC Frequency converterVector Control for opening/closing speed up to 2,4 / 1,4 m/s for door with safety contact edge, protection IP 55. Without display, interface card delivered separately, including power- and interface cable, with main switch in separate box.
8	**Power suppy:**	3L(N)PE 380/400/415/440/460 and 480 V, 50/60 Hz
9	**Safety features:**	Safety edge with cable chain integrated in side frames, door line photocell (Transmitter / Receiver) inside side frames, emergency crank and mechanical drop-down protection.
10	**Safety limit switch:**	1 Schmersal safety limit switch PL e EN ISO 13849-1, SIL 3 EN 62061 on drive side integrated in the side frame to save space.
11	**Display**	Display "Up-Stop-Down"
12	**Motor Position**	Left Hand Side
13	**Interface Card**	MCC without display unit, with combibox in plastic (175x250x150 mm) with interface card and main switch included in combibox, including power- and interface cable.
14	**Top Roll material**	Aluminum
15	**Top Roll Cover**	Made of aluminum
16	**Motor Cover**	powder coated standard
17	**Packing**	Box, Heat Treated
18	**warranty**	1 Year
19	**CE Sign**	Yes
20	**Documentation language**	English
21	**Documentation Control System**	English
22	**MCC Display Language**	English

Tech Specs are ok

31/03/2023