GEARBOX

SERIES	A - Series Bevel Gearboxes
SIZE	60 - Mn2=2800Nm/Tn2=24800LbIn
REDUCTIONS	4 - 4 Reduction Stages
VERSION	UR - Metric Single Solid O/P Shaft
GEAR RATIO	404.7
INPUT CONFIGURATION	P90 - Metric Motor Adaptor IEC 90
MOUNTING POSITION	VA

MOTOR

PRODUCT SERIES	BX - AC IE3 Three Phase Motor
FRAME SIZE	90S - Motor Size 90S
POLE NUMBER	4 - 4 Poles
VOLTAGE-FREQUENCY	230/400-50 - 230 [V] Δ - 400 [V] Y 50 [Hz]
DEGREE OF PROTECTION	IP55 - Standard and Brake Motors
INSULATION CLASS	CLF - Standard Insulation Class
MOUNTING	B5 - B5 Motor Mounting Flange

TECHNICAL DATA

Measurement Internat. System	METRIC
n2 Output Speed [min-1]	3.5
Mn2 Output rated torque [Nm]	2665
Rn2 Output OHL [N]	30000
Gearb.Mom.Inert.(•10-4) [kgm2]	N/A
sf Service factor	1.1
Output Shaft Dimensions	Ø60 h6 x 105 mm
Frequency [Hz]	50
n Motor Speed [min-1]	N/A
Mn Motor Nominal Torque [Nm]	N/A
Tn Motor Nom. Torque [lb-in]	N/A
η100 Efficiency 100% [%]	N/A
η75 Efficiency 75% [%]	N/A
η50 Efficiency 50% [%]	N/A
Cosφ	N/A
Pn Motor Nominal Power [kW]	1.1
Pn Motor Nominal Power [Hp]	1.5
Pn-60 Motor Nominal Power [kW]	N/A
Pn-60 Motor Nominal Power [Hp]	N/A

Gearmotor Weight [Kg]	106.0
Oil Quantity [l]	19.000