NIHVA
NIHVA Technologies Pvt. Ltd.

PRE DISPATCH INSPECTION REPORT

Format no.: NIHVA- QA-F-07	
Rev. no.: 00	
Rev date:	
Date of origin: 01.01.2017	

Client Name- Unique Constrcution Engineers & Contractor

Project Name- Rolling shutter | **Location -**Shop | **Date-13-07-2024 & 15-07-2024**

Product Name- Motorised 1 mm GI Single Skin Rolling Shutter (W 3000 X H 5500) | **Qty-**01 NOS

Sr.No	Part Name	Drawing no.	Specification	Observation			Instrument used	Status	Remark
				1	2	3			
1	Curtain	Curtain Length	3150	3150	3150	3150	Steel tape	OK	Accepted
		Curtain width	75	79	80	79	DVC	NOK	Deviation required
		Curtain Thickness	1	2	2	1.99	DMM	NOK	thickness measure after powder coating
		Curtain Profile	Curved	Flat			Visual	NOK	Deviation required
2	Roller shaft	Roller Length	3000	3000			Steel tape	OK	Accepted
		Roller dia.	140	140			DVC	OK	Accepted
3	Hood cover	Hood cover Length	3700	3700			Steel tape	OK	Accepted
		Dimension	299.69	325			Steel tape	NOK	Conditionally accepted
		Dimension	267.76	267			Steel tape	OK	Accepted
		Dimension	70.1	73			Steel tape	OK	Accepted
		Dimension	49.57	50			Steel tape	OK	Accepted
		Dimension	404.39	405			Steel tape	OK	Accepted
		Dimension	40	39			Steel tape	OK	Accepted
		Dimension	40	39			Steel tape	OK	Accepted
		Dimension	249.26	252			Steel tape	OK	Accepted
		Dimension	40	40			Steel tape	OK	Accepted
		Dimension	40	40			Steel tape	OK	Accepted
		Hood cover thickness	0.9	1			DVC	OK	Accepted
4	Motor bkt	length	500	500			Steel tape	OK	Accepted
		Dimension	450	440			Steel tape	OK	Accepted
		Dia	45	50			DVC	NOK	Approval/Deviation required
		dia	14	16			DVC	NOK	Approval/Deviation required
5	MS tube structure	length	6200	6240 mm	6240 mm		Steel tape	NOK	Conditionally accepted
		width	3000	3000			Steel tape	OK	Accepted
6	Support tibe length	Length	600	610	610		Steel tape	OK	Accepted
	MS plate 1	LxLxT	50x50x5 mm	50x50x6mm	50x50x6mm		DVC	OK	Accepted
7	MS plate 2	LxLxT	150x150x14	170x170x16 mm			DVC	NOK	Conditionally accepted
		dia	14	16			DVC	NOK	Conditionally accepted
8	Motor cover	length	600	600				OK	Accepted
		width	348,53	350				OK	Accepted
		height	375,59	350				NOK	Conditionally accepted
		Slot	100x100	100x100				OK	Accepted

Note-1)All dimensions are in mm 2) Tolerance used as per DIN ISO 2768 - mk

Remark -1)For NOK Dimension approval/Deviation rquired.
2) Motor plastic cover damage ,rework/replace required.

Inspected By- Sumit Jadhav

Approved By- Bheemappa Bandargal