A guide to preventative maintenance for Albany High Performance Doors

ASSA ABLOY

ASSA ABLOY Entrance Systems

The global leader in door opening solutions



Safety edge

What is the function?

- To protect people, goods and vehicles against closing forces
- To seal against floor for reduced energy loss
- To fulfill regulations regarding the safety of doors

What is the manufacturer's specification?

To make sure the manufacturer's specifications are observed, replace every:

- 5 years

Can I also replace it earlier?

- Yes, if there are visible signs of porosity, damage or deformation
- If there are increased peak forces
- If the rubber begins to stiffen
- Insensitivity of contact strip

How do they wear?

During the lifetime of the safety edge there will be wear and tear due to:

- The hardening and corrosion of the rubber profile
- The closing force on the contact strip and rubber
- Abrasion towards the side frame
- Crashes
- Cleaning agents
- Water contact, which leads to damage on the contact strip

What is the risk of not replacing?

When not following the manufacturer's specifications the customer is taking the responsibility for unintended breakdown, e.g.:

- Door stops working only hold-to-run mode is possible
- Closing forces become to high, failing to fulfill regulations, posing the potential for hazards
- Contact strip malfunctions
- Air leakage due to reduced sealing capabilities

Top reasons for preventive maintenance

- Keeps the warranty valid
- Prevents unexpected and expensive break-downs
- Prolongs lifetime
- Cost saving
- Minimises risk of personal injury
- Minimises energy loss
- Fulfills legal requirements
- Improves working environment

©ASSA ABLOY Entrance Systems AB/PL.MAP/DEU-EN-1.0/1504

Maintenance & Modernization