Motore *Motor*		Ingombri Principali *Main Overall Dimensions*						Piedi *Feet*								Flangia *Flange*						
JM	Pol.	AC	AD	H	HD	LB	L	A	B	C	AB	BB	AA	HA	K	IM	M	N_{j6}	P	LA	T	S
56 M	2 , 4	110	99	56	155	180	200	90	71	36	112	88,5	23	7,5	5,8	B5 B14	100 65	80 50	120 80	8 3	3 2,5	7 M 5
63 M	2 , 4	122	103	63	166	194	217	100	80	40	124	100	24,5	7,5	7,0	B5 B14	115 75	95 60	140 90	10 4	3 2,5	10 M 5
71 M	2...6	136	109	71	180	215	245	112	90	45	137	110	26	8	7,0	B5 B14	130 85	110 70	160 105	11 6	3,5 2,5	10 M 6
80 M	2...8	156	125	80	205	250	290	125	100	50	157	125	35	10	10	B5 B14	165 100	130 80	200 120	13 0	3,5 3	12 M 6
90 S	2...8	176	138	90	228	263	313	140	100	56	174	125	38	11	10	B5 B14	165 115	130 95	200 140	13 0	3,5 3	12 M 8
90 L	2...8					290	340		125			150										
100 L	2...8	197	152	100	252	325	385	160	140	63	197	172	40	12	12	B5 B14	215 130	180 110	250 160	14 0	4 3,5	14,5 M 8
112 M	2...8	219	174	112	286	345	405	190	140	70	227	180	41,5	12,5	12	B5 B14	215 130	180 110	250 160	15 7	4 3,5	14,5 M 8
132 S	2...8	260	194	132	326	390	470	216	140	89	264	186	51	15	12	B5 B14	265 165	230 130	300 200	15 7	4 3,5	14,5 M10
132 M						430	510		178			224										

Motore *Motor*		Estremità d'Albero *Shaft - End*					Tenute sull'albero [3] - *Shaft - Seals* [3]		Morsettiera *Terminal - Box*					
						Linguetta [2] *Key* [2]	Lato Flangia *Flange-end*	Lato Acc. B3 ; Lato opp. acc. *B3_Drive end ; N-drive end*	Morsetti *Studs*		Pressacavo *Cable Gland*			Cavo *Cable*
JM	Pol.	D	DB [1]	E	GA	F x GD x EB (b x h x l)	[$Ø_i$ x $Ø_e$ x H]	V-Ring [Øi x Øe x H]	N°	Ø	N°	KK	LD	$Ø_{max}$
56	2 , 4	9 j6	M4	20	10,2	3 x 3 x 14	12 x 25 x 7	10.5 x 16,5 x 5,5	6	M 4	1*	M 20 x 1,5	83	13
63	2 , 4	11 j6	M4	23	12,5	4 x 4 x 16	12 x 25 x 7	10.5 x 16,5 x 5,5	6	M 4	1*	M 20 x 1,5	92	13
71	2...6	14 j6	M5	30	16,0	5 x 5 x 25	15 x 30 x 7	12,5 x 18,5 x 5,5	6	M 4	1*	M 20 x 1,5	104,5	13
80	2...8	19 j6	M6	40	21,5	6 x 6 x 30	20 x 35 x 7	18 x 26 x 7,5	6	M 4	1*	M 20 x 1,5	116	13
90	2...8	24 j6	M8	50	27,0	8 x 7 x 40	25 x 40 x 7	22 x 30 x 7,5	6	M 4	1*	M 25 x 1,5	136	14,5
100	2...8	28 j6	M10	60	31,0	8 x 7 x 50	30 x 47 x 7	27 x 35 x 7,5	6	M 4	1*	M 25 x 1,5	142	14,5
112	2...8	28 j6	M10	60	31,0	8 x 7 x 50	30 x 47 x 7	27 x 35 x 7,5	6	M 5	2**	M 32 x 1,5	130	20
132	2...8	38 k6	M12	80	41,0	10 x 8 x 65	40 x 62 x 7	36 x 46 x 9	6	M 5	2**	M 32 x 1,5	157	20

[1] Filettatura del centro.

[2] Linguetta arrotondata - forma "A" - secondo UNI 6604-69, DIN 6885-1. Dimensioni F x GD x EB secondo EN 50347, fatta eccezione per la lunghezza EB sui motori JM 80 e JM 132.

[3] **Lato accoppiamento:**
- costruzione con flangia: anello di tenuta a contatto circolare-radiale;
- IM B3: tenute a contatto piano frontale (V-ring).

Lato opposto accoppiamento: tenute a contatto piano frontale (V-ring).

* N° 1 pressacavo + N° 1 foro filettato con tappo su lato opposto scatola morsettiera.

** N° 2 pressacavi sullo stesso lato della scatola morsettiera.

[1] *Thread of centre.*

[2] *Rounded key type "A" according to UNI 6604-69, DIN 6885-1. Dimensions F x GD x EB according to EN 50347, except for the length EB on motors JM 80 and JM 132.*

[3] ***Drive end:***
- *flange mounting: seal ring with radial-circular contact;*
- *IM B3: seals with frontal-plane contact (V-ring).*

Non-Drive end: *seals with frontal-plane contact (V-ring).*

** N° 1 cable gland + N° 1 threaded hole with cap on the opposite side of the terminal-box.*

*** N° 2 cable glands on the same side of terminal box.*