# High Performance Door Rapid Roll® 300 Plus (High Speed Door)



| Door type | RR300 Plus | PL. indicate your requirement |
|---|---|---|
| **Description** | Flexible High Performance Door, opening in vertical direction for interior use in wind-protected areas | |
| **Side frames** | Made of aluminum | |
| **Door curtain** | Made of transparent PVC with fabric reinforcement stripes, ultramarine (similar to RAL 5002) or red (similar to RAL 3002). | |
| **Top roll** | Made of anodized aluminum | |
| **Wind protection** | wind tabs on the door curtain | |
| **Wind resistance** | Class 1 (EN 12424). | |
| **Bottom profile** | anodized aluminum | |
| **Drive unit** | Hollow shaft gear motor | |
| **Protection** | IP 55 | |
| **Control system** | ACS 50, electronic control system with mini contactors including main switch and open-stop-close switch, control voltage 24 V DC | |
| **Supply voltage** | ACS 50: 3L(N)PE/230/380/400/415V, 50Hz<br>Transformer necessary for 440/480/500V 50Hz | |
| **Safety devices** | electrical safety contact edge, evaluation via integrated cable chain, door line photocell in the side frames, drop down protection by integrated balancing system | |
| **Manual activation** | By releasing the brake at ground level. Depending on width/height ratio the door opens up to max. 2.0 m | |
| **Opening / closing Speed** | Up to max. 1.2 / 1.2 m/s. | |
| **Size max** | (DWxDH) 5000 x 5000 mm. | |
| **Make** | ALBANY RapidRoll® 300 Plus Alu | |
| **Options:** | | |
| **Surface / material:**<br>**Covers** | Top roll cover required for doors DH < 2500 mm<br>Motor cover required for doors DH < 2500 mm | |



**91 8551008333 ☎ +91 20 66304033**

**Email: marketing@nihva.com**

| | | |
|---|---|---|
| **Door curtain (alternatively):** | PVC with coloured reinforcement stripes:<br>➢ Beige (similar RAL 1014),<br>➢ Yellow (similar RAL 1021),<br>➢ Orange (similar RAL 2011),<br>➢ Green (similar RAL 6018),<br>➢ White (similar RAL 9016) or<br>➢ Grey (similar RAL 7035).<br>➢ PVC with silicone-free reinforcement stripes – colour<br>➢ Blue (similar RAL 5010),<br>➢ Alu-grey (similar RAL 7037),<br>➢ Red (similar RAL 3002),<br>➢ Yellow (similar RAL 1021),<br>➢ Orange (similar RAL 2011),<br>➢ White (similar RAL 9010),<br>➢ Black (similar RAL 9005).<br>➢ Curtain made of RollTex® Plus – colour<br>➢ blue (similar RAL 5002),<br>➢ orange (similar RAL 2009) or<br>➢ grey (similar RAL 7001)<br>➢ Curtain made of RollTex® Original – colour<br>➢ Blue (similar RAL 5002),<br>➢ Orange (similar RAL 5002) or<br>➢ Grey (similar RAL 7001)<br>➢ Curtain made of NomaTex® – colour<br>➢ Grey (similar RAL 7038, varnishable on request)<br>➢ Window (DWxDH) 500x700mm (only for RollTex® or NomaTex®)<br>➢ Window (DWxDH) 700x500mm (only for RollTex® or NomaTex®)<br>➢ Vision panels for curtain NomaTex®<br>➢ Curtain made of NomaTex® flame retardant without vision panels or window- colour grey (similar RAL 7045)<br>➢ Curtain made of fabric type travitop - colour<br>➢ Blue (similar RAL 5010),<br>➢ red (similar RAL 3002) or<br>➢ grey (similar RAL 7035) | |

| | | |
|---|---|---|
| | ➢ vision panels for curtain type travitop | |
| **Control system (alternatively)** | Frequency converter control system MCC$^{VectorControl}$, based on vector control including boost function at start-up. Graphic display and foil keypad for easy guided operation. Easy access to all important information for operation and service,<br>➢ (open/close) up to max. 2,2/0,9 m/s,<br>➢ Supply voltage 3L(N)PE/380/400/415/440/480V;50/60Hz,<br>➢ Transformer necessary for 220/230/500V | |
| **Miscellaneous** | ➢ Knock-out capability with sensor, only for version with coil cable (without interior cable chain),<br>➢ Not possible in combination with integrated light curtain<br>➢ Integrated light curtain not possible in combination with knock-out function<br>➢ Automatic egress on power failure<br>➢ Extended flexible seal<br>➢ Actuators | |
| **Option: Escape and rescue routes** | | |
| **Size max.** | (DWxDH) 4000 mm x 4000 mm | |
| **Wind resistance** | class 1 (EN 12424) up to DH = 3500 mm, class 0 (EN 12424 at DH > 3500 mm | |
| **Control unit** | Solely frequency converter control MCC$^{VectorControl}$ with extension and special software (configuration). | |
| **Drive unit** | Hollow shaft gear motor with operating current brake | |
| **Emergency opening** | ➢ In case of power failure the door opens automatically, the door can be opened manually via the main switch/CEE plug<br>➢ A radar motion detector for the detection of people is included in delivery.<br>➢ Key switches for the deactivation of the escape and rescue function is optionally available. | |
| **Delivery** | Installation incl. wiring | |