MOBILE DOCK RAMP

NIHVA
We Make Possible



Detailed Product Description

Loading Capacity:	10000 KG	**Platform Length:**	3m
Max. Working Height:	1.6m	**Slope Length:**	5.5m
Overall Length:	10 m	**Overall Width:**	2.1m
Lip Plate Length:	0.4m		

Quick Detail:

Name	Mobile Dock Ramp	Brand Name	NIHVA
Loading Capacity	10000Kg	Color	AS PER RAL SHADE
Adjustable Working Height	1200mm-1600mm	Pump	Manual/Electrical/Both
Platform Length	3000mm	Power Supply	Manual/AC
Bridge Width	2100mm		

Description:

Mobile Dock Ramp is an auxiliary machine for loading and unloading cargos with forklift coordination use. The forklift can drive from the ground to the truck compartment to work directly through the Mobile Dock Ramp. There is no need to connect to power supply, for it uses manual hydraulic power. Only one man

needed to manipulate the machine to load and unload goods safely and fast. With it, you can save abundant labor-using, increase the efficiency of loading and unloading, and speed up the flow of goods, then get more economic benefits.

Main Features:

1.Reinforced gusseted lip
2.Heavy duty (6-8 box beams) deck construction
3.Non skid tread plate deck and lip
4.Full width one-piece lip hinges pin and tube
5.Heavy duty high pressure cylinders
6.First class hydraulic power unit, good seal capability and long life
7.Power is available in 1ph. 230V 3ph. 400V 50/60HZ
8. Forklift pick-up slot
9.The safety locking chains to attach yard ramp to the rear of vehicles
10. Brake pads to prevent yard ramp from moving when load or unload goods.

Safety Precaution:

- Have two hooks which can tighten the machine with vehicle during loading and unloading.
- Have two brake pads

Specifications/ Major Parameters:

Model: NIHVA-DR-10TON

- Loading Capacity 10000Kg
- Overall Length 10000mm
- Overall Width 2100mm
- Clear Width 2000mm
- LIP Plate Length 400mm
- Labial Plate Width 2000mm
- Adjustable Working Height 1200-1600mm
- Platform Length 3000mm
- Slope Length 5500mm
- Without Outriggers