## Technical Specification of Telescopic conveyor (good Year Tyres )

| Sr. no. | Description | Remark |
|---|---|---|
| 1 | Size of Conveyor | 19500 mm |
| 2 | Elongated length with no of boom | 12 mtr with 3 booms |
| 3 | Collapsed length | 7000 mm |
| 4 | Width of belt | 800 mm |
| 5 | Mechanical Structure | M.S. Powder coated (RAL 5022) |
| 6 | Type | Fixed (Grouted) |
| 7 | Speed of Conveyor | 0-30 mtr/min adjustable with VFD |
| 8 | Cycle time (for telescopic operation | 100 - 150 sec |
| 9 | Cycle time (for telescopic collapsing operation | 100 - 120 sec |
| 10 | Capacity of conveyor | 50 kg / mtr |
| 11 | weight of total system | 950 kg |
| 12 | Bearings | SKF |
| 13 | Conveyor belt | Derco (From Bindal) |
| 14 | Direction | Unidirectional (Reverse & Forward) |
| 15 | Roller guide with chain drive for telescopic operation | |
| 16 | Brake motor used in conveyor | 3 hp , 2HP |
| 17 | Make: | Bonfiglioli |
| 18 | Hydraulic lifting arrangement for conveying height adjustment | |
| 19 | Rigid piping of Hydraulic connections | |
| 20 | cable Routing through Flexible conduit | |
| 21 | Belt Tightening arrangement to avoid slagging in belt | |
| 22 | Led Light unit is mounted at front of boom to illuminate light | |
| 23 | Audible warning to alert operator of impending belt starts. | |
| 24 | Anti-collision strip fitted at the front of the boom which causes the machine to retract / Stop | |