High Speed Door - (European Components)		
• Safe & for continous operations		
• Smooth & silent opening & closing		
• Can be equipped with full vision PVC curtain		
• Modular Interchaegable panels permit to replace worn & damged panels		
Sr. No	**Description**	**Specifications**
1	Use	Internal Door
2	Speed	Inverter Motion system to adjust different speeds, with progressive control of acceleration & deceleration during braking
3	Opening speed	upto 3 m/s
4	Closing speed	0.8 m/s
5	Control Panel	4 Push Button operated
6	Security Features	EN 13241-1 Standard
7	Resistance to wind load	EN12424 upto class 1
8	Curtain	Fabric 1mm thick- RAL Colour 9002
9	Guide Material	Aluminum anodised
10	Hood & Motor Cover	Galvanised Steel - Included
11	Operator & Control	CE Certified German Make Motor
12	Connecting Voltage	220V , 1Ph , N
13	Open-Stop-Close Button	Standarad
14	Protection Category	IP 54
15	Power Consumption	0.75 kw Motor
16	Emergency Off Button	Standard
17	Closing Zone Monitoring	Optical Safety edge
18	Safety Device	Photocell
19	Emergency Opening	Crank Handle
20	Colour	RAL 9002
21	Controller	MR220 Controller with Inverter
22	Vision Panel	Required