Motorized Rolling Sutter



Door type	Motorized Rolling Sutter
Clear Opening dimension (w) -- x (h) --	1. (W)6045 x (H)5994 mm – 1 Qty
	2. (W)6077 x (H)5994 mm – 1 Qty
	3. (W)6782 x (H)6706 mm – 1 Qty
Opening Direction	Vertical - from bottom to Top
Mounting Location area	Inside area
Mounting Surface	Side Brackets: Steel Guides : Steel
Opening/Closing Speed	0.5 m/sec
Door Material	
material	GI
Panel	The panel made of 1mm thick GI
Profile	Corrugation
Bottom Profile	M. S. Plate 100 mm x 2.5 mm thick with angle stiffener with Rubber Bottom Seal
Side Guide Profile	MS Guide 100 X 3 mm thick
Roller Shaft	M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Dia - 100 to 300 mm as per w x h will vary
Side Brackets	MS Plate 5 mm thick , as per the opening dimension
Hood Cover	Made of GI Sheet Thickness 0.9 mm

Surface finish	
Painting	Two coats of epoxy primer & one coat of synthetic enamel paint.
Automation	
Control Type	Pulse Control with push button
Drive Unit & Mounting Type	Electric Motor (Imported) (single phase / three phase) - Indirect Mounting - Sprocket chain arrangement
Emergency Operation	Manual Chain
Operating Switch	Push Button from inside
Installation check points	Need to be check = space requirements + substructure + Mounting access + Access in the event of power cut

Structure too mount Rolling Shutter client scope