ASSA ABLOY

AUFTRAGSBESTÄTIGUNG/ ORDER CONFIRMATION

ASSA ABLOY Entrance Systems - Am Mondschein 25 - D-59557 Lippstadt

NIHVA Technologies PVT LTD 27 8/1 Coromant Housing Society 411044 Pune, Nigdi Pradhikar India	**Auftrags-Nr./Order No** 30789338 **Datum/Date** 2020-05-25 **Referenz/Reference** Mr. Patil **Verkäufer/Salesman**

Kunden-Nr./Customer No.	**Innendienst/Internal department**	**Versandart/Way of delivery**
1059669	Tatjana Rerich 02941/766-748	pick up Germany
Ihre Ust-ID Nr./Your TAX No	**Ihre Bestell-Nr./Your Order**	**Versandbedingungen/Terms of delivery**
	John Deere	FCA / Hemau, Germany / Forwarder (W)

Lieferadresse/Delivery address **Nr. Lieferadresse/Delivery address No.**	**Zahlungsbedingungen/Terms of payment**
NIHVA Technologies PVT LT1059669 27 8/1 Coromant Housing Society 411044 Pune, Nigdi Pradhikar India	Due Net 90

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price
10	**AD_RR5000**	**ASSA ABLOY RR3000 ISO**	**2020-07-09**	**1.000**	**ST**	**9,007.00**	**9,007.00**

Serien-Nr. 2701002798

Door type	RapidRoll 3000 ISO_
Daylight width	4.000 mm
Daylight height	4.500 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,1 m/s
Max. Closing Speed	0,7 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	3
Side frame version	Galvanised steel
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Top roll material	Top roll made of steel
Door curtain	Lamella type AI
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	4.500 mm
Light curtain	With light curtain integrated in the side frames
Photocell	Without photocell
Documentation language	English

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
Qty. window lamella	2
Window level	1.535 mm
CE - Sign	Yes
Packing	Box, heat treated
Warranty	1 Year
Dimension packing 1 LxWxH	4980X1150X1490
Dimension packing 2 LxWxH	5450X900X870

20 AD_RR5000 ASSA ABLOY RR3000 ISO 2020-07-09 1.000 ST 9,000.00 9,000.00

Serien-Nr. 2701002799

Door type	RapidRoll 3000 ISO_
Daylight width	4.500 mm
Daylight height	4.500 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,1 m/s
Max. Closing Speed	0,7 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	3
Side frame version	Galvanised steel
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Top roll material	Top roll made of steel
Door curtain	Lamella type AI
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	4.500 mm
Light curtain	With light curtain integrated in the side frames
Photocell	Without photocell
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
Qty. window lamella	2
Window level	1.535 mm
CE - Sign	Yes
Packing	Box, heat treated
Warranty	1 Year
Dimension packing 1 LxWxH	5480X1150X1490
Dimension packing 2 LxWxH	5450X900X870

30 AD_RR5000 ASSA ABLOY RR3000 ISO 2020-07-08 1.000 ST 9,000.00 9,000.00

Serien-Nr. 2701002800

Door type	RapidRoll 3000 ISO_
Daylight width	3.000 mm

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. / item	Produkt / Product	Beschreibung / Description	Versanddatum / Ship date	Anzahl / QTY	Einheit / Unit	Preis/Einh. / Price/Unit	Preis / Price

Daylight height	3.500 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,1 m/s
Max. Closing Speed	0,7 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	3
Side frame version	Galvanised steel
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Top roll material	Top roll made of steel
Door curtain	Lamella type AI
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	4.500 mm
Light curtain	With light curtain integrated in the side frames
Photocell	Without photocell
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
Qty. window lamella	2
Window level	1.535 mm
CE - Sign	Yes
Packing	Box, heat treated
Warranty	1 Year
Dimension packing 1 LxWxH	3980X1150X1490
Dimension packing 2 LxWxH	4450X900X870

40 AD_RR5000 ASSA ABLOY RR3000 ISO 2020-07-08 1.000 ST 9,000.00 9,000.00

Serien-Nr. 2701002801

Door type	RapidRoll 3000 ISO_
Daylight width	4.000 mm
Daylight height	5.000 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,1 m/s
Max. Closing Speed	0,7 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	3
Side frame version	Galvanised steel
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Top roll material	Top roll made of steel
Door curtain	Lamella type AI
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos.	Produkt	Beschreibung	Versanddatum	Anzahl	Einheit	Preis/Einh.	Preis
item	Product	Description	Ship date	QTY	Unit	Price/Unit	Price

Main switch	With main switch
Mains connection cable length	4.500 mm
Light curtain	With light curtain integrated in the side frames
Photocell	Without photocell
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
Qty. window lamella	2
Window level	1.535 mm
CE - Sign	Yes
Packing	Box, heat treated
Warranty	1 Year
Dimension packing 1 LxWxH	5040X1225X1570
Dimension packing 2 LxWxH	5950X900X870

50 AD_RR5000 ASSA ABLOY RR3000 ISO 2020-07-14 1.000 ST 9,258.00 9,258.00

Serien-Nr. 2701002802

Door type	RapidRoll 3000 ISO_
Daylight width	4.000 mm
Daylight height	4.500 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,1 m/s
Max. Closing Speed	0,7 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	3
Side frame version	Galvanised steel
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Top roll material	Top roll made of steel
Door curtain	Lamella type AI
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	4.500 mm
Light curtain	With light curtain integrated in the side frames
Photocell	Without photocell
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
Qty. window lamella	2
Window level	1.535 mm
CE - Sign	Yes
Packing	Box, heat treated
Warranty	1 Year
Dimension packing 1 LxWxH	4980X1150X1490
Dimension packing 2 LxWxH	5450X900X870

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

60 AD_RR5000 ASSA ABLOY RR3000 ISO 2020-07-14 1.000 ST 9,000.00 9,000.00

Serien-Nr. 2701002803

Door type	RapidRoll 3000 ISO_
Daylight width	4.000 mm
Daylight height	4.000 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,1 m/s
Max. Closing Speed	0,7 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	3
Side frame version	Galvanised steel
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Top roll material	Top roll made of steel
Door curtain	Lamella type AI
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	4.500 mm
Light curtain	With light curtain integrated in the side frames
Photocell	Without photocell
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
Qty. window lamella	2
Window level	1.535 mm
CE - Sign	Yes
Packing	Box, heat treated
Warranty	1 Year
Dimension packing 1 LxWxH	4980X1150X1490
Dimension packing 2 LxWxH	4950X900X870

70 AD_RR5000 ASSA ABLOY RR3000 ISO 2020-07-15 1.000 ST 9,000.00 9,000.00

Serien-Nr. 2701002804

Door type	RapidRoll 3000 ISO_
Daylight width	4.000 mm
Daylight height	4.500 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,1 m/s
Max. Closing Speed	0,7 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	3
Side frame version	Galvanised steel
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Top roll material	Top roll made of steel

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Door curtain	Lamella type AI
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	4.500 mm
Light curtain	With light curtain integrated in the side frames
Photocell	Without photocell
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
Qty. window lamella	2
Window level	1.535 mm
CE - Sign	Yes
Packing	Box, heat treated
Warranty	1 Year
Dimension packing 1 LxWxH	4980X1150X1490
Dimension packing 2 LxWxH	5450X900X870

80 AD_RR5000 ASSA ABLOY RR3000 ISO 2020-07-17 1.000 ST 9,000.00 9,000.00

Serien-Nr. 2701002805

Door type	RapidRoll 3000 ISO_
Daylight width	6.000 mm
Daylight height	6.000 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	1,6 m/s
Max. Closing Speed	0,6 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	2
Side frame version	Galvanised steel
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Top roll material	Top roll made of steel
Door curtain	Lamella type AI
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	4.500 mm
Light curtain	With light curtain integrated in the side frames
Photocell	Without photocell
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
Qty. window lamella	2
Window level	1.535 mm

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

CE - Sign	Yes
Packing	Box, heat treated
Warranty	1 Year
Dimension packing 1 LxWxH	7040X1225X1570
Dimension packing 2 LxWxH	6950X900X870

90 AD_RR5000 ASSA ABLOY RR3000 ISO 2020-07-16 1.000 ST 9,007.00 9,007.00

Serien-Nr. 2701002806

Door type	RapidRoll 3000 ISO_
Daylight width	4.000 mm
Daylight height	4.500 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,1 m/s
Max. Closing Speed	0,7 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	3
Side frame version	Galvanised steel
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Top roll material	Top roll made of steel
Door curtain	Lamella type AI
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	4.500 mm
Light curtain	With light curtain integrated in the side frames
Photocell	Without photocell
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
Qty. window lamella	2
Window level	1.535 mm
CE - Sign	Yes
Packing	Box, heat treated
Warranty	1 Year
Dimension packing 1 LxWxH	4980X1150X1490
Dimension packing 2 LxWxH	5450X900X870

Warenwert/Value of goods **81,272.00**

Summe/Total **EUR** **81,272.00**

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Wir danken für Ihren Auftrag Thank you for the order
Mit freundlichen Grüßen Best regards
Albany Door Systems GmbH

(Automatisch erstellt, daher ohne Unterschrift gültig
Written automatically, valid without signature)

Dem Auftrag liegen unsere allgemeinen, zur Zeit gültigen Verkaufsbedingungen zugrunde, die auch für alle weiteren Verträge Gültigkeit haben.
The order is based on our current general terms of sales, which will as well be applicable for all further contracts.

Die gesetzlichen durch die DSGVO geforderten Informationen zum Umgang mit Ihren personenbezogenen Daten erhalten Sie unter dem folgenden Link: https://goo.gl/qGzSw5

Sollten Sie keinen Zugang zum Internet haben, senden wir Ihnen gerne die Informationen postalisch zu. Bitte sprechen Sie uns ggf. unter Telefon: 02941/766-622 darauf an.

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye