A guide to preventative maintenance for Albany High Performance Doors

ASSA ABLOY

ASSA ABLOY Entrance Systems

The global leader in door opening solutions



Brake

What is the function?

- Stopping / holding door in open/close position
- Stopping the door in case of emergency
- Fulfill regulations regarding closing forces
- Inverted brake for doors in emergency exits (opening by power loss)

What is the manufacturer's specification?

To make sure the manufacturer's specifications are observed, replace every:

- FC-control 1.000.000 cycles
- Contactor control 500.000 cycles

Can I also replace it earlier?

- Yes, if there is slipping or a visible space between brake lining and friction plate larger than 0,2 mm

How do they wear?

During the lifetime of the brake there will be wear and tear due to:

- Friction / Abrasion of the brake lining
- Oil leakage of drive unit can damage brake
- Feather key groove due to forces
- No exact positioning in lower / upper position, due to reduced braking performance

What is the risk of not replacing?

When not following the manufacturer's specifications the customer is taking the responsibility for unintended breakdown, e.g.:

In a situation where the brake is damaged or worn out the closing forces may get too high, the opening and closing position may not be exact, the door may not stop or stop too late in an emergency or if the brake gets stuck, the door won't run.

Top reasons for preventive maintenance

- Keeps the warranty valid
- Prevents unexpected and expensive break-downs
- Prolongs lifetime
- Cost saving
- Minimises risk of personal injury
- Minimises energy loss
- Fulfills legal requirements
- Improves working environment

©ASSA ABLOY Entrance Systems AB/PL.MAP/DEU-EN-1.0/1504

ASSA ABLOY ENTRANCE SYSTEMS Maintenance & Modernization