NIHVA NIHVA Technologies Pvt. Ltd.	PRE DISPATCH INSPECTION REPORT	Format no.: NIHVA- QA-F-07 Rev. no.: 00 Rev date: Date of origin: 01.01.2017

Client Name- Rinac India Limited		**Report No--**
Project Name- High speed door	**Location-** NIHVA MANUFACTURING UNIT	**Date-25-03-2024**
Product Name- High speed door (W4500 mm X H4200 mm)	**Qty-**01 NOS	

Sr.No	Part Name	Parameter	Specification	Qty per Product	Observation			Instrument used	Remark
					1	2	3		
1	Shaft	Shaft Length	4910	1	4910	_	_	Steel tape	OK
2	Fabric	Fabric length	4300	1	4300	_	_	Steel tape	OK
		Fabric width	4600		4600	_	_	Steel tape	OK
3	Guide	Guide length	4700	2	4700	4700	_	Steel tape	OK
4	Hood cover	Hood cover Length	4720	1	4720	_	_	Steel tape	OK
		Hood cover width	350		350	_	_	Steel tape	OK
		Hood cover thickness	0.9		0.8	_	_	DMM	OK
5	Motor	TC Given						Visual	OK
6	Surface finish	Matched with RAL 7035						Visual	OK
		Coating Thickness	60-70µ		67µ	65µ	69µ	DFT meter	OK

Note-1)All dimensions are in mm 2) Tolerance used as per DIN ISO 2768 - mk

Inspected By- Maruti Yamgar

Approved By- Amit Kurhade

PUNE ★ NIHVA TECHNOLOGIES PVT. LTD.

NIHVA
NIHVA Technologies Pvt. Ltd.

PRE DISPATCH INSPECTION REPORT

Format no.: NIHVA- QA-F-07	
Rev. no.: 00	
Rev date:	
Date of origin: 01.01.2017	

Client Name- Rinac India Limited

Project Name- High speed door | **Location-** NIHVA MANUFACTURING UNIT | **Date-25-03-2024**

Product Name- High speed door (W3000 mm X H 3500 mm) | **Qty-**02 NOS

Sr.No	Part Name	Parameter	Specification	Qty per Product	Observation			Instrument used	Remark
					1	2	3		
1	Shaft	Shaft Length	3410	1	3410	3410	_	Steel tape	OK
2	Fabric	Fabric length	3600	1	3600	3600	_	Steel tape	OK
		Fabric width	3100		3100	3100	_	Steel tape	OK
3	Guide	Guide length	4000	2	4000	4000	4000	Steel tape	OK
4	Hood cover	Hood cover Length	3220	1	3220	3220	_	Steel tape	OK
		Hood cover width	350		350	350	_	Steel tape	OK
		Hood cover thickness	0.9		0.8	0.8	_	DMM	OK
5	Motor	TC Given						Visual	OK
6	Surface finish	Matched with RAL 7035						Visual	OK
		Coating Thickness	60-70µ		67µ	65µ	69µ	DFT meter	OK

Note-1)All dimensions are in mm 2) Tolerance used as per DIN ISO 2768 - mk

Inspected By- Maruti Yamgar

Approved By- Amit Kurhade

NIHVA TECHNOLOGIES PVT. LTD. PUNE

NIHVA
NIHVA Technologies Pvt. Ltd.

PRE DISPATCH INSPECTION REPORT

Format no.: NIHVA- QA-F-07
Rev. no.: 00
Rev date:
Date of origin: 01.01.2017

Client Name- Rinac India Limited | **Report No--**

Project Name- High speed door | **Location-** NIHVA MANUFACTURING UNIT | **Date-25-03-2024**

Product Name- High speed door (W3000 mm X H 3500 mm) | **Qty-**01 NOS

Sr.No	Part Name	Parameter	Specification	Qty per Product	Observation 1	2	3	Instrument used	Remark
1	Shaft	Shaft Length	3410	1	3410	_	_	Steel tape	OK
2	Fabric	Fabric length	3600	1	3600	_	_	Steel tape	OK
		Fabric width	3100		3100	_	_	Steel tape	OK
3	Guide	Guide length	4000	2	4000	4000	_	Steel tape	OK
4	Hood cover	Hood cover Length	3220	1	3220	_	_	Steel tape	OK
		Hood cover width	350		350	_	_	Steel tape	OK
		Hood cover thickness	0.9		0.8	_	_	DMM	OK
5	Motor	TC Given						Visual	OK
6	Surface finish	Matched with RAL 7035						Visual	OK
		Coating Thickness	60-70µ		67µ	65µ	69µ	DFT meter	OK

Note-1)All dimensions are in mm 2) Tolerance used as per DIN ISO 2768 - mk

Inspected By- Maruti Yamgar

Approved By- Amit Kurhade

NIHVA TECHNOLOGIES PVT. LTD. * PUNE *

NIHVA NIHVA Technologies Pvt. Ltd.	PRE DISPATCH INSPECTION REPORT	Format no.: NIHVA- QA-F-07 Rev. no.: 00 Rev date: Date of origin: 01.01.2017

Client Name- Rinac India Limited		**Report No--**
Project Name- High speed door	**Location-** NIHVA MANUFACTURING UNIT	**Date-25-03-2024**
Product Name- High speed door (W4500 mm X H4200 mm)	**Qty-**02 NOS	

Sr.No	Part Name	Parameter	Specification	Qty per Product	Observation			Instrument used	Remark
					1	2	3		
1	Shaft	Shaft Length	4910	1	4910	4910	_	Steel tape	OK
2	Fabric	Fabric length	4300	1	4300	4300	_	Steel tape	OK
		Fabric width	4600		4600	4600	_	Steel tape	OK
3	Guide	Guide length	4700	2	4700	4700	4700	Steel tape	OK
4	Hood cover	Hood cover Length	4720	1	4720	4720	_	Steel tape	OK
		Hood cover width	350		350	350	_	Steel tape	OK
		Hood cover thickness	0.9		0.8	0.8	_	DMM	OK
5	Motor	TC Given						Visual	OK
6	Surface finish	Matched with RAL 7035						Visual	OK
		Coating Thickness	60-70µ		67µ	65µ	69µ	DFT meter	OK

Note-1)All dimensions are in mm 2) Tolerance used as per DIN ISO 2768 - mk

Inspected By- Maruti Yamgar

Approved By- Amit Kurhade

NIHVA TECHNOLOGIES PVT. LTD. * PUNE *

NIHVA NIHVA Technologies Pvt. Ltd.	PRE DISPATCH INSPECTION REPORT	Format no.: NIHVA- QA-F-07 Rev. no.: 00 Rev date: Date of origin: 01.01.2017

Client Name- Rinac India Limited		**Report No--**
Project Name- High speed door	**Location-** NIHVA MANUFACTURING UNIT	**Date-25-03-2024**
Product Name- High speed door (W4500 mm X H4200 mm)		**Qty-**05 NOS

Sr.No	Part Name	Parameter	Specification	Qty per Product	Observation			Instrument used	Remark
					1	2	3		
1	Shaft	Shaft Length	4910	1	4910	4910	4910	Steel tape	OK
2	Fabric	Fabric length	4300	1	4300	4300	4300	Steel tape	OK
		Fabric width	4600		4600	4600	4600	Steel tape	OK
3	Guide	Guide length	4700	2	4700	4700	4700	Steel tape	OK
4	Hood cover	Hood cover Length	4720	1	4720	4720	4720	Steel tape	OK
		Hood cover width	350		350	350	350	Steel tape	OK
		Hood cover thickness	0.9		0.8	0.8	0.8	DMM	OK
5	Motor	TC Given						Visual	OK
6	Surface finish	Matched with RAL 7035						Visual	OK
		Coating Thickness	60-70µ		67µ	65µ	69µ	DFT meter	OK

Note-1)All dimensions are in mm 2) Tolerance used as per DIN ISO 2768 - mk

Inspected By- Maruti Yamgar

Approved By- Amit Kurhade

NIHVA TECHNOLOGIES PVT. LTD. * PUNE *

NIHVA Technologies Pvt. Ltd.	PRE DISPATCH INSPECTION REPORT	Format no.: NIHVA- QA-F-07
		Rev. no.: 00
		Rev date:
		Date of origin: 01.01.2017

Client Name- Rinac India Limited		**Report No--**
Project Name- High speed door	**Location-** NIHVA MANUFACTURING UNIT	**Date-25-03-2024**
Product Name- High speed door (W4500 mm X H4200 mm)		**Qty-**01 NOS

Sr.No	Part Name	Parameter	Specification	Qty per Product	Observation			Instrument used	Remark
					1	2	3		
1	Shaft	Shaft Length	4910	1	4910	_	_	Steel tape	OK
2	Fabric	Fabric length	4300	1	4300	_	_	Steel tape	OK
		Fabric width	4600		4600	_	_	Steel tape	OK
3	Guide	Guide length	4700	2	4700	4700	_	Steel tape	OK
4	Hood cover	Hood cover Length	4720	1	4720	_	_	Steel tape	OK
		Hood cover width	350		350	_	_	Steel tape	OK
		Hood cover thickness	0.9		0.8	_	_	DMM	OK
5	Motor	TC Given						Visual	OK
6	Surface finish	Matched with RAL 7035						Visual	OK
		Coating Thickness	60-70µ		67µ	65µ	69µ	DFT meter	OK

Note-1)All dimensions are in mm 2) Tolerance used as per DIN ISO 2768 - mk

Inspected By- Maruti Yamgar

Approved By- Amit Kurhade

NIHVA TECHNOLOGIES PVT. LTD. * PUNE *

NIHVA NIHVA Technologies Pvt. Ltd.	PRE DISPATCH INSPECTION REPORT	Format no.: NIHVA- QA-F-07 Rev. no.: 00 Rev date: Date of origin: 01.01.2017

Client Name- Rinac India Limited		**Report No--**
Project Name- High speed door	**Location-** NIHVA MANUFACTURING UNIT	**Date-25-03-2024**
Product Name- High speed door (W4500 mm X H3500 mm)		**Qty-**02 NOS

Sr.No	Part Name	Parameter	Specification	Qty per Product	Observation			Instrument used	Remark
					1	2	3		
1	Shaft	Shaft Length	4910	1	4910	4910	_	Steel tape	OK
2	Fabric	Fabric length	3600	1	3600	3600	_	Steel tape	OK
		Fabric width	4600		4600	4600	_	Steel tape	OK
3	Guide	Guide length	4000	2	4000	4000	4000	Steel tape	OK
4	Hood cover	Hood cover Length	4720	1	4720	4720	_	Steel tape	OK
		Hood cover width	350		350	350	_	Steel tape	OK
		Hood cover thickness	0.9		0.8	0.8	_	DMM	OK
5	Motor	TC Given						Visual	OK
6	Surface finish	Matched with RAL 7035						Visual	OK
		Coating Thickness	60-70µ		67µ	65µ	69µ	DFT meter	OK

Note-1)All dimensions are in mm 2) Tolerance used as per DIN ISO 2768 - mk

Inspected By- Maruti Yamgar

Approved By- Amit Kurhade

NIHVA TECHNOLOGIES PVT. LTD. * PUNE *

NIHVA NIHVA Technologies Pvt. Ltd.	PRE DISPATCH INSPECTION REPORT	Format no.: NIHVA- QA-F-07 Rev. no.: 00 Rev date: Date of origin: 01.01.2017

Client Name- Rinac India Limited		**Report No--**
Project Name- High speed door	Location- NIHVA MANUFACTURING UNIT	**Date-25-03-2024**
Product Name- High speed door (W3500 mm X H4200 mm)		**Qty-**01 NOS

Sr.No	Part Name	Parameter	Specification	Qty per Product	Observation			Instrument used	Remark
					1	2	3		
1	Shaft	Shaft Length	3910	1	3910	_	_	Steel tape	OK
2	Fabric	Fabric length	4300	1	4300	_	_	Steel tape	OK
		Fabric width	3600		3600	_	_	Steel tape	OK
3	Guide	Guide length	4700	2	4700	4700	_	Steel tape	OK
4	Hood cover	Hood cover Length	3720	1	3720	_	_	Steel tape	OK
		Hood cover width	350		350	_	_	Steel tape	OK
		Hood cover thickness	0.9		0.8	_	_	DMM	OK
5	Motor	TC Given						Visual	OK
6	Surface finish	Matched with RAL 7035						Visual	OK
		Coating Thickness	60-70µ		67µ	65µ	69µ	DFT meter	OK

Note-1)All dimensions are in mm 2) Tolerance used as per DIN ISO 2768 - mk

Inspected By- Maruti Yamgar

Approved By- Amit Kurhade

NIHVA TECHNOLOGIES PVT. LTD. * PUNE *