GIOTTO 60 BT

Barrier with 24V power supply for clear opening up to 6m and opening time 5 sec . Impact Resistance by means of encoder. Grey RAL 7015

TECHNICAL SPECIFICATIONS:

MOTOR:

Power supply	230V±10% 50Hz(*)
Power absorbed	250W (GIOTTO BT 60)
Internal lubrication	permanent grease
Max torque	350 Nm (GIOTTO BT 60)
Opening time	5s (GIOTTO BT 60)
Boom length	6 m (GIOTTO BT 60)
Manual mechanical release	customised key
Type of boom	Round
Limit devices	electrical incorporated and electronically adjustable
Type of use	semi intensive (GIOTTO BT 60)
Working temperature	from -20°C to +55°C
Degree of protection	IP 54
Operator weight (without boom)	41 Kg (GIOTTO BT 60)

CONTROL UNIT:

Mains/low voltage insulation	> 2MOhm 500V
Dielectric strength mains/low voltage	3750V~ for 1 minute
Supply to accessories	24V~ (180 mA max absorption)
Barrier-open warning light	24V~ 3W max
Blinker	24V~ 25W max
N° of combinations	4 billion
Built-in Rolling-Code radio-receiver	frequency 433.92MHz
Max. n° of remotes that can be memorized	63