ASSA ABLOY

AUFTRAGSBESTÄTIGUNG/ ORDER CONFIRMATION

ASSA ABLOY Entrance Systems - Am Mondschein 25 - D-59557 Lippstadt

NIHVA Technologies PVT LTD 27 8/1 Coromant Housing Society 411044 Pune, Nigdi Pradhikar India	**Auftrags-Nr./Order No**	30741034
	Datum/Date	2019-05-02
	Referenz/Reference	
	Verkäufer/Salesman	

Kunden-Nr./Customer No.	**Innendienst/Internal department**	**Versandart/Way of delivery**
1059669	Olga Ziebart +49.2941.766. x 746	Sea freight
Ihre Ust-ID Nr./Your TAX No	**Ihre Bestell-Nr./Your Order**	**Versandbedingungen/Terms of delivery**
	NVA-437	FCA / Hemau, Germany / Forwarder (W)

Lieferadresse/Delivery address **Nr. Lieferadresse/Delivery address No.**	**Zahlungsbedingungen/Terms of payment**
NIHVA Technologies PVT LT1059669 27 8/1 Coromant Housing Society 411044 Pune, Nigdi Pradhikar India	Due Net 90

Pos. **item**	**Produkt** **Product**	**Beschreibung** **Description**	**Versanddatum** **Ship date**	**Anzahl** **QTY**	**Einheit** **Unit**	**Preis/Einh.** **Price/Unit**	**Preis** **Price**
10	**AD_RP300**	**ASSA ABLOY RP300**	**2019-05-22**	**1.000**	**ST**	**3,950.00**	**3,950.00**

Serien-Nr. 2620002207

Door type	High-speed roller door RapidProtect 300
Daylight width	1.500 mm
Daylight height	2.500 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s
Max. Closing Speed	1,0 m/s
Control system position	Left
Motor Position	Left
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1.100 mm

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. / item	Produkt / Product	Beschreibung / Description	Versanddatum / Ship date	Anzahl / QTY	Einheit / Unit	Preis/Einh. / Price/Unit	Preis / Price

Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	3.000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

20 AD_RP300 ASSA ABLOY RP300 2019-05-22 1.000 ST 3,950.00 3,950.00

Serien-Nr. 2620002208

Door type	High-speed roller door RapidProtect 300
Daylight width	1.500 mm
Daylight height	2.500 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s
Max. Closing Speed	1,0 m/s
Control system position	Left
Motor Position	Left
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1.100 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	3.000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos.	Produkt	Beschreibung	Versanddatum	Anzahl	Einheit	Preis/Einh.	Preis
item	Product	Description	Ship date	QTY	Unit	Price/Unit	Price

Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

30 AD_RP300 ASSA ABLOY RP300 2019-05-22 1.000 ST 3,950.00 3,950.00

Serien-Nr. 2620002209

Door type	High-speed roller door RapidProtect 300
Daylight width	1.500 mm
Daylight height	2.500 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s
Max. Closing Speed	1,0 m/s
Control system position	Left
Motor Position	Left
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1.100 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	3.000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price
40	**AD_RP300**	**ASSA ABLOY RP300**	**2019-05-22**	**1.000**	**ST**	**3,950.00**	**3,950.00**

Serien-Nr. 2620002210

Door type	High-speed roller door RapidProtect 300
Daylight width	1.500 mm
Daylight height	2.500 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s
Max. Closing Speed	1,0 m/s
Control system position	Left
Motor Position	Left
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1.100 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	3.000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

50	**AD_RP300**	**ASSA ABLOY RP300**	**2019-05-22**	**1.000**	**ST**	**3,950.00**	**3,950.00**

Serien-Nr. 2620002211

Door type	High-speed roller door RapidProtect 300
Daylight width	1.500 mm
Daylight height	2.500 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s
Max. Closing Speed	1,0 m/s
Control system position	Left

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. / item	Produkt / Product	Beschreibung / Description	Versanddatum / Ship date	Anzahl / QTY	Einheit / Unit	Preis/Einh. / Price/Unit	Preis / Price

Motor Position	Left
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1.100 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	3.000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

60 **AD_RP300** **ASSA ABLOY RP300** **2019-05-22** **1.000** **ST** **3,950.00** **3,950.00**

Serien-Nr. 2620002212

Door type	High-speed roller door RapidProtect 300
Daylight width	1.500 mm
Daylight height	2.500 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s
Max. Closing Speed	1,0 m/s
Control system position	Left
Motor Position	Left
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

	monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1.100 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	3.000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

70	**AD_RP300**	**ASSA ABLOY RP300**	**2019-05-22**	**1.000**	**ST**	**3,950.00**	**3,950.00**

Serien-Nr. 2620002213

Door type	High-speed roller door RapidProtect 300
Daylight width	1.500 mm
Daylight height	2.500 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s
Max. Closing Speed	1,0 m/s
Control system position	Left
Motor Position	Left
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1.100 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. / item	Produkt / Product	Beschreibung / Description	Versanddatum / Ship date	Anzahl / QTY	Einheit / Unit	Preis/Einh. / Price/Unit	Preis / Price

Frequency	50 Hz
Motor cable length	3.000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

80 AD_RP300 ASSA ABLOY RP300 2019-05-22 1.000 ST 3,950.00 3,950.00

Serien-Nr. 2620002214

Door type	High-speed roller door RapidProtect 300
Daylight width	1.500 mm
Daylight height	2.500 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s
Max. Closing Speed	1,0 m/s
Control system position	Left
Motor Position	Left
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1.100 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	3.000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

90 AD_RP300 ASSA ABLOY RP300 2019-05-22 1.000 ST 3,950.00 3,950.00

Serien-Nr. 2620002215

Door type	High-speed roller door RapidProtect 300
Daylight width	1.500 mm
Daylight height	2.500 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s
Max. Closing Speed	1,0 m/s
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1.100 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	3.000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

100 AD_RP300 ASSA ABLOY RP300 2019-05-22 1.000 ST 3,950.00 3,950.00

Serien-Nr. 2620002216

Door type	High-speed roller door RapidProtect 300
Daylight width	1.500 mm

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Daylight height	2.500 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s
Max. Closing Speed	1,0 m/s
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1.100 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	3.000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

110 AD_RP300 ASSA ABLOY RP300 2019-05-22 1.000 ST 3,950.00 3,950.00

Serien-Nr. 2620002217

Door type	High-speed roller door RapidProtect 300
Daylight width	1.500 mm
Daylight height	2.500 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s
Max. Closing Speed	1,0 m/s
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. / item	Produkt / Product	Beschreibung / Description	Versanddatum / Ship date	Anzahl / QTY	Einheit / Unit	Preis/Einh. / Price/Unit	Preis / Price

Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1.100 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	3.000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

120 AD_RP300 ASSA ABLOY RP300 2019-05-22 1.000 ST 3,950.00 3,950.00

Serien-Nr. 2620002218

Door type	High-speed roller door RapidProtect 300
Daylight width	1.500 mm
Daylight height	2.500 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s
Max. Closing Speed	1,0 m/s
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Window Quantity	1
Height:bott.edge to bott.prof.	1.100 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	3.000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

130 AD_RP300 ASSA ABLOY RP300 2019-05-22 1.000 ST 3,950.00 3,950.00

Serien-Nr. 2620002219

Door type	High-speed roller door RapidProtect 300
Daylight width	1.500 mm
Daylight height	2.500 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s
Max. Closing Speed	1,0 m/s
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1.100 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	3.000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

140 AD_RP300 ASSA ABLOY RP300 2019-05-22 1.000 ST 3,950.00 3,950.00

Serien-Nr. 2620002220

Door type	High-speed roller door RapidProtect 300
Daylight width	1.500 mm
Daylight height	2.500 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s
Max. Closing Speed	1,0 m/s
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1.100 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	3.000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

150 AD_RP300 ASSA ABLOY RP300 2019-05-22 1.000 ST 3,950.00 3,950.00

Serien-Nr. 2620002221

Door type	High-speed roller door RapidProtect 300
Daylight width	1.500 mm
Daylight height	2.500 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s
Max. Closing Speed	1,0 m/s
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1.100 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	3.000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

160 AD_RP300 ASSA ABLOY RP300 2019-05-22 1.000 ST 3,950.00 3,950.00

Serien-Nr. 2620002222

Door type	High-speed roller door RapidProtect 300
Daylight width	1.500 mm
Daylight height	2.500 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

ASSA ABLOY

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Max. Closing Speed	1,0 m/s
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1.100 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	3.000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

Warenwert/Value of goods **63,200.00**

Summe/Total **EUR** **63,200.00**

Wir danken für Ihren Auftrag Thank you for the order
Mit freundlichen Grüßen Best regards
Albany Door Systems GmbH

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

(Automatisch erstellt, daher ohne Unterschrift gültig
Written automatically, valid without signature)

Dem Auftrag liegen unsere allgemeinen, zur Zeit gültigen Verkaufsbedingungen zugrunde, die auch für alle weiteren Verträge Gültigkeit haben.
The order is based on our current general terms of sales, which will as well be applicable for all further contracts.

Die gesetzlichen durch die DSGVO geforderten Informationen zum Umgang mit Ihren personenbezogenen Daten erhalten Sie unter dem folgenden Link: https://goo.gl/qGzSw5

Sollten Sie keinen Zugang zum Internet haben, senden wir Ihnen gerne die Informationen postalisch zu. Bitte sprechen Sie uns ggf. unter Telefon: 02941/766-622 darauf an.

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye