NIHVA make – Motorized Sliding Gate

Door type	Motorized Sliding Gate
Clear Opening gate dimension	(W) 7000 mm X (H) 1800 mm
Quantity	4 No
Opening Direction	**Horizontal - from left to right or reverse**
Mounting Location area	Inside area
Design Pattern	Standard Tubular Design Pattern
Outer Frame Tube Sizes	80 x 80 x 3.2 mm
Internal Vertical Tube Sizes	38 x 38 x 2.6 mm
Gap Between Tubes	100 mm C/C
Bottom Rail on ground	dia 20 mm round bright bar with heavy duty support ISMB 100 X 50 Beams
Bottom Rollers	Heavy Duty Bottom Wheel With both side Bearings (chorme plated)
Full Height Column sizes	100 x 100 x 3.2 mm
Guide Rollers supporter during Gate movement	**Nylon Rollers with Bearings both sides mounted on column for support smooth movement of gate**
Painting	Powder Coating
El motor	100% imported from Europe
Emergency Operation	Manual after turn the switch
Operating Switch	Push Button from inside
Safety	Photocells, Flashing Light
Metal Rack	Zinc plated metal rack
Installation Checks	need to be check = space requirements + substructure + Mounting access + Access in the event of power cut
Civil work	Client scope – client need to grout the I beam in concrete to create track for sliding gate