SECTIONAL DOORS	
Specification	**Crawford - NIHVA Assaabloy**
Door type	1042P
Clear Opening dimension	(W)3000 x (H)3000 mm
Opening Direction	Vertical
Type of Mounting	Vertical
Door produced Based on which certificatior	Doors produced according to ISO 9000 or ISO 14000 certified processes
Opening/Closing Speed	0,28/0,28 m/s
Door Material	GI Steel
Panel Thickness	42mm
Panel colour	RAL 9002 Powder coated
External surface of the panel	diamond grid design with a glossy finish at the section joints.
inside surface of the panel	Monolithic surface on the inside of the door
Broken cold bridge	Section joints with broken cold bridges
Panels are euipped with ?	Panels to have integrated steel reinforcement for fixation of hinges and hardware.
Door sealent	All door sealants made of EPDM rubber, temperature resistant -30/+70
All Panek height	All panels should be 545mm high
Panel Inside insulation metrial	Insulation material to be CFC free polyuretane foam.
Panel Flam Retardent standrad	Flame retardant polyurethane foam according DIN4102-class B2.
Steel component Material	All steel components to be electro galvanized
Hinge Material	Glass fibre reinforced Polyamide
Panel Thickness	42 mm
Spring Material surface finish	Powder coated
Spings transport till plant	Pre tensioned spring package
Water Penetration	EN 12425 class 3
Air Permealibity	EN12426 class 3
Wind Load	EN21424 class 3
Thermal Transittance	EN 12428 1.10W /m2K
Bottom sealing	Bottom of the door to be equiped with three lip sealing made of oil resistant EPDM rubber
Door saftey device 1	Doors equiped with spring break device
Door saftey device 2	Door equiped with pneumatic safety edge
Door saftey 3	Having hinges flush with the inside door surface is a safety feature that eliminates the risk of things or people getting caught by parts protuding from a moving door
Incase of Power failuer	Doors to be equiped with quick release fuction
Operator power conumption	**Operator to have a maximum power consumption of 0,37kW and a standby consumption of Maximum 15W**
Frequency converter	Built in Frequency converter
Drive Unit & Mounting Type	Single phase 230V direct drive on shaft
Emergency Operation	by Disengagement rope manual
Operating Switch	Up/Down Keypad + stopbutton
Environmental Green Product Declaration Certification	as per ISO 14025 and EN 15804