TECHNICAL SPECIFICATION:-

PRODUCT	GOODS LIFT MANUAL DOOR
CAPACITY	2500 KG
SPEED	0.25 M/S
CAR TRAVEL	G+4
NO OF STOPS	FIVE STOPS
NO OF OPENNG	FIVE OPENINGS (ALL OPENNING ON THE SAME SIDE)
DRIVE	NA
MAIN POWER SUPPLY SYSTEM	415 VOLTS, 3 PHASE, 50 HZ A.C. (CLIENT SCOPE)
LIGHT SUPPLY	230 VOLTS, SINGLE PHASE 50 HZ A.C. (CLIENT SCOPE)
MACHINE	HYDRAULIC TRACTION MACHINE
LANDING DOOR FINISH	MANUAL COLLAPSIBLE DOOR
CAR DOOR FINISH	MANUAL COLLAPSIBLE DOOR
DOOR OPENNING	1200 MM CLEAR DOOR OPENNING
CAR SIZE	1600MM WIDTH AND 2000MM DEPTH (SIZE CAN BE CHANGES AS PER GAD)
CAR FINISH	MILD STEEL POWDER COATED (MADE BY HIGH QUALITY PRECOATED SHEET)
CAR FLOORING	M.S. PLATE
FALSE CEILING	MILD STEEL POWDER COATED
HAND RAIL	NA
ELEVATOR ROPE	USHA MARTIN (DUAL STRENGTH)
ELEVATOR WELL	1800 MM WIDTH, 2500 MM DEPTH (INSIDE FINISHED)
MACHINE ROOM	AS PER REQUIRED
ELEVATOR PIT	500 MM DEPTH
SPEED GOVERNOR	NA
FIREMAN OPTION	NA
CONTROL SYSTEM	SIMPLEX DOWN COLLECTIVE CONTROL PANEL
CONTROLLERTYPE	MICROPROCESSOR BASE CONTROL PANEL
SIGNALS	1) UP/DOWN DIRECTION INDICATORS AT ALL LANDING 2) DIGITAL CAR POSITION INDICATORS