NIHVA TECHNOLOGIES PVT LTD

8/1 Coromant Housing Society, Sec. No. 27
Nigdi Pradhikaran , Pune- 411044, Maharashtra, India
Tel : +91 20 66304033 / 8551093333
Email : sales@nihva.com

PURCHASE ORDER

Supplier's Name and Address :	Purchase Order No.	Date
Teckentrup GmbH & Co. KG Industriestr. 50 33415 Veri-Surenheide Tel No. : +495246504182 Contact Person : Atilla Ozel Fax. No. :+495246504177	**NVA-530**	**10-08-2021**
	Reference : Quotation **2000163286** **Date - 09/08/2021** Project :	

We have pleasure to entrust you our order for the following Goods / Services to be rendered subject to the terms and conditions

Sr. No.	Item Description		QTY	Unit In	Rate / CURRECY	Total Value
1	**Roller shutter Thermo Teck (C) 153718 Size - 4.515 X 8.200 MM (W XH)** Double-skinned Teckentrup roller shutter made from PU-foamed steel profiles. outside of profiles- micro-profiled, inner surface "smooth" w groove (curve). For outer rollers the actual inside is visible on the outside! Micro-profiling then inside. Refer attached Annexure A for more details		10	Nos	5007.39 Euro	50073.90
					Total Euro	**50073.90**

Terms & Conditions :

Payment Term	:50 % advance , 50 % before dispatch of material
Delivery Schedule	4 weeks
Incoterms	:Ex- Works Prices are inclusive of documentation charges, loading r & packing.
Special Note	By Sea
Transshipment: Allowed/ NOT Allowed	: NOT ALLOWED
Partial Shipment: Allowed/ NOT Allowed	: NOT ALLOWED
Final Destination	: Mumbai India.(Nhava sheva Port)

Document Required: Following document to be send to us immediately & which are compulsary required after shipment Original AWB,ORIGINAL INVOICE, ORIGINAL PACKING LIST, Test Certificates,Certificate of Origin Installation Manual, Service Manual, Product certification.

Consigned to : **NIHVA TECHNOLOGIES PVT LTD**	**FOR NIHVA TECHNOLOGIES PVT LTD** NIHVA TECHNOLOGIES PVT LTD CHINCHWAD PUNE **AUTHORISED SIGNATORY**

ALL the document should be address to the above address only.
Subject to Pune Jurisdiction

NIHVA TECHNOLOGIES PVT LTD

Annexure A enclosed for Purchase Order NVA 530

Technical specification **Date - 10/08/2021**

Product Name - Roller shutter Thermo Teck (C)

Double-skinned Teckentrup roller shutter made from PU-foamed steel profiles.

outside of profiles micro-profiled, inner surface "smooth" w groove (curve).

Sr No	Parameter	Description
1	roller d. curtain profile type	ThermoTeck steel filled with PU-foam
2	ordering size (b x h)	4.515 mm (W) x 8.200 mm (H)
3	roller door surface outside	galvanised with protective fil
4	door color inside / outside	uniformly
5	roller shutter type	internal roller
		with storm hooks
6	buffer drive side min./exist.	325 mm / 325 mm
7	buffer bear. side min./exist.	200 mm / 200 mm
8	lintel height min./existing	700 mm / 700 mm
9	insertion depth	948 mm
10	building structure	concrete
11	bottom profile	ET-1 for Teckentrup ThermoTeck
12	welding shaft	steel tube ø 159mm primed
13	guide rail	FS 110 steel
14	underlining size	60 mm
15	console drive/bearing side	console type 7.5 / console type 7.5
16	brush sealing type	BH - 50
17	drive type / -edition	direct mount drive
		TAR 5.75 KU 400V/3Ph AWG
		. 12 U/min; IP54; 60% ED
18	drive mounted	inside left, standing
19	emergency drive operation	emergency hand crank
20	door operation	normal operation quantity
21	control unit	CS 310 (pulse)
		. with built-in triple button
		. CEE-plug with wire
22	control side	same as drive side
23	safety edge device	opto-sensors
24	control cable length	9.000 mm
25	heat transmis. value [W/m2K]	3,34
26	wind load class	wind load resistance class 3
	Total Amount for 10 Nos Rolling shutter	**Euro 50073.90**

NIHVA TECHNOLOGIES PVT. LTD. CHINCHWAD PUNE