




Inside Elevation



Top View

DOOR OPENING RIGHT HAND(OPTION 2)

Abbrevation's:
WOW-Wall Opening Width
WOH-Wall Opening Height
UC-Under Cut
FFL-Finished Floor Level

ASSESORIES DETALES

(a) HINGES: 3 No.SS Ball bearing butt hinges 100x75x3mm.


(b) LOCK: Mortise lock

(c) DOOR CLOSER

(d) HANDLE : Lever Handle

Shutter thickness : 47 mm
Frame Sheet thick : 1.5mm
Shutter sheet thick : 1.2mm
Fixing : On Soliid Brick plasterd wall with Anchors
Electrostatic powder coated

NOTE:- *All Dimensions are in mm.
*Tolerance:-All Linear Dimensions ±3mm,Others ±0.5mm.
*The Drawing Is For Location of Hardware only. Drawing Does Not Represent The Hardware For More Clarity, Please Go Through Hardware Broucher.



Detail view of Section A

FIRE DOOR SIZES		
WOW	WOH	QUANTITY
750	2100	1

COLOR:- OFF WHITE

This drawing & designing is the property of NIHVA TECHNOLOGIES. Not be sold or copy to any other concern.

SINGLE LEAF STEEL DOOR

CLIENT APPROVAL

ALL DIMENSION ARE IN mm

	NAME	DATE	SIGN.
DRAWN	OMKAR	27/02/16	
CHECK	ANIL	27/02/16	
REV.	00		
APPRD.			
MFG			

NIHVA TECHNOLOGIES PVT. LTD.
NIHVA TECHNOLOGY PVT. LTD. PUNE
Tel : 020 66304033
Email:- info@nihva.com
Website:-www.nihva.com

CLIENT - S.S.GHORPADE
PROJECT -
SITE -
DWG. NO. - NIHVA/15-16/233
SCALE: 01 | WT: | SHEET: 01 OF 01
If any queries contact : projects@nihva.com