Overhead sectional Speed door

ASSA ABLOY OH1042S

ASSA ABLOY

ASSA ABLOY Entrance Systems

The global leader in door opening solutions



Engineered to let your business be busy

ASSA ABLOY OH1042S overhead sectional doors have been designed with a modified control system and reinforced construction to increase speed and benefit your business. Speed improves your working environment, increases safety, reduces energy expenses and more. The ASSA ABLOY OH1042S is engineered to let your business be busy.

The benefits of speed
For businesses with frequently used doors, vehicles of different height, concerns of temperature control, regular door-collisions or an interest in reducing noise and dust –speed provides an invaluable advantage. With an operating speed of one meter per second, the ASSA ABLOY OH1042S not only saves time but gives it back to you.

Energy and economy efficient
Speed gives you control over indoor climate with a faster closing time. It has tight seals for water tightness, wind load and air permeability. More regulation over temperature means less heat loss, less wasted energy, and lower CO_2 emissions.

Concerned with safety, comfort and convenience
When the door's photo-cell light grid detects an obstacle in the door opening, it stops the door immediately, reducing the risk of accidents and injury. Because the door is faster, the risk of collisions with vehicles and loading materials while opening is much lower. The quick operation time prevents unwanted drafts and lowers noise levels to create a better, healthier work environment for employees.

A door to fit your needs
You can customize the ASSA ABLOY OH1042S. Configure track systems, select the color of the door, and choose the shape, number and placement of windows. There are literally thousands of options so you can tailor your door to your unique operation.

Technical Data


Standard size up to (W x H)[1]	5000 x 5000 mm
Panel thickness	42 mm
Windows	optional
Pass-door	not possible
Opening speed	1,0 m/s
Wind load, EN 12424[2]	class 3
Thermal transmittance, EN 12428[3] Full panel steel door	1,0 W/(m²K)
Water penetration, EN 12425[4]	class 3
Air permeability, EN 12426[4]	class 3

1) Other sizes on request 2) Higher wind load classification on request 3) Door size 5000 x 5000 mm

Dimensional specifications



Panel options




You can customize the OH1042S
Configure track systems, select the color of the door, and choose the shape, number and placement of windows. There are literally thousands of options so you can tailor your door to your unique operation.




Windows
Several variations of windows in different materials with burglar resistant frames are available.

Options access and automation







When the door's photo-cell light grid detects an obstacle in the door opening, it stops the door immediately, reducing the risk of accidents and injury.



Inside Outside

Complete lock including handle and cylinder for both sides or inside only. Any door equipped with an electrical lock can be remotely locked by means of a switch or via a PC. Lock mode can be monitored.

Standard available outside colours

Steel

Yellow RAL 1021	Green RAL 6005	Grey white RAL 9002	White Aluminium RAL 9006	White RAL 9010	
Red RAL 3002	Anthracite grey RAL 7016	Jet black RAL 9005	Aluminium grey RAL 9007	On request	Other colours
Blue RAL 5010	Chocolate brown RAL 8017				

ASSA ABLOY, Besam, Crawford, Albany and Megadoor, as words and logos, are examples of trademarks owned by ASSA ABLOY Entrance Systems or companies with in the ASSA ABLOY Group.

Q2.0-2017 © ASSA ABLOY Entrance Systems AB Technical data subject to change without notice.