Product:

NIHVA Motorized Rolling Shutter

Clear Opening dimension (w) -- x (h) -- :

W)…… x (H) ……. std. dimension or non. std. dimension Double acrylic vision panels

Opening Direction: Vertical - from bottom to Top

Mounting Location area: Optional = Inside area / Outside area

Mounting Surface: Guides : Optional = On Concrete/Steel / Masonry

Opening/Closing Speed: 0.1 m/sec

Wind Resistance: 90 Km/hrs.

Door Material

Curtain material: Optional = MS / GI / SS / AL

Curtain Panel: The panel made of 1.0mm thick CRCA steel

Curtain panel size: 75mm wide

Curtain Profile: Optional = Corrugation / Flat / Ribbed

Slat Thickness: 0.9 mm to 1.2 mm (As per IS 6248)

Bottom Profile: M. S. Plate 100 mm x 2.5 mm thick with angle stiffener
(Optional - Rubber Bottom Seal)

Side Guide Profile: M.S." U" Shaped profile 65 mm -200 mm x 3 mm thick (as per the opening width dimension)

Roller Shaft: M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Dia -100 to 300 mm as per w x h

Side Brackets: MS Plate 3 mm to 10 mm thick , as per the opening dimension

Hood Cover: Made of GI Sheet Thickness 0.8 mm with 25x25x3mm angle stiffener

Surface finish

Painting: 2 Coats (each coat of 35 microns DFT) of EPOXY polyamide based enamel finish of approved color and make over a Coat (each one coat 25 microns DFT) of EPOXY polyamide based red oxide zinc phosphate primer

Options Available: Perforation in Slat Profile / Rolling Grill

91 8551091333 ☎ +91 20 66304033

Email: marketing@nihva.com

Accessories: Option = Flashing Light / Door line Safety Photocell

Operating Switch: Option = Push Button from inside / or do you need Outside also

Automation

Control Type: Optional = Dead man / Pulse Control

Drive Unit & Mounting Type:

1) Electric Motor (Imported German Make) (Single Phase/Three Phase) - Direct Mounting on Shaft

2) Electric Motor (Imported China make) (single phase / three phase) - Indirect Mounting - Sprocket chain arrangement

Emergency Operation:

Option = Manual Hand Driven / Chain Wheel Drive

Option = Push Button / Key Switch From Outside

Integration optional:

Option = need to interlock or integrate with other door or machine or Equipment

Option = Remote Control with receiver

Installation Constraint any:

Need to be check = space requirements + substructure + Mounting access + Access in the event of power cut