Product datasheet

High speed door
ASSA ABLOY HS9010PFR

ASSA ABLOY

ASSA ABLOY Entrance Systems

The global leader in
door opening solutions



Copyright and Disclaimer Notice

Although the contents of this publication have been compiled with the greatest possible care, ASSA ABLOY Entrance Systems cannot accept liability for any damage that might arise from errors or omissions in this publication. We also reserve the right to make appropriate technical modifications/replacements without prior notice.

No rights can be derived from the contents of this document.

Color guides: Color differences may occur due to different printing and publication methods.

No part of this publication may be copied or published by means of scanning, printing, photocopying, microfilm or any other process whatsoever without prior permission in writing by ASSA ABLOY Entrance Systems.

Copyright © ASSA ABLOY Entrance Systems AB 2006-2017.
All rights reserved.

ASSA ABLOY, Besam, Crawford, Albany and Megadoor as word and logo are trademarks belonging to the ASSA ABLOY Group.

Technical facts

Features

Area of use:	Inside
Structure:	Galvanized steel
Max size: (W x H)*	4000 mm x 5500 mm
Colours:	8 standard colors - white, yellow, green, orange, red, gray, black, blue
Safety:	Photocells in side columns Flexible soft bottom edge including wireless edge activator Break-away and self-repair function
Options:	Different vision options are available. Colour of side column cover, motor cover.

* Other sizes may be available on request

Performance

Operating speed:	Opening: up to 2,4 m/s ** Closing: 1,2 m/s
Wind load resistance:	Class 1 (300 Pa (N/m²))
Water penetration:	Class 1 (30 Pa (N/m²))
Air permeability:	Class 1 (24 m³/m²/h at 50 Pa)
Thermal transmittance:	6,02 W/(m²K)
Temperature working range:	-30°C +5°C
Lifetime expectations:	1.000.000 cycles

** Depending on door size

Contents

Copyright and Disclaimer Notice 2

Technical facts 3

Contents 4

1. Description 5

1.1 General 5
1.1.1 Standard 5
1.1.2 Options 5
1.2 Door curtain 6
1.2.1 Construction 6
1.2.2 Material 6
1.2.3 Colours 6
1.2.4 Windows and vision panels 7
1.2.5 Insulated door curtain 7
1.2.6 Self repair system 7
1.2.7 Bottom edge 7
1.3 Side columns 8
1.3.1 General 8
1.4 Header box 8
1.4.1 Fabric roll 8
1.4.2 Covers 8
1.5 Operating system 9
1.5.1 General 9
1.5.2 Operator 9
1.5.3 Door drive system 9
1.5.4 Control unit 9
1.5.5 Access and automation 10
1.6 Monitoring systems 13
1.6.1 Saving energy 13
1.6.2 Security enhancement 13
1.6.3 Dock management 13
1.6.4 Facility management 13

2. Specifications 14

2.1 Daylight width and height 14
2.2 Fabric specifications 14
2.3 Windows 14
2.3.1 Required Daylight Width 14
2.3.2 Required Daylight Height 14

3. CEN Performance 15

4. Building and space requirements 16

4.1 Building preparations 16
4.1.1 Installation preparations 16
4.1.2 Electrical preparations 16
4.2 Space requirements 17


5. Service 18

Index 19

1. Description

1.1 General

The ASSA ABLOY HS9010PFR is designed for freezer environments, allowing efficient traffic flow while minimizing temperature variations. The high operating speed combined with an excellent seal optimizes the internal traffic flow and provides energy savings. The door can be set to open automatically every 20-25 minutes to avoid build-up of ice on side-guides and curtain. Heating cables in the side columns and motor help prevent this ice-formation.



The ASSA ABLOY HS9010PFR high speed door has 4 primary parts:

1) Door curtain
2) Side columns
3) Header box
4) Operating system

1.1.1 Standard

The ASSA ABLOY HS9010PFR high speed door is supplied with the following specifications as standard:

Door curtain:	900 g/m² coloured PVC Self repairing function
Header box:	Galvanized steel operator cover
Side column:	Galvanized steel side column covers
Frame:	Galvanized steel
Safety:	Photocells in side columns Flexible soft bottom edge including wireless edge activator Break-away and self-repair function
Operation:	Operator + control unit
Thermal protection:	Heating cables in side columns and motor. PU layer between side guides and wall PU coating on springs
Colours:	8 standard colors - white, yellow, green, orange, red, gray, black, blue

1.1.2 Options

ASSA ABLOY provides a wide range of options and accessories to customize the ASSA ABLOY HS9010PFR high speed door to any customer's needs.

Construction:	Stainless steel
Header box:	Painted or Stainless steel operator cover
Side Column:	Painted or Stainless steel covers
Operation:	Access and Automation Monitoring System
Windows:	Small windows in freezer quality PVC
Insulated door curtain	Static insulation 2,41 W/m²K (max. 4500 mm x 4500 mm)

1.2 Door curtain

1.2.1 Construction

The door curtain is constructed from one single piece of PVC fabric. The door curtain rolls up above the door opening and requires little space.

Top

The top of the fabric is connected to a fabric roll, located in the header box above the door opening.

Bottom

The flexible bottom edge of the door curtain does not contain any stiffeners, making the door curtain completely safe as the curtain moulds itself in case a person is trapped below the closing door.

Side

The left and right sides of the door curtain are constructed with a patented retaining strap. If the door is hit by a vehicle, a part of this retaining strap is pulled out of the side column. The self repair function acts as a zipper to put the retaining strap back in the side column.

1.2.2 Material

Fabric type

- 900 g/m² colored PVC,
- high resistance

1.2.3 Colours

The ASSA ABLOY HS9010PFR high speed door is available in 8 standard colors fabric colours. The RAL-colours are as close as possible to the official RAL HR collection. Max. deviation is 1,0 DE.

	RAL 1003
	RAL 2004
	RAL 3000
	RAL 5002
	RAL 6005
	RAL 7035
	RAL 9005
	RAL 9010

1.2.4 Windows and vision panels

To increase the admission of daylight or to improve the visibility, the door curtain can be equipped with freezer quality PVC windows. Windows have fixed sizes and are located on a pre-defined grid.




1.2.5 Insulated door curtain

For an improved temperature management an insulated door curtain is available with static insulation of 2,41 W/m²K

- Max. 4500 mm x 4500 mm
- No windows

1.2.6 Self repair system

The high speed doors are equipped with an automatic repair system. If a door is hit by a vehicle during operation, the resistant door curtain absorbs the impact and releases itself from its side guides without damage. The door reinserts itself automatically within the next open and close cycle. This unique feature makes the door crash-resistant without sustaining damage, reducing production downtime and maintenance.



1.2.7 Bottom edge

The bottom edge is a flexible bag that contains a wireless edge activator. When the door is hit by a vehicle, the curtain folds around the object and the contacts within the bottom edge make a closed circuit. The wireless signal is then sent to the operator to stop the door movement immediately.




1.3 Side columns

The side columns guide the door curtain up and down. This guidance is a plastic-to-plastic connection, which makes lubrication essential.

1.3.1 General

The side columns are part of the frame that also contains the header box. This frame is made of 3 mm thick galvanised steel tubes. The side column is as a standard equipped with a side guide cover. Inside the side column four heating cables prevent ice-formation. Between the side column and the building/wall a 10 mm layer of polyurethane isolation creates a thermal barrier between the steel structure and the ice cold wall. All these measures help prevent freezing and immobilising the door.




1) Low-friction polyethylene side guide inside a steel rail
2) Galvanised steel structure. U-channel 80 mm x 40 mm x 3 mm
3) Flexible rubber seal
4) Tension spring
5) Heating cables
6) Side guide cover
7) Polyurethane isolation (10 mm) between building and side column

1.4 Header box

1.4.1 Fabric roll

The fabric roll is installed in the header box above the door curtain. Its function is to roll up the door curtain by means of a counterweight. A gear drive system forces the door curtain up and down the tracks.



1.4.2 Covers

The motor is as a standard isolated by a galvanized steel cover. The motor compartment is heated with heating cables. The motor cover isolates the heating.

1.5 Operating system


1.5.1 General

The ASSA ABLOY HS9010PFR high speed door is always operated electrically. The operating system is a combination of an operator and a control unit. The operator opens and closes the door with an electric engine. The operator secures a safe closing speed with a soft start and stop.

1.5.2 Operator


Exceptional reliability and smooth operation is ensured by a motor driven by a frequency inverter. This technology ensures a soft start and stop, which increases the longevity of the motor considerably. It also allows faster opening/closing speed. This motor delivers reliable operations around-the clock. The operator is always combined with a control unit.

The operator drives the fabric roll to open or close the door. In case of a main supply failure, the operator can be disconnected and the door can be opened or closed manually using the hand crank.




1.5.3 Door drive system

The ASSA ABLOY HS9010PFR high speed door is equipped with a unique door drive system. This system eliminates the need for ballast in the door curtain or tension straps. This gear driven system consists of a pinion on the drive shaft that forces the lateral retaining straps up or down the tracks.



1.5.4 Control unit

The control unit is installed beside the door. It has impulse UP and DOWN buttons, an emergency stop mushroom button and a mechanical mains switch.



1) Display
2) UP button
3) DOWN button
4) Emergency stop
5) Mechanical main switch

1.5.5 Access and automation

ASSA ABLOY offers a wide range of functions that allow advanced opening and safety control.

1.5.5.1 Basic control functions


Interlocking



Developed for climate control or safety; If door A is open, door B cannot be opened. If door B is open, door A cannot be opened. An interlocked door can remember an up-command, if selected via a micro switch. Optionally an external locked switch can be installed to deactivate it.


- Function Interlock operating (switch interlock ON/OFF delivered with priority door)
- Switch interlock on/off (requires interlock function)
- Switch interlock on/off with key (requires interlock function)

Airlock



Developed for climate control or safety: Other than the interlock, door B will open automatically when door A is closed.
Circuit card Installed in control unit. Optionally an external locked switch can be installed to deactivate it.

Reduced opening



When people pass through the door, it may be unnecessary to fully open a door. A manual (pedestrian) command can trigger a reduced door opening, while a radar or magnetic loop still triggers a full door opening.
Pre-fitted micro-switch to be activated in control unit.

- Function Two opening heights I/II with manual selection (switch included)
- Function Two opening heights I/II with automatic selection (2 different opening impulses)


1.5.5.2 External control functions

External push button box



An extra control box is installed outside the building or inside close to the door if the main control unit needs to be installed away from the door opening. Usually combined with reduced opening.
Installed on the inside or outside wall beside the door.

Pull-rope switch



A pull-rope switch above the door opening can be operated from e.g. a forklift truck. Pulling the rope opens the door.
Installed on the inside construction above the door.

- Pull down switch complete 5 m cord
- Pull switch bracket in galvanised steel – L 3000 mm
- Pull switch bracket in painted steel – L 3000 mm
- Pull switch bracket in stainless steel – L 3000 mm

Remote control




A hand-held radio transmitter allows door operation from a vehicle or any position within 50-100 meters from the receiver and aerial at the door. For closing, the door can be provided with a photocell beam.
Receiver installed in control unit, antenna installed on the wall beside the door.

1.5.5.3 Automatic control functions


- Function Auto/Manual (includes switch on the control box)
- Function Manual closing with opening/closing using a common manual command (e.g. one single pull rope opens and closes the door)
- Function Manual closing with separate impulse (e.g. 2 buttons up and down)

Magnetic loop




A sensor in the floor detects a metal object (usually forklift trucks, pallet trucks) and opens the door automatically. This is an ideal solution for frequent vehicle traffic.
Installed on the outside, inside or both sides of the door in the floor.

Radar




An infrared sensor above the door detects an object (person, vehicle) within a specified distance from the door and opens the door automatically. This is an ideal solution for frequent vehicle or personal traffic. Often combined with automatic closing.
Installed on the inside or outside wall above the door.

Photocell open door



A set of photocells on pillars, on each side of the door. When a person or vehicle passes between the photocells, the beam is interrupted and the door opens.
Photocells installed on pillars, away from the door.

Automatic closing (standard)



A programmable timer that closes the door after a specified time, counted from either the fully open position and/or from passing through the photocell beam. Usually also a switch on the control unit is used to turn to manual closing.
Adjustable micro switches in control unit.


1.5.5.4 Safety functions

Wireless edge activator (standard)




All doors are equipped with an edge activator. A wireless edge activator in the bottom seal detects any obstruction under a closing door and reverses the door.
Installed in the bottom edge.

Safety photocells 1-channel (standard)




A set of a photocell transmitter and receiver is installed in the door opening. If the photocell beam is interrupted during closing, the door will stop in less than 30 mm and reverse to the fully open position.
Installed in the door opening 300 mm from floor level.

Warning lights - Red



A red warning light on each side gives information on the current door behaviour. Flashing light seconds before and during door movement.
Installed on the inside and outside wall beside the door.

Acoustic signal




An acoustic signal is given, starting just before the door begins to close and continues until the door is fully closed.
Installed on the inside and outside wall beside the door.

- Acoustic signal 24VAC 80 dB at 1 meter (horn when door is moving)

1.5.5.5 Lights


- Standard function flashing light
- Standard function flashing light with pre-warning before closing and opening

Warning lights - Orange




An orange warning light on each side gives information on the current door behaviour. Flashing light seconds before and during door movement.
Installed on the inside and outside wall beside the door.

Warning lights - Green



A green warning light installed on each side of the door indicating the open position of the door by continuous light signal.

Traffic lights - Red & Green



If traffic through a door needs to be directed; two red and two green traffic lights can be installed to indicate traffic direction. From the side where a vehicle is first detected to approach the door, the green traffic light comes on. The opposing side shows a red traffic light. Traffic from this direction must give way to the other. Usually installed in e.g. parking garages.
Installed on the inside and outside wall beside the door.

1.5.5.6 Additional functions

UPS battery backup



In case of main supply failure or emergency situations, it may be necessary to be able to open the door. The UPS battery stores enough power for one emergency opening cycle.
Installed on the inside wall beside the door.

- Kit UPS Interface, automatic opening in case of power failure
- Kit UPS Interface, semi-automatic in case of power failure

1.6 Monitoring systems

As an option on all our products, a Monitoring System can be installed. This system helps to ensure efficiency and security in daily operations. All doors or docking stations are connected to the Monitoring System's server, which gives the opportunity to supervise, monitor and report a wide variety of aspects in a facility.



1.6.1 Saving energy

A monitoring system reduces energy costs and contributes to a better environment. Energy is lost every time a door is open. If a door is open when no truck is at the bay, even more energy is lost.

A Monitoring System automatically ensures that no door will open unless there is a truck at the bay and even set it to close when there an activity is delayed.

1.6.2 Security enhancement

Closing and locking doors is an obvious daily routine. However, checking this manually can be time consuming in a busy facility.

A Monitoring System can automatically ensure that all doors are closed and locked when they need to be. It can also activate all doors and locks from its remote location, and give a real-time overview of the building's situation.

1.6.3 Dock management

A good way to increase throughput and thereby efficiency at a logistics facility is to reduce the time of having no truck – or the wrong truck – at a loading bay.

A Monitoring System makes visible – in real-time –which bays are occupied or free, and for how long. It makes it possible to reserve bays for docking activities and to inform drivers via SMS. Since it incorporates information from cameras and other inputs (RFID, card readers, etc.), the system stays updated in real-time.

1.6.4 Facility management

The Monitoring System gives a real-time service status for all your door and docking equipment. If an error code occurs, the ASSA ABLOY service organisation is automatically notified, and will respond quickly. Other maintenance information can easily be integrated, further reducing the overall costs.

2. Specifications

2.1 Daylight width and height

The standard ASSA ABLOY HS9010PFR high speed door is delivered in the following size range:

Standard door sizes*		
	Daylight width	Daylight height
Min.:	1000 mm	2000 mm
Max.:	4000 mm	5500 mm

* Other sizes may be available on request

2.2 Fabric specifications

	Coloured fabric	**Vision panel**
Material	Reinforced PVC	PVC
Thickness	0,8 mm	2,0 mm
Weight	900 g/m²	2,5 kg / m²
Tensile strength (kN/5cm)	4,0 L / 3,5 W	1,6
Tearing resistance	600 N (DIN 53363)	100 N (DIN 53515)

2.3 Windows


Dimensions: W x H: 640 mm x 580 mm.
Combinations: Any combination of rows is possible.

2.3.1 Required Daylight Width

DLW	**Available no. of columns**
1140 mm – 1929 mm	1
1930 mm – 2719 mm	2
2720 mm – 3509 mm	3
3510 mm – 4000 mm	4

2.3.2 Required Daylight Height

DLH	**Available no. of rows**	**CC**
2040 mm	1	1600 mm



3. CEN Performance

Characteristic	Standard	Test acc.	Result	Value
Wind load	EN 12424	EN 12444	Class 1	300 Pa (N/m²)
Water permeability	EN 12425	EN 12489	Class 1	30 Pa (N/m²) water spray for 20 minutes
Air permeability	EN 12426	EN 12427	Class 1	24 m³/m²/h at 50 Pa
Safe openings	EN 12453	EN 12445	Pass	
Mechanical resistance	EN 12604	EN 12605	Pass	
Unintended movements	EN 12604	EN 12605	Pass	
Thermal resistance	EN 12428		6,02 W/(m²K)	
Performance (cycles)	EN 12604	EN 12605	1.000.000 cycles	

4. Building and space requirements

4.1 Building preparations

4.1.1 Installation preparations

The door is pre-assembled in the factory as much as possible to ensure that installation can be carried out easily and quickly. The door is installed directly on the wall. A forklift truck is needed to raise the frame to the wall.


The fixation of the wall must be of an adequate strength to sustain the wind load as well as the blow of a collision.

4.1.2 Electrical preparations

The following environment criteria and electrical supplies are required for the operator to function properly:

Voltage supply:	400V 3-phase
Power:	1,5 kW 3 x 16A
Frequency:	50Hz - 60Hz
Degree of protection:	Operator: IP65 Control unit: IP54
Temperature working range:	0 °C to +40 °C

4.2 Space requirements



Reduced head room

The space requirement of the head room is 500 mm. This head room can be reduced to 370 mm if the door is max. 4000 mm high and is not equipped with a drum cover.

5. Service

Preventive Maintenance Program and Modernization Services

As your entrances are part of your business flow, there's every reason to keep them working well. ASSA ABLOY Entrance Systems offers you a maintenance and modernization expertise to rely on. Our Maintenance Programs and Modernization Services are backed by a extensive expertise for all types of industrial door and docking systems, independent of brand. At your disposal is a team of dedicated expert technicians, proven through decades of maintenance, service and satisfied customers.

Preventive Maintenance Programs

Minimizing lost time, lost energy and unexpected hassle is our team's constant objective. Our service organization can support you 24/7 in maintaining all industrial door and docking systems, independent of brand. If you want to be one step ahead of break-downs, explore our portfolio of Pro-Active Care plans. Naturally, we also offer entrance upgrades to suit your specific wishes and business needs.

Pro-Active Care - Maintenance plans to fit your business

Regular maintenance can extend the lifetime of your equipment and help prevent unexpected problems. Our technician arrives on-site equipped with the knowledge and tools to service all automatic entrances, independent of brand.

- **Pro-Active Bronze**

The base on which all Pro-Active Plans are built provides the security of knowing that your equipment is regularly inspected and certified for safety, as well as performing optimally. It includes a number of planned on-site visits depending on your needs. Any unplanned service calls required during the term of the contract (including labor, travel and parts) are billed at special Pro-Active Care prices.

- **Pro-Active Silver**

This plan provides all the benefits of Pro-Active Bronze with the added advantage of labor and travel being included for service calls during regular business hours. The only additional charge would be for any parts that may be needed throughout the term of the contract.

- **Pro-Active Gold**


This plan provides the ultimate protection for your automatic entrance investment. It includes all the benefits of Pro-Active Silver, plus replacement of any parts required during an unplanned repair or planned maintenance visit. Pro-Active Gold is an excellent way to budget your automatic door expenses annually.

- **Pro-Active Tailor-Flex**

Our most flexible maintenance and service offering. The Pro-Active Care plan is designed by you, our customer. The plan allows you to balance your maintenance expenses against your real-world budget and presents the option to add or delete a number of maintenance elements to suit your budget goals, while meeting your overall performance and safety needs.

Modernization

Your entrances are a long-term investment, from which you always want the best. Products develop over time, so do regulations and your business. Let us help you increase energy savings and meet today's standards. We provide advice and modernization kits for outdated installations, ensuring your investment meet requirements and performs optimally for many more years to come.



Index

A

Access and automation 10
Acoustic signal 11
Additional functions 12
Airlock 10
Automatic closing (standard) 11
Automatic control functions 11

B

Basic control functions 10
Bottom edge 7
Building and space requirements ... 16
Building preparations 16

C

CEN Performance 15
Colours 6
Construction 6
Control unit 9
Copyright and Disclaimer Notice 2
Covers 8

D

Daylight width and height 14
Description 5
Dock management 13
Door curtain 6
Door drive system 9

E

Electrical preparations 16
External control functions 10
External push button box 10

F

Fabric roll 8
Fabric specifications 14
Facility management 13
Features 3

G

General 5, 8, 9

H

Header box 8

I

Installation preparations 16
Insulated door curtain 7
Interlocking 10

L

Lights 12

M

Magnetic loop 11
Material 6
Monitoring systems 13

O

Operating system 9
Operator 9
Options 5

P

Performance 3
Photocell open door 11
Pull-rope switch 10

R

Radar 11
Reduced opening 10
Remote control 10
Required Daylight Height 14
Required Daylight Width 14

S

Safety functions 11
Safety photocells 1-channel (standard) 11
Saving energy 13
Security enhancement 13
Self repair system 7
Service 18
Side columns 8
Space requirements 17
Specifications 14
Standard 5

T

Technical facts 3
Traffic lights - Red & Green 12

U

UPS battery backup 12

W

Warning lights - Green 12
Warning lights - Orange 12
Warning lights - Red 11
Windows 14
Windows and vision panels 7
Wireless edge activator (standard) 11

ASSA ABLOY Entrance Systems is a leading supplier of entrance automation solutions for the efficient flow of goods and people. Building on the long-term success of the Besam, Crawford, Albany and Megadoor brands, we offer our solutions under the ASSA ABLOY brand. Our products and services are dedicated to satisfying end-user needs for safe, secure, convenient and sustainable operations.
ASSA ABLOY Entrance Systems is a division of ASSA ABLOY.

assaabloyentrance.com

Q3.0 - 2017

ASSA ABLOY Entrance Systems

assaabloyentrance.com