Dock leveler specification		Nihva	AU REMARK
Sr. No.	**Description**	Specifications	
		Dock leveler specification- 2000(W)X3000(L)	
1	Manufacturing Standard	EN 1398	EN 1398
2	Capacity of Dock Leveller (Dynamic/point load)-Min	DYNAMIC CAPACITY 6 TON	3T is client requirement, we can go for 5T to make it standard if cost difference is not huge
3	Make	NIHVA	ok
4	Deck width(minimum)	2000 MM	ok
5	Deck Length (minimum)	2900 MM	ok
6	Lip Extension	Lip length 400 mm	ok
7	Lip Thickness (Minimum)	12 mm	Lip plate should be 12mm min.
8	Working Rannge		
	Above	300	Details from Gatemaan are missing. Gandhi has provided best Range
	Below	250 mm	
9	Fixed Position Bumper	Two pair of rubber bumper provided	Pair of Bumper required Per Dock Leveller
10	Platform	M.S. chequered sheet platform Minimum 8 mm thickness sheet	ok
11	Swing Lip	Lip operated by hydraulic cylinder	ok
12	Hydraulic System	Standard powerpack with 1 HP motor , 5 Litre tank capacity	ok
13	Pressure rating of Cylinder	Operating pressure - 100 to 150 bar Maximum pressure - 200 bar	ok. Need apporpriate response from GateMaan
14	Motor Rating	1 HP	
15	Motor Cable Spec	Polycab multi-core cable 1.5 sq. mm	ok
16	Main Fuse Rating	details will be confirmed after confirmation of order.	
18	Safety Arrangments	Hose burst valve	Inbuilt safety arrangement for Powr failure related Dock leveller movement restrcition is must.
19	Wall mounted controll panel	Control panel can be easily mounted on wall , mounting brackets provided	required
20	Finish	Painting & RAL shade of approved colour	Color to be defined by GB/ Gurit
21	Makes of all accessories. Motor -	details will be confirmed after confirmation of order.	ok
22	Total Quantity of Dock leveller		5
23	Size of Dock door (Rolling Shutter)& Total Quantity of Dock door(Motorised Rolling Shutter)		Dock Levellers are planned as per gurit Requirement