



DRAWING









TECHNICAL SPECIFICATION:-

SR.	SPECIFICATION	DETAILS
1.	DESCRIPTION & DRIVE	MOTORIZED ROLLING SHUTTER (INDIRECT DRIVE)
2.	LOCATION AREA	INSIDE AREA / OUTSIDE AREA
3.	MOUNTING SURFACE	SIDE BRACKETS: OPTIONAL = ON CONCRETE/STEEL&SIDE
4.	SLAT	GI SLAT- 1.2MM THICK (75 MM WIDTH)
5.	BOTTOM PROFILE	MS PLATE100 x 3.15 MM THICK WITH ANGLE 35X35X5 MM .
6.	GUIDE PROFILE	M.S." T " SHAPED PROFILE 100X150X3 MM THICK.
7.	HOOD COVER & MOTOR COVER	MADE OF GI SHEET THICKNESS 0.9 MM.
8.	SURFACE FINISH	SYNTHETIC ENAMEL PAINT
9.	PUSH BOTTON	3 WAY PUSH BUTTON ON SINGLE SIDE

SHUTTER SIZES :- (FOR MANUFACTURING COMPLEX)

SR.	CLEAR WIDTH	CLEAR HEIGHT	QTY.
01	5000 mm	5000 mm	01

RIVISION.	DATE
REV 01 : SLAT THICKNESS CHANGE 1MM TO 1.2MM BOTTOM PLATE THICKNESS CHANGE 2.5MM TO 3.15MM ANGLE STIFFENER CHANGE 35X35X3 MM TO 35X35X5 MM	03-12-2025

NOTE-
1. ALL CIVIL WORK WILL BE CLIENT'S SCOPE.
2.IF STRUCTURE REQUIRED FOR SHUTTER IS IN CLIENT'S SCOPE.

NOTE :
GALVANISATION SHALL BE MIN 230 g/SQ.M
PUSH BUTTON BOTH SIDE

SPECIAL INSTRUCTION'S :

TITLE - DOOR AUTOMATION

DWG NO - NTPL- 300-PM-01

NIHVA TECHNOLOGIES PVT.LTD.PUNE
Website - www.nihva.com

	NAME	SIGNATURE	DATE
DRAWN	V.W.		08-11-2025
CHK'D	B.S.		10-11-2025
APPV'D	V.T.		10-11-2025

PRODUCT - MOTORIZED ROLLING SHUTTER
PROJECT NO - NTPL- 300 | REVISION - 01
SITE LOCATION-GUJARAT | WEIGHT -
MATERIAL - | QTY - 01 NOS
IF ANY QUERIES CONTACT - Design@nihva.com
PROJECTION METHOD | SCALE :
ALL DIMENSIONS ARE IN 'MM' | A2 | SHEET 1 OF 1