


(CLEAR OPENING (C.W.)1100X(C.H.)2060)
(C.W.)1850X(C.H.)2260)

(NOTE: REQUIRED STRUCTURE FOR DOOR SHOULD BE IN CLIENT SCOPE.)

structure should bear approx. 500 k.g. weight. While Door is in operation, structure should not vibrate and bear/sustain all movements of HSD.

This drawing & designing is the property of NIHVA TECHNOLOGIES. Not be sold or copy to any other concern.

TITLE

STRUCTURE FOR HIGH SPEED DOOR

CLIENT APPROVAL

ALL DIMENSION ARE IN mm

	SIGN	DATE
DRAWN	ABHIJIT	07/12/15
CHECK	ANIL	07/12/15
ENG		
APPRD.		
MFG		
Ref. No.		

NIHVA TECHNOLOGIES PVT. LTD.
NIHVA TECHNOLOGY PVT. LTD. PUNE
Tel : 020 66304033
Email:- info@nihva.com
Website:- www.nihva.com

CLIENT -FAURECIA EMMISION CONTROL TECHNOLOGIES

PROJECT-

SITE -

DWG. NO. - NIHVA/15-16/171

SCALE: 01 | WT: | SHEET: 01

If any queries contact : projects@nihva.com