Technical Specifications For 300 mm - Red Traffic Light





No.	Item	Specifications	Compliances
1	**Brand**		**Nucleonics traffic equipmentts**
2	**Model**		**NTE10054**
3	**Technology**	LED based 5mm oval type	**yes**
4	**Dimension**	280mm x 560mm x 350mm	**350mm*350mm*360mm**
5	**Led retrofit dia.**	200mm (±10%) full round	**300mm**
6	**Material and finishes**	Polycarbonate black color powder coated with Sun visor	**yes Polycarbonate housing with HDPE visor (one side glossy and one side matt finish)**
7	**Aspect diameter**	200mm	**300 mm dia**
8	**PCB**	Green masking Pads- Tin plated Conformal coating for moisture protection	**yes**
9	**Type of signal**	Ball type	**Yes**
10	**Luminance**	200cd	**Yes**
11	**Chain failure**	No chain failure of LED's.Failed LED will not work	**Failed LED with 9 LED's in series will not work**

12	**Wavelength**	Red - 625nm	**Yes**
13	**Aspect Color**	Red and Pure Green	**yes**
14	**Interface**	230VAC switching from potential free devices	**yes**
15	**Visibility**	>20mtrs	**200-500 mtrs**
16	**Viewing Angle**	< 23 degrees	**23 degree**
17	**Cables**	Power Cable	**yes**
18	**LED Type**	5mm Super Bright Day visible-clear	**yes**
19	**LED intensity**	12000 - 14000 mcd at 20 mA, 30˚ viewing angle for Red 21000 - 24000 mcd at 20 mA, 30˚ viewing angle for GREEN	**15000 to 20000mcd at 20ma 23 degree standard viewing angle** **21000 to 24000mcd at 20ma 23 degree standard viewing angle**
20	**Weight**	<6 Kg	**3 Kg**
21	**Operating Voltage**	220-270VAc /50-60 Hz	**yes**
22	**Power Consumption**	10W max	**8 watts**
23	**Installation**	Bolting Arrangement to the Traffic Pole	**yes clamps and brackets wth hose clip to the traffc pole**
24	**Environment Conditions**	Operating Temp : -10°C to 60°C	**yes**
		Humidity : 0 to 90%	**yes**
25	**Reliability**	MBTF: 50,000 hours	**yes**
		MTTR: 0.20 hrs	**yes**
26	**Access For maintenance**	Front Door Access for Easy Maintenance	**yes**
27	**Protection**	IP65	**yes**
28	**Operating Temperature**	5 ºC to 65 ºC	**yes**
29	**Auto Diming**	Night Dimming facility available (optionally)	**No**