```
**************************************************
*                                                *
*          STAAD.Pro 2023                        *
*          Version  23.00.01.25                  *
*          Proprietary Program of                *
*          Bentley Systems, Inc.                 *
*          Date=    JUN 28, 2025                 *
*          Time=    15: 3:51                     *
*                                                *
*  Licensed to: Salt Design Services             *
**************************************************
```

```
     1. STAAD SPACE
INPUT FILE: C:\Users\Harshal\OneDrive\Salt\1790 NIHVA MISC\OBEROI\STAAD\MAXIMA (03.04.2023).STD
     2. START JOB INFORMATION
     3. ENGINEER DATE 16-DEC-22
     4. END JOB INFORMATION
     5. INPUT WIDTH 79
     6. UNIT METER KN
     7. JOINT COORDINATES
     8. 1 0.0500001 3.10059E-05 0; 2 4.68701 3.10059E-05 0; 3 0.0500001 0.250028 0
     9. 4 4.68701 0.250028 0; 5 2.3685 0.700001 0; 6 0.590291 0.419001 0
    10. 7 1.18214 0.586001 0; 8 1.775 0.686001 0; 9 4.14672 0.419001 0
    11. 10 3.55487 0.586001 0; 11 2.96201 0.686001 0; 12 0.0500001 3.10059E-05 -0.825
    12. 13 4.68701 3.10059E-05 -0.825; 14 0.0500001 0.250028 -0.825
    13. 15 4.68701 0.250028 -0.825; 16 2.3685 0.700001 -0.825
    14. 17 0.590291 0.419001 -0.825; 18 1.18214 0.586001 -0.825
    15. 19 1.775 0.686001 -0.825; 20 4.14672 0.419001 -0.825
    16. 21 3.55487 0.586001 -0.825; 22 2.96201 0.686001 -0.825
    17. 23 0.0500001 3.10059E-05 0.825; 24 0.0500001 0.250028 0.825
    18. 25 4.68701 3.10059E-05 0.825; 26 4.68701 0.250028 0.825
    19. 27 0.590291 0.419001 0.825; 28 1.18214 0.586001 0.825; 29 1.775 0.686001 0.825
    20. 30 2.3685 0.700001 0.825; 31 4.14672 0.419001 0.825; 32 3.55487 0.586001 0.825
    21. 33 2.96201 0.686001 0.825; 34 0.0500001 3.10059E-05 1.65
    22. 35 0.0500001 0.250028 1.65; 36 4.68701 3.10059E-05 1.65
    23. 37 4.68701 0.250028 1.65; 38 0.590291 0.419001 1.65; 39 1.18214 0.586001 1.65
    24. 40 1.775 0.686001 1.65; 41 2.3685 0.700001 1.65; 42 4.14672 0.419001 1.65
    25. 43 3.55487 0.586001 1.65; 44 2.96201 0.686001 1.65
    26. 45 0.0500001 3.10059E-05 2.475; 46 0.0500001 0.250028 2.475
    27. 47 4.68701 3.10059E-05 2.475; 48 4.68701 0.250028 2.475
    28. 49 0.590291 0.419001 2.475; 50 1.18214 0.586001 2.475; 51 1.775 0.686001 2.475
    29. 52 2.3685 0.700001 2.475; 53 4.14672 0.419001 2.475; 54 3.55487 0.586001 2.475
    30. 55 2.96201 0.686001 2.475; 56 1.59567 3.10059E-05 2.475
    31. 57 3.14134 3.10059E-05 2.475; 60 1.59567 0.655753 2.475
    32. 61 3.14134 0.655753 2.475; 62 0.0500001 3.10059E-05 2.0625
    33. 63 4.68701 3.10059E-05 2.0625; 64 0.0500001 3.10059E-05 -0.4125
    34. 65 4.68701 3.10059E-05 -0.4125
    35. MEMBER INCIDENCES
    36. 1 1 3; 2 2 4; 3 3 6; 4 6 7; 5 7 8; 6 8 5; 7 4 9; 8 9 10; 9 10 11; 10 11 5
    37. 13 3 14; 14 4 15; 15 5 16; 16 6 17; 17 7 18; 18 8 19; 19 9 20; 20 10 21
    38. 21 11 22; 22 12 14; 23 13 15; 24 14 17; 25 17 18; 26 18 19; 27 19 16; 28 15 20
```

```
39. 29 20 21; 30 21 22; 31 22 16; 32 23 24; 33 25 26; 34 24 27; 35 27 28; 36 28 29
40. 37 29 30; 38 26 31; 39 31 32; 40 32 33; 41 33 30; 42 24 3; 43 26 4; 44 30 5
41. 45 27 6; 46 28 7; 47 29 8; 48 31 9; 49 32 10; 50 33 11; 51 34 35; 52 36 37
42. 53 35 38; 54 38 39; 55 39 40; 56 40 41; 57 37 42; 58 42 43; 59 43 44; 60 44 41
43. 61 35 24; 62 37 26; 63 41 30; 64 38 27; 65 39 28; 66 40 29; 67 42 31; 68 43 32
44. 69 44 33; 70 45 46; 71 47 48; 72 46 49; 73 49 50; 74 50 60; 75 51 52; 76 48 53
45. 77 53 54; 78 54 61; 79 55 52; 80 46 35; 81 48 37; 82 52 41; 83 49 38; 84 50 39
46. 85 51 40; 86 53 42; 87 54 43; 88 55 44; 89 45 56; 90 56 57; 91 57 47; 92 56 60
47. 93 57 61; 94 60 51; 95 61 55; 96 45 62; 97 47 63; 98 1 64; 99 23 1; 100 34 23
48. 101 2 65; 102 25 2; 103 36 25; 104 62 34; 105 63 36; 106 64 12; 107 65 13
49. SUPPORTS
50. 62 TO 65 PINNED
51. MEMBER RELEASE
52. 13 TO 21 42 TO 50 61 TO 69 80 TO 88 START MY MZ
53. 13 TO 21 42 TO 50 61 TO 69 80 TO 88 END MY MZ
54. DEFINE MATERIAL START
55. ISOTROPIC ALUMINUM
56. E 6.89473E+07
57. POISSON 0.33
58. DENSITY 26.6017
59. ALPHA 1.28E-05
60. DAMP 0.03
61. ISOTROPIC STEEL
62. E 1.99947E+08
63. POISSON 0.3
64. DENSITY 76.8191
65. ALPHA 6.5E-06
66. DAMP 0.03
67. TYPE STEEL
68. STRENGTH RY 1.5 RT 1.2
69. END DEFINE MATERIAL
70. CONSTANTS
71. MATERIAL STEEL ALL
72. MEMBER PROPERTY APLAPOLLOTUBES
73. 13 TO 21 42 TO 50 61 TO 69 80 TO 88 TABLE ST 80X80X2.9SHS
74. MEMBER PROPERTY INDIAN
75. 1 TO 10 22 TO 41 51 TO 60 70 TO 79 89 TO 94 -
76. 95 TABLE ST TUBE TH 0.006 WT 0.08 DT 0.16
77. 96 TO 107 TABLE ST TUBE TH 0.006 WT 0.16 DT 0.16
78. MEMBER OFFSET
79. 96 TO 107 START 0 -0.08 0
80. 96 TO 107 END 0 -0.08 0
81. DEFINE WIND LOAD

*** NOTE: If any floor diaphragm is present in the model Wind Load definition
          should be defined after Floor Diaphragm definition. Otherwise wind
          load generation may be unsuccessful during analysis.

82. TYPE 1 WIND 1
83. INT 1.11 1.23 1.27 1.4 1.52 1.71 HEIG  10  20  25  30  50  100
84. LOAD 1 LOADTYPE DEAD  TITLE DL
85. MEMBER LOAD
86. 1 TO 10 22 TO 41 51 TO 60 70 TO 79 94 95 UNI GY -0.025
87. SELFWEIGHT Y -1 LIST ALL
88. LOAD 2 LOADTYPE DEAD  TITLE LL
89. MEMBER LOAD
```

```
 90. 3 TO 10 24 TO 31 34 TO 41 53 TO 60 72 TO 79 94 95 UNI GY -0.35
 91. LOAD 3 LOADTYPE NONE  TITLE WL X
 92. MEMBER LOAD
 93. 3 4 24 25 34 35 53 54 72 73 UNI Y -0.055
 94. 5 TO 10 15 18 TO 21 26 TO 31 36 TO 41 44 47 TO 50 55 TO 60 63 66 TO 69 74 -
 95. 75 TO 79 82 85 TO 88 94 95 UNI Y 1.44
 96. LOAD 4 LOADTYPE NONE  TITLE WL Z
 97. MEMBER LOAD
 98. 3 TO 10 24 TO 31 34 TO 41 53 TO 60 72 TO 79 94 95 UNI Y 1.18
 99. LOAD 5 LOADTYPE NONE  TITLE WL-X
100. MEMBER LOAD
101. 7 8 28 29 38 39 57 58 76 77 UNI Y -0.055
102. 3 TO 6 9 10 24 TO 27 30 31 34 TO 37 40 41 53 TO 56 59 60 72 TO 75 78 79 94 -
103. 95 UNI Y 1.44
104. LOAD 6 LOADTYPE NONE  TITLE WL-Z
105. MEMBER LOAD
106. 3 TO 10 24 TO 31 34 TO 41 53 TO 60 72 TO 79 94 95 UNI Y 1.18
107. LOAD COMB 101 1.5(DL+LL)
108. 1 1.5 2 1.5
109. LOAD COMB 102 1.5(DL+WLX)
110. 1 1.5 3 1.5
111. LOAD COMB 103 1.5(DL+WLZ)
112. 1 1.5 4 1.5
113. LOAD COMB 104 1.5(DL+WL-X)
114. 1 1.5 5 1.5
115. LOAD COMB 105 1.5(DL+WL-Z)
116. 1 1.5 6 1.5
117. LOAD COMB 201 DL + LL
118. 1 1.0 2 1.0
119. LOAD COMB 202 DL+WLX
120. 1 1.0 3 1.0
121. LOAD COMB 203 DL+WLZ
122. 4 1.0 1 1.0
123. LOAD COMB 204 DL+WL-X
124. 1 1.0 5 1.0
125. LOAD COMB 205 DL+WL-Z
126. 6 1.0 1 1.0
127. LOAD COMB 206 DL+0.8WLX
128. 1 1.0 3 0.8
129. LOAD COMB 207 DL+0.8WLZ
130. 4 0.8 1 1.0
131. LOAD COMB 208 DL+0.8WL-X
132. 5 0.8 1 1.0
133. LOAD COMB 209 DL+0.8WL-Z
134. 6 0.8 1 1.0
135. PERFORM ANALYSIS PRINT ALL
```

P R O B L E M S T A T I S T I C S

NUMBER OF JOINTS	63	NUMBER OF MEMBERS	105
NUMBER OF PLATES	0	NUMBER OF SOLIDS	0
NUMBER OF SURFACES	0	NUMBER OF SUPPORTS	4

Using 64-bit analysis engine.

SOLVER USED IS THE IN-CORE ADVANCED MATH SOLVER

TOTAL PRIMARY LOAD CASES = 6, TOTAL DEGREES OF FREEDOM = 366
TOTAL LOAD COMBINATION CASES = 14 SO FAR.

LOADING 1 LOADTYPE DEAD TITLE DL

MEMBER LOAD - UNIT KN METE

MEMBER	UDL	L1	L2	CON	L	LIN1	LIN2
1	-0.0250 GY	0.00	0.25				
2	-0.0250 GY	0.00	0.25				
3	-0.0250 GY	0.00	0.57				
4	-0.0250 GY	0.00	0.61				
5	-0.0250 GY	0.00	0.60				
6	-0.0250 GY	0.00	0.59				
7	-0.0250 GY	0.00	0.57				
8	-0.0250 GY	0.00	0.61				
9	-0.0250 GY	0.00	0.60				
10	-0.0250 GY	0.00	0.59				
22	-0.0250 GY	0.00	0.25				
23	-0.0250 GY	0.00	0.25				
24	-0.0250 GY	0.00	0.57				
25	-0.0250 GY	0.00	0.61				
26	-0.0250 GY	0.00	0.60				
27	-0.0250 GY	0.00	0.59				
28	-0.0250 GY	0.00	0.57				
29	-0.0250 GY	0.00	0.61				
30	-0.0250 GY	0.00	0.60				
31	-0.0250 GY	0.00	0.59				
32	-0.0250 GY	0.00	0.25				
33	-0.0250 GY	0.00	0.25				
34	-0.0250 GY	0.00	0.57				
35	-0.0250 GY	0.00	0.61				
36	-0.0250 GY	0.00	0.60				
37	-0.0250 GY	0.00	0.59				
38	-0.0250 GY	0.00	0.57				
39	-0.0250 GY	0.00	0.61				
40	-0.0250 GY	0.00	0.60				
41	-0.0250 GY	0.00	0.59				
51	-0.0250 GY	0.00	0.25				
52	-0.0250 GY	0.00	0.25				
53	-0.0250 GY	0.00	0.57				
54	-0.0250 GY	0.00	0.61				
55	-0.0250 GY	0.00	0.60				
56	-0.0250 GY	0.00	0.59				
57	-0.0250 GY	0.00	0.57				
58	-0.0250 GY	0.00	0.61				
59	-0.0250 GY	0.00	0.60				
60	-0.0250 GY	0.00	0.59				
70	-0.0250 GY	0.00	0.25				
71	-0.0250 GY	0.00	0.25				
72	-0.0250 GY	0.00	0.57				
73	-0.0250 GY	0.00	0.61				
74	-0.0250 GY	0.00	0.42				
75	-0.0250 GY	0.00	0.59				

76	-0.0250	GY	0.00	0.57
77	-0.0250	GY	0.00	0.61
78	-0.0250	GY	0.00	0.42
79	-0.0250	GY	0.00	0.59
94	-0.0250	GY	0.00	0.18
95	-0.0250	GY	0.00	0.18

SELFWEIGHT Y -1.000

ACTUAL WEIGHT OF THE STRUCTURE = 10.635 KN

LOADING 2 LOADTYPE DEAD TITLE LL

MEMBER LOAD - UNIT KN METE

MEMBER	UDL	L1	L2	CON	L	LIN1	LIN2
3	-0.3500	GY	0.00	0.57			
4	-0.3500	GY	0.00	0.61			
5	-0.3500	GY	0.00	0.60			
6	-0.3500	GY	0.00	0.59			
7	-0.3500	GY	0.00	0.57			
8	-0.3500	GY	0.00	0.61			
9	-0.3500	GY	0.00	0.60			
10	-0.3500	GY	0.00	0.59			
24	-0.3500	GY	0.00	0.57			
25	-0.3500	GY	0.00	0.61			
26	-0.3500	GY	0.00	0.60			
27	-0.3500	GY	0.00	0.59			
28	-0.3500	GY	0.00	0.57			
29	-0.3500	GY	0.00	0.61			
30	-0.3500	GY	0.00	0.60			
31	-0.3500	GY	0.00	0.59			
34	-0.3500	GY	0.00	0.57			
35	-0.3500	GY	0.00	0.61			
36	-0.3500	GY	0.00	0.60			
37	-0.3500	GY	0.00	0.59			
38	-0.3500	GY	0.00	0.57			
39	-0.3500	GY	0.00	0.61			
40	-0.3500	GY	0.00	0.60			
41	-0.3500	GY	0.00	0.59			
53	-0.3500	GY	0.00	0.57			
54	-0.3500	GY	0.00	0.61			
55	-0.3500	GY	0.00	0.60			
56	-0.3500	GY	0.00	0.59			
57	-0.3500	GY	0.00	0.57			
58	-0.3500	GY	0.00	0.61			
59	-0.3500	GY	0.00	0.60			
60	-0.3500	GY	0.00	0.59			
72	-0.3500	GY	0.00	0.57			
73	-0.3500	GY	0.00	0.61			
74	-0.3500	GY	0.00	0.42			
75	-0.3500	GY	0.00	0.59			

76	-0.3500	GY	0.00	0.57
77	-0.3500	GY	0.00	0.61
78	-0.3500	GY	0.00	0.42
79	-0.3500	GY	0.00	0.59
94	-0.3500	GY	0.00	0.18
95	-0.3500	GY	0.00	0.18

LOADING 3 LOADTYPE NONE TITLE WL X

MEMBER LOAD - UNIT KN METE

MEMBER	UDL		L1	L2	CON	L	LIN1	LIN2
3	-0.0550	Y	0.00	0.57				
4	-0.0550	Y	0.00	0.61				
24	-0.0550	Y	0.00	0.57				
25	-0.0550	Y	0.00	0.61				
34	-0.0550	Y	0.00	0.57				
35	-0.0550	Y	0.00	0.61				
53	-0.0550	Y	0.00	0.57				
54	-0.0550	Y	0.00	0.61				
72	-0.0550	Y	0.00	0.57				
73	-0.0550	Y	0.00	0.61				
5	1.4400	Y	0.00	0.60				
6	1.4400	Y	0.00	0.59				
7	1.4400	Y	0.00	0.57				
8	1.4400	Y	0.00	0.61				
9	1.4400	Y	0.00	0.60				
10	1.4400	Y	0.00	0.59				
15	1.4400	Y	0.00	0.83				
18	1.4400	Y	0.00	0.83				
19	1.4400	Y	0.00	0.83				
20	1.4400	Y	0.00	0.83				
21	1.4400	Y	0.00	0.83				
26	1.4400	Y	0.00	0.60				
27	1.4400	Y	0.00	0.59				
28	1.4400	Y	0.00	0.57				
29	1.4400	Y	0.00	0.61				
30	1.4400	Y	0.00	0.60				
31	1.4400	Y	0.00	0.59				
36	1.4400	Y	0.00	0.60				
37	1.4400	Y	0.00	0.59				
38	1.4400	Y	0.00	0.57				
39	1.4400	Y	0.00	0.61				
40	1.4400	Y	0.00	0.60				
41	1.4400	Y	0.00	0.59				
44	1.4400	Y	0.00	0.83				
47	1.4400	Y	0.00	0.83				
48	1.4400	Y	0.00	0.83				
49	1.4400	Y	0.00	0.83				
50	1.4400	Y	0.00	0.83				
55	1.4400	Y	0.00	0.60				
56	1.4400	Y	0.00	0.59				

57	1.4400	Y	0.00	0.57
58	1.4400	Y	0.00	0.61
59	1.4400	Y	0.00	0.60
60	1.4400	Y	0.00	0.59
63	1.4400	Y	0.00	0.83
66	1.4400	Y	0.00	0.83
67	1.4400	Y	0.00	0.83
68	1.4400	Y	0.00	0.83
69	1.4400	Y	0.00	0.83
74	1.4400	Y	0.00	0.42
75	1.4400	Y	0.00	0.59
76	1.4400	Y	0.00	0.57
77	1.4400	Y	0.00	0.61
78	1.4400	Y	0.00	0.42
79	1.4400	Y	0.00	0.59
82	1.4400	Y	0.00	0.83
85	1.4400	Y	0.00	0.83
86	1.4400	Y	0.00	0.83
87	1.4400	Y	0.00	0.83
88	1.4400	Y	0.00	0.83
94	1.4400	Y	0.00	0.18
95	1.4400	Y	0.00	0.18

LOADING 4 LOADTYPE NONE TITLE WL Z

MEMBER LOAD - UNIT KN METE

MEMBER	UDL		L1	L2	CON	L	LIN1	LIN2
3	1.1800	Y	0.00	0.57				
4	1.1800	Y	0.00	0.61				
5	1.1800	Y	0.00	0.60				
6	1.1800	Y	0.00	0.59				
7	1.1800	Y	0.00	0.57				
8	1.1800	Y	0.00	0.61				
9	1.1800	Y	0.00	0.60				
10	1.1800	Y	0.00	0.59				
24	1.1800	Y	0.00	0.57				
25	1.1800	Y	0.00	0.61				
26	1.1800	Y	0.00	0.60				
27	1.1800	Y	0.00	0.59				
28	1.1800	Y	0.00	0.57				
29	1.1800	Y	0.00	0.61				
30	1.1800	Y	0.00	0.60				
31	1.1800	Y	0.00	0.59				
34	1.1800	Y	0.00	0.57				
35	1.1800	Y	0.00	0.61				
36	1.1800	Y	0.00	0.60				
37	1.1800	Y	0.00	0.59				
38	1.1800	Y	0.00	0.57				
39	1.1800	Y	0.00	0.61				
40	1.1800	Y	0.00	0.60				
41	1.1800	Y	0.00	0.59				

53	1.1800	Y	0.00	0.57
54	1.1800	Y	0.00	0.61
55	1.1800	Y	0.00	0.60
56	1.1800	Y	0.00	0.59
57	1.1800	Y	0.00	0.57
58	1.1800	Y	0.00	0.61
59	1.1800	Y	0.00	0.60
60	1.1800	Y	0.00	0.59
72	1.1800	Y	0.00	0.57
73	1.1800	Y	0.00	0.61
74	1.1800	Y	0.00	0.42
75	1.1800	Y	0.00	0.59
76	1.1800	Y	0.00	0.57
77	1.1800	Y	0.00	0.61
78	1.1800	Y	0.00	0.42
79	1.1800	Y	0.00	0.59
94	1.1800	Y	0.00	0.18
95	1.1800	Y	0.00	0.18

LOADING 5 LOADTYPE NONE TITLE WL-X

MEMBER LOAD - UNIT KN METE

MEMBER	UDL		L1	L2	CON	L	LIN1	LIN2
7	-0.0550	Y	0.00	0.57				
8	-0.0550	Y	0.00	0.61				
28	-0.0550	Y	0.00	0.57				
29	-0.0550	Y	0.00	0.61				
38	-0.0550	Y	0.00	0.57				
39	-0.0550	Y	0.00	0.61				
57	-0.0550	Y	0.00	0.57				
58	-0.0550	Y	0.00	0.61				
76	-0.0550	Y	0.00	0.57				
77	-0.0550	Y	0.00	0.61				
3	1.4400	Y	0.00	0.57				
4	1.4400	Y	0.00	0.61				
5	1.4400	Y	0.00	0.60				
6	1.4400	Y	0.00	0.59				
9	1.4400	Y	0.00	0.60				
10	1.4400	Y	0.00	0.59				
24	1.4400	Y	0.00	0.57				
25	1.4400	Y	0.00	0.61				
26	1.4400	Y	0.00	0.60				
27	1.4400	Y	0.00	0.59				
30	1.4400	Y	0.00	0.60				
31	1.4400	Y	0.00	0.59				
34	1.4400	Y	0.00	0.57				
35	1.4400	Y	0.00	0.61				
36	1.4400	Y	0.00	0.60				
37	1.4400	Y	0.00	0.59				
40	1.4400	Y	0.00	0.60				
41	1.4400	Y	0.00	0.59				

53	1.4400	Y	0.00	0.57
54	1.4400	Y	0.00	0.61
55	1.4400	Y	0.00	0.60
56	1.4400	Y	0.00	0.59
59	1.4400	Y	0.00	0.60
60	1.4400	Y	0.00	0.59
72	1.4400	Y	0.00	0.57
73	1.4400	Y	0.00	0.61
74	1.4400	Y	0.00	0.42
75	1.4400	Y	0.00	0.59
78	1.4400	Y	0.00	0.42
79	1.4400	Y	0.00	0.59
94	1.4400	Y	0.00	0.18
95	1.4400	Y	0.00	0.18

LOADING 6 LOADTYPE NONE TITLE WL-Z

MEMBER LOAD - UNIT KN METE

MEMBER	UDL		L1	L2	CON	L	LIN1	LIN2
3	1.1800	Y	0.00	0.57				
4	1.1800	Y	0.00	0.61				
5	1.1800	Y	0.00	0.60				
6	1.1800	Y	0.00	0.59				
7	1.1800	Y	0.00	0.57				
8	1.1800	Y	0.00	0.61				
9	1.1800	Y	0.00	0.60				
10	1.1800	Y	0.00	0.59				
24	1.1800	Y	0.00	0.57				
25	1.1800	Y	0.00	0.61				
26	1.1800	Y	0.00	0.60				
27	1.1800	Y	0.00	0.59				
28	1.1800	Y	0.00	0.57				
29	1.1800	Y	0.00	0.61				
30	1.1800	Y	0.00	0.60				
31	1.1800	Y	0.00	0.59				
34	1.1800	Y	0.00	0.57				
35	1.1800	Y	0.00	0.61				
36	1.1800	Y	0.00	0.60				
37	1.1800	Y	0.00	0.59				
38	1.1800	Y	0.00	0.57				
39	1.1800	Y	0.00	0.61				
40	1.1800	Y	0.00	0.60				
41	1.1800	Y	0.00	0.59				
53	1.1800	Y	0.00	0.57				
54	1.1800	Y	0.00	0.61				
55	1.1800	Y	0.00	0.60				
56	1.1800	Y	0.00	0.59				
57	1.1800	Y	0.00	0.57				
58	1.1800	Y	0.00	0.61				
59	1.1800	Y	0.00	0.60				
60	1.1800	Y	0.00	0.59				

72	1.1800 Y	0.00	0.57
73	1.1800 Y	0.00	0.61
74	1.1800 Y	0.00	0.42
75	1.1800 Y	0.00	0.59
76	1.1800 Y	0.00	0.57
77	1.1800 Y	0.00	0.61
78	1.1800 Y	0.00	0.42
79	1.1800 Y	0.00	0.59
94	1.1800 Y	0.00	0.18
95	1.1800 Y	0.00	0.18

FOR LOADING - 1
APPLIED JOINT EQUIVALENT LOADS

JOINT	FORCE-X	FORCE-Y	FORCE-Z	MOM-X	MOM-Y	MOM-Z
1	0.00000E+00	-2.05074E-01	0.00000E+00	1.20778E-02	0.00000E+00	0.00000E+00
2	0.00000E+00	-2.05074E-01	0.00000E+00	1.20778E-02	0.00000E+00	0.00000E+00
3	7.52229E-10	-1.51290E-01	0.00000E+00	0.00000E+00	0.00000E+00	-5.99421E-03
4	-6.00884E-10	-1.51290E-01	0.00000E+00	0.00000E+00	0.00000E+00	5.99419E-03
5	2.52374E-12	-1.94945E-01	0.00000E+00	0.00000E+00	0.00000E+00	-2.34863E-07
6	-3.40003E-10	-1.94206E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.13876E-03
7	-5.43465E-10	-1.98337E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.47278E-04
8	4.83637E-10	-1.95833E-01	0.00000E+00	0.00000E+00	0.00000E+00	8.05012E-05
9	2.13727E-10	-1.94206E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.13881E-03
10	6.10021E-10	-1.98337E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.47312E-04
11	-1.36937E-10	-1.95835E-01	0.00000E+00	0.00000E+00	0.00000E+00	-8.02617E-05
12	0.00000E+00	-8.79559E-02	0.00000E+00	4.02594E-03	0.00000E+00	0.00000E+00
13	0.00000E+00	-8.79559E-02	0.00000E+00	4.02594E-03	0.00000E+00	0.00000E+00
14	7.52229E-10	-1.23627E-01	0.00000E+00	0.00000E+00	0.00000E+00	-5.99421E-03
15	-6.00884E-10	-1.23627E-01	0.00000E+00	0.00000E+00	0.00000E+00	5.99419E-03
16	2.52374E-12	-1.67281E-01	0.00000E+00	0.00000E+00	0.00000E+00	-2.34863E-07
17	-3.40003E-10	-1.66542E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.13876E-03
18	-5.43465E-10	-1.70674E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.47278E-04
19	4.83637E-10	-1.68170E-01	0.00000E+00	0.00000E+00	0.00000E+00	8.05012E-05
20	2.13727E-10	-1.66542E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.13881E-03
21	6.10021E-10	-1.70674E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.47312E-04
22	-1.36937E-10	-1.68171E-01	0.00000E+00	0.00000E+00	0.00000E+00	-8.02617E-05
23	0.00000E+00	-2.63633E-01	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00
24	7.52229E-10	-1.51290E-01	0.00000E+00	0.00000E+00	0.00000E+00	-5.99421E-03
25	0.00000E+00	-2.63633E-01	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00
26	-6.00884E-10	-1.51290E-01	0.00000E+00	0.00000E+00	0.00000E+00	5.99419E-03
27	-3.40003E-10	-1.94206E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.13876E-03
28	-5.43465E-10	-1.98337E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.47278E-04
29	4.83637E-10	-1.95833E-01	0.00000E+00	0.00000E+00	0.00000E+00	8.05012E-05
30	2.52374E-12	-1.94945E-01	0.00000E+00	0.00000E+00	0.00000E+00	-2.34863E-07
31	2.13727E-10	-1.94206E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.13881E-03
32	6.10021E-10	-1.98337E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.47312E-04
33	-1.36937E-10	-1.95835E-01	0.00000E+00	0.00000E+00	0.00000E+00	-8.02617E-05
34	0.00000E+00	-2.05074E-01	0.00000E+00	-1.20778E-02	0.00000E+00	0.00000E+00
35	7.52229E-10	-1.51290E-01	0.00000E+00	0.00000E+00	0.00000E+00	-5.99421E-03
36	0.00000E+00	-2.05074E-01	0.00000E+00	-1.20778E-02	0.00000E+00	0.00000E+00
37	-6.00884E-10	-1.51290E-01	0.00000E+00	0.00000E+00	0.00000E+00	5.99419E-03
38	-3.40003E-10	-1.94206E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.13876E-03
39	-5.43465E-10	-1.98337E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.47278E-04
40	4.83637E-10	-1.95833E-01	0.00000E+00	0.00000E+00	0.00000E+00	8.05012E-05
41	2.52374E-12	-1.94945E-01	0.00000E+00	0.00000E+00	0.00000E+00	-2.34863E-07

STAAD SPACE -- PAGE NO. 12

APPLIED JOINT EQUIVALENT LOADS

JOINT	FORCE-X	FORCE-Y	FORCE-Z	MOM-X	MOM-Y	MOM-Z
42	2.13727E-10	-1.94206E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.13881E-03
43	6.10021E-10	-1.98337E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.47312E-04
44	-1.36937E-10	-1.95835E-01	0.00000E+00	0.00000E+00	0.00000E+00	-8.02617E-05
45	0.00000E+00	-2.50388E-01	0.00000E+00	-4.02594E-03	0.00000E+00	-4.18444E-02
46	7.52229E-10	-1.23627E-01	0.00000E+00	0.00000E+00	0.00000E+00	-5.99421E-03
47	0.00000E+00	-2.50388E-01	0.00000E+00	-4.02594E-03	0.00000E+00	4.18444E-02
48	-6.00884E-10	-1.23627E-01	0.00000E+00	0.00000E+00	0.00000E+00	5.99419E-03
49	-3.40003E-10	-1.66542E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.13876E-03
50	-1.76338E-09	-1.49289E-01	0.00000E+00	0.00000E+00	0.00000E+00	3.73422E-03
51	2.99639E-10	-1.18857E-01	0.00000E+00	0.00000E+00	0.00000E+00	-6.26603E-03
52	2.52374E-12	-1.67281E-01	0.00000E+00	0.00000E+00	0.00000E+00	-2.34863E-07
53	2.13727E-10	-1.66542E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.13881E-03
54	1.14090E-09	-1.49289E-01	0.00000E+00	0.00000E+00	0.00000E+00	-3.73425E-03
55	-2.97115E-10	-1.18858E-01	0.00000E+00	0.00000E+00	0.00000E+00	6.26626E-03
56	0.00000E+00	-3.93773E-01	0.00000E+00	0.00000E+00	0.00000E+00	-3.36721E-09
57	0.00000E+00	-3.93773E-01	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00
60	-3.06384E-10	-1.39607E-01	0.00000E+00	0.00000E+00	0.00000E+00	2.75959E-03
61	-3.84782E-11	-1.39607E-01	0.00000E+00	0.00000E+00	0.00000E+00	-2.75959E-03
62	0.00000E+00	-1.17118E-01	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00
63	0.00000E+00	-1.17118E-01	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00
64	0.00000E+00	-1.17118E-01	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00
65	0.00000E+00	-1.17118E-01	0.00000E+00	0.00000E+00	0.00000E+00	0.00000E+00

STATIC LOAD/REACTION/EQUILIBRIUM SUMMARY FOR CASE NO. 1
LOADTYPE DEAD TITLE DL

CENTER OF FORCE BASED ON Y FORCES ONLY (METE).
(FORCES IN NON-GLOBAL DIRECTIONS WILL INVALIDATE RESULTS)

X = 0.236850496E+01
Y = 0.373460525E+00
Z = 0.100769215E+01

TOTAL APPLIED LOAD 1

***TOTAL APPLIED LOAD (KN METE) SUMMARY (LOADING 1)
SUMMATION FORCE-X = 0.00
SUMMATION FORCE-Y = -11.29
SUMMATION FORCE-Z = 0.00

SUMMATION OF MOMENTS AROUND THE ORIGIN-
MX= 11.38 MY= -0.00 MZ= -26.74

TOTAL REACTION LOAD 1

***TOTAL REACTION LOAD(KN METE) SUMMARY (LOADING 1)
SUMMATION FORCE-X = -0.00
SUMMATION FORCE-Y = 11.29
SUMMATION FORCE-Z = -0.00

SUMMATION OF MOMENTS AROUND THE ORIGIN-
MX= -11.38 MY= 0.00 MZ= 26.74

STAAD SPACE -- PAGE NO. 13

MAXIMUM DISPLACEMENTS (CM /RADIANS) (LOADING 1)

	MAXIMUMS	AT NODE
X =	5.52841E-03	25
Y =	-2.62843E-02	30
Z =	6.11069E-04	5
RX=	4.60824E-05	1
RY=	5.67046E-05	2
RZ=	-1.22127E-04	27

EXTERNAL AND INTERNAL JOINT LOAD SUMMARY (KN METE)-

JT	EXT FX/ INT FX	EXT FY/ INT FY	EXT FZ/ INT FZ	EXT MX/ INT MX	EXT MY/ INT MY	EXT MZ/ INT MZ	
							SUPPORT=1
62	0.00	-0.12	0.00	0.00	0.00	0.00	
	-2.67	-3.12	-0.87	-0.00	0.00	0.00	111000
63	0.00	-0.12	0.00	0.00	0.00	0.00	
	2.67	-3.12	-0.87	-0.00	-0.00	-0.00	111000
64	0.00	-0.12	0.00	0.00	0.00	0.00	
	-2.50	-2.29	0.87	0.00	-0.00	-0.00	111000
65	0.00	-0.12	0.00	0.00	0.00	0.00	
	2.50	-2.29	0.87	0.00	0.00	0.00	111000

FOR LOADING - 2
APPLIED JOINT EQUIVALENT LOADS

JOINT	FORCE-X	FORCE-Y	FORCE-Z	MOM-X	MOM-Y	MOM-Z
3	1.87313E-09	-9.90670E-02	0.00000E+00	0.00000E+00	0.00000E+00	-8.92083E-03
4	-2.58490E-09	-9.90669E-02	0.00000E+00	0.00000E+00	0.00000E+00	8.92080E-03
5	-3.17057E-11	-2.07785E-01	0.00000E+00	0.00000E+00	0.00000E+00	-3.49348E-07
6	-1.76778E-09	-2.06685E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.69475E-03
7	-1.00753E-09	-2.12834E-01	0.00000E+00	0.00000E+00	0.00000E+00	2.19184E-04
8	-2.05222E-09	-2.09107E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.19804E-04
9	1.66630E-10	-2.06685E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.69482E-03
10	2.44745E-09	-2.12834E-01	0.00000E+00	0.00000E+00	0.00000E+00	-2.19236E-04
11	2.40574E-10	-2.09109E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.19447E-04
14	1.87313E-09	-9.90670E-02	0.00000E+00	0.00000E+00	0.00000E+00	-8.92083E-03
15	-2.58490E-09	-9.90669E-02	0.00000E+00	0.00000E+00	0.00000E+00	8.92080E-03
16	-3.17057E-11	-2.07785E-01	0.00000E+00	0.00000E+00	0.00000E+00	-3.49348E-07
17	-1.76778E-09	-2.06685E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.69475E-03
18	-1.00753E-09	-2.12834E-01	0.00000E+00	0.00000E+00	0.00000E+00	2.19184E-04
19	-2.05222E-09	-2.09107E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.19804E-04
20	1.66630E-10	-2.06685E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.69482E-03
21	2.44745E-09	-2.12834E-01	0.00000E+00	0.00000E+00	0.00000E+00	-2.19236E-04
22	2.40574E-10	-2.09109E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.19447E-04
24	1.87313E-09	-9.90670E-02	0.00000E+00	0.00000E+00	0.00000E+00	-8.92083E-03
26	-2.58490E-09	-9.90669E-02	0.00000E+00	0.00000E+00	0.00000E+00	8.92080E-03
27	-1.76778E-09	-2.06685E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.69475E-03
28	-1.00753E-09	-2.12834E-01	0.00000E+00	0.00000E+00	0.00000E+00	2.19184E-04
29	-2.05222E-09	-2.09107E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.19804E-04
30	-3.17057E-11	-2.07785E-01	0.00000E+00	0.00000E+00	0.00000E+00	-3.49348E-07
31	1.66630E-10	-2.06685E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.69482E-03
32	2.44745E-09	-2.12834E-01	0.00000E+00	0.00000E+00	0.00000E+00	-2.19236E-04
33	2.40574E-10	-2.09109E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.19447E-04
35	1.87313E-09	-9.90670E-02	0.00000E+00	0.00000E+00	0.00000E+00	-8.92083E-03

STAAD SPACE -- PAGE NO. 14

APPLIED JOINT EQUIVALENT LOADS

JOINT	FORCE-X	FORCE-Y	FORCE-Z	MOM-X	MOM-Y	MOM-Z
37	-2.58490E-09	-9.90669E-02	0.00000E+00	0.00000E+00	0.00000E+00	8.92080E-03
38	-1.76778E-09	-2.06685E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.69475E-03
39	-1.00753E-09	-2.12834E-01	0.00000E+00	0.00000E+00	0.00000E+00	2.19184E-04
40	-2.05222E-09	-2.09107E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.19804E-04
41	-3.17057E-11	-2.07785E-01	0.00000E+00	0.00000E+00	0.00000E+00	-3.49348E-07
42	1.66630E-10	-2.06685E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.69482E-03
43	2.44745E-09	-2.12834E-01	0.00000E+00	0.00000E+00	0.00000E+00	-2.19236E-04
44	2.40574E-10	-2.09109E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.19447E-04
46	1.87313E-09	-9.90670E-02	0.00000E+00	0.00000E+00	0.00000E+00	-8.92083E-03
48	-2.58490E-09	-9.90669E-02	0.00000E+00	0.00000E+00	0.00000E+00	8.92080E-03
49	-1.76778E-09	-2.06685E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.69475E-03
50	1.30156E-09	-1.81008E-01	0.00000E+00	0.00000E+00	0.00000E+00	5.55742E-03
51	3.50856E-10	-1.35717E-01	0.00000E+00	0.00000E+00	0.00000E+00	-9.32536E-03
52	-3.17057E-11	-2.07785E-01	0.00000E+00	0.00000E+00	0.00000E+00	-3.49348E-07
53	1.66630E-10	-2.06685E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.69482E-03
54	2.18088E-09	-1.81008E-01	0.00000E+00	0.00000E+00	0.00000E+00	-5.55747E-03
55	8.21975E-12	-1.35719E-01	0.00000E+00	0.00000E+00	0.00000E+00	9.32571E-03
60	7.75533E-10	-1.05216E-01	0.00000E+00	0.00000E+00	0.00000E+00	4.10694E-03
61	-9.03740E-10	-1.05216E-01	0.00000E+00	0.00000E+00	0.00000E+00	-4.10693E-03

STATIC LOAD/REACTION/EQUILIBRIUM SUMMARY FOR CASE NO. 2
LOADTYPE DEAD TITLE LL

CENTER OF FORCE BASED ON Y FORCES ONLY (METE).
(FORCES IN NON-GLOBAL DIRECTIONS WILL INVALIDATE RESULTS)

X = 0.236850502E+01
Y = 0.543857891E+00
Z = 0.825000025E+00

TOTAL APPLIED LOAD 2

***TOTAL APPLIED LOAD (KN METE) SUMMARY (LOADING 2)
SUMMATION FORCE-X = -0.00
SUMMATION FORCE-Y = -8.32
SUMMATION FORCE-Z = 0.00

SUMMATION OF MOMENTS AROUND THE ORIGIN-
MX= 6.86 MY= -0.00 MZ= -19.70

TOTAL REACTION LOAD 2

***TOTAL REACTION LOAD(KN METE) SUMMARY (LOADING 2)
SUMMATION FORCE-X = 0.00
SUMMATION FORCE-Y = 8.32
SUMMATION FORCE-Z = -0.00

SUMMATION OF MOMENTS AROUND THE ORIGIN-
MX= -6.86 MY= 0.00 MZ= 19.70

STAAD SPACE -- PAGE NO. 15

MAXIMUM DISPLACEMENTS (CM /RADIANS) (LOADING 2)

	MAXIMUMS	AT NODE
X =	-5.86624E-03	23
Y =	-2.64172E-02	30
Z =	-2.08300E-04	41
RX=	3.32765E-05	1
RY=	5.99108E-05	34
RZ=	-1.29947E-04	27

EXTERNAL AND INTERNAL JOINT LOAD SUMMARY (KN METE)-

JT	EXT FX/ INT FX	EXT FY/ INT FY	EXT FZ/ INT FZ	EXT MX/ INT MX	EXT MY/ INT MY	EXT MZ/ INT MZ	
							SUPPORT=1
62	0.00	0.00	0.00	0.00	0.00	0.00	
	-2.68	-2.08	-0.69	-0.00	-0.00	-0.00	111000
63	0.00	0.00	0.00	0.00	0.00	0.00	
	2.68	-2.08	-0.69	-0.00	-0.00	-0.00	111000
64	0.00	0.00	0.00	0.00	0.00	0.00	
	-2.88	-2.08	0.69	-0.00	-0.00	0.00	111000
65	0.00	0.00	0.00	0.00	0.00	0.00	
	2.88	-2.08	0.69	0.00	0.00	0.00	111000

FOR LOADING - 3
APPLIED JOINT EQUIVALENT LOADS

JOINT	FORCE-X	FORCE-Y	FORCE-Z	MOM-X	MOM-Y	MOM-Z
3	4.64676E-03	-1.48580E-02	0.00000E+00	0.00000E+00	0.00000E+00	-1.46880E-03
4	1.21661E-01	3.89009E-01	0.00000E+00	0.00000E+00	0.00000E+00	-3.84558E-02
5	6.34498E-11	2.04265E+00	0.00000E+00	0.00000E+00	0.00000E+00	1.43443E-06
6	9.23926E-03	-3.11338E-02	0.00000E+00	0.00000E+00	0.00000E+00	-2.64496E-04
7	-6.74075E-02	4.10583E-01	0.00000E+00	0.00000E+00	0.00000E+00	4.51113E-02
8	-8.20800E-02	2.04218E+00	0.00000E+00	0.00000E+00	0.00000E+00	-1.08535E-03
9	2.41901E-01	2.00314E+00	0.00000E+00	0.00000E+00	0.00000E+00	-6.92530E-03
10	1.92240E-01	2.04099E+00	0.00000E+00	0.00000E+00	0.00000E+00	2.00318E-03
11	8.20800E-02	2.04219E+00	0.00000E+00	0.00000E+00	0.00000E+00	1.08389E-03
14	4.64676E-03	-1.48580E-02	0.00000E+00	0.00000E+00	0.00000E+00	-1.46880E-03
15	1.21661E-01	3.89009E-01	0.00000E+00	0.00000E+00	0.00000E+00	-3.84558E-02
16	6.34498E-11	1.44865E+00	0.00000E+00	0.00000E+00	0.00000E+00	1.43443E-06
17	9.23926E-03	-3.11338E-02	0.00000E+00	0.00000E+00	0.00000E+00	-2.64496E-04
18	-6.74075E-02	4.10583E-01	0.00000E+00	0.00000E+00	0.00000E+00	4.51113E-02
19	-8.20800E-02	1.44818E+00	0.00000E+00	0.00000E+00	0.00000E+00	-1.08535E-03
20	2.41901E-01	1.40914E+00	0.00000E+00	0.00000E+00	0.00000E+00	-6.92530E-03
21	1.92240E-01	1.44699E+00	0.00000E+00	0.00000E+00	0.00000E+00	2.00318E-03
22	8.20800E-02	1.44819E+00	0.00000E+00	0.00000E+00	0.00000E+00	1.08389E-03
24	4.64676E-03	-1.48580E-02	0.00000E+00	0.00000E+00	0.00000E+00	-1.46880E-03
26	1.21661E-01	3.89009E-01	0.00000E+00	0.00000E+00	0.00000E+00	-3.84558E-02
27	9.23926E-03	-3.11338E-02	0.00000E+00	0.00000E+00	0.00000E+00	-2.64496E-04
28	-6.74075E-02	4.10583E-01	0.00000E+00	0.00000E+00	0.00000E+00	4.51113E-02
29	-8.20800E-02	2.04218E+00	0.00000E+00	0.00000E+00	0.00000E+00	-1.08535E-03
30	6.34498E-11	2.04265E+00	0.00000E+00	0.00000E+00	0.00000E+00	1.43443E-06
31	2.41901E-01	2.00314E+00	0.00000E+00	0.00000E+00	0.00000E+00	-6.92530E-03
32	1.92240E-01	2.04099E+00	0.00000E+00	0.00000E+00	0.00000E+00	2.00318E-03
33	8.20800E-02	2.04219E+00	0.00000E+00	0.00000E+00	0.00000E+00	1.08389E-03
35	4.64676E-03	-1.48580E-02	0.00000E+00	0.00000E+00	0.00000E+00	-1.46880E-03

STAAD SPACE -- PAGE NO. 16

APPLIED JOINT EQUIVALENT LOADS

JOINT	FORCE-X	FORCE-Y	FORCE-Z	MOM-X	MOM-Y	MOM-Z
37	1.21661E-01	3.89009E-01	0.00000E+00	0.00000E+00	0.00000E+00	-3.84558E-02
38	9.23926E-03	-3.11338E-02	0.00000E+00	0.00000E+00	0.00000E+00	-2.64496E-04
39	-6.74075E-02	4.10583E-01	0.00000E+00	0.00000E+00	0.00000E+00	4.51113E-02
40	-8.20800E-02	2.04218E+00	0.00000E+00	0.00000E+00	0.00000E+00	-1.08535E-03
41	6.34498E-11	2.04265E+00	0.00000E+00	0.00000E+00	0.00000E+00	1.43443E-06
42	2.41901E-01	2.00314E+00	0.00000E+00	0.00000E+00	0.00000E+00	-6.92530E-03
43	1.92240E-01	2.04099E+00	0.00000E+00	0.00000E+00	0.00000E+00	2.00318E-03
44	8.20800E-02	2.04219E+00	0.00000E+00	0.00000E+00	0.00000E+00	1.08389E-03
46	4.64676E-03	-1.48580E-02	0.00000E+00	0.00000E+00	0.00000E+00	-1.46880E-03
48	1.21661E-01	3.89009E-01	0.00000E+00	0.00000E+00	0.00000E+00	-3.84558E-02
49	9.23926E-03	-3.11338E-02	0.00000E+00	0.00000E+00	0.00000E+00	-2.64496E-04
50	-4.56289E-02	2.81466E-01	0.00000E+00	0.00000E+00	0.00000E+00	2.28380E-02
51	-3.18586E-02	1.15044E+00	0.00000E+00	0.00000E+00	0.00000E+00	3.83237E-02
52	6.34498E-11	1.44865E+00	0.00000E+00	0.00000E+00	0.00000E+00	1.43443E-06
53	2.41901E-01	1.40914E+00	0.00000E+00	0.00000E+00	0.00000E+00	-6.92530E-03
54	1.70461E-01	1.31787E+00	0.00000E+00	0.00000E+00	0.00000E+00	2.42764E-02
55	3.18586E-02	1.15045E+00	0.00000E+00	0.00000E+00	0.00000E+00	-3.83251E-02
60	-7.20000E-02	4.26859E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.71358E-02
61	7.20000E-02	4.26859E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.71358E-02

STATIC LOAD/REACTION/EQUILIBRIUM SUMMARY FOR CASE NO. 3
LOADTYPE NONE TITLE WL X

CENTER OF FORCE BASED ON Y FORCES ONLY (METE).
(FORCES IN NON-GLOBAL DIRECTIONS WILL INVALIDATE RESULTS)

X = 0.296250377E+01
Y = 0.601544337E+00
Z = 0.825000019E+00

TOTAL APPLIED LOAD 3

***TOTAL APPLIED LOAD (KN METE) SUMMARY (LOADING 3)
SUMMATION FORCE-X = 2.51
SUMMATION FORCE-Y = 48.68
SUMMATION FORCE-Z = 0.00

SUMMATION OF MOMENTS AROUND THE ORIGIN-
MX= -40.16 MY= 2.07 MZ= 143.18

TOTAL REACTION LOAD 3

***TOTAL REACTION LOAD(KN METE) SUMMARY (LOADING 3)
SUMMATION FORCE-X = -2.51
SUMMATION FORCE-Y = -48.68
SUMMATION FORCE-Z = -0.00

SUMMATION OF MOMENTS AROUND THE ORIGIN-
MX= 40.16 MY= -2.07 MZ= -143.18

STAAD SPACE -- PAGE NO. 17

MAXIMUM DISPLACEMENTS (CM /RADIANS) (LOADING 3)

	MAXIMUMS	AT NODE
X =	5.18222E-02	23
Y =	2.20299E-01	30
Z =	-2.07677E-03	57
RX=	3.15113E-04	36
RY=	5.35879E-04	1
RZ=	-1.25631E-03	31

EXTERNAL AND INTERNAL JOINT LOAD SUMMARY (KN METE)-

JT	EXT FX/ INT FX	EXT FY/ INT FY	EXT FZ/ INT FZ	EXT MX/ INT MX	EXT MY/ INT MY	EXT MZ/ INT MZ	
							SUPPORT=1
62	0.00	0.00	0.00	0.00	0.00	0.00	
	21.50	9.23	4.40	0.00	-0.00	0.00	111000
63	0.00	0.00	0.00	0.00	0.00	0.00	
	-20.25	15.11	8.21	0.00	-0.00	0.00	111000
64	0.00	0.00	0.00	0.00	0.00	0.00	
	20.08	9.10	-4.39	-0.00	0.00	-0.00	111000
65	0.00	0.00	0.00	0.00	0.00	0.00	
	-18.82	15.24	-8.21	-0.00	0.00	-0.00	111000

FOR LOADING - 4
APPLIED JOINT EQUIVALENT LOADS

JOINT	FORCE-X	FORCE-Y	FORCE-Z	MOM-X	MOM-Y	MOM-Z
3	-9.96941E-02	3.18772E-01	0.00000E+00	0.00000E+00	0.00000E+00	3.15125E-02
4	9.96941E-02	3.18771E-01	0.00000E+00	0.00000E+00	0.00000E+00	-3.15124E-02
5	4.75344E-10	7.00336E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.17516E-06
6	-1.98224E-01	6.67963E-01	0.00000E+00	0.00000E+00	0.00000E+00	5.67464E-03
7	-1.57530E-01	6.98978E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.64132E-03
8	-6.72600E-02	6.99952E-01	0.00000E+00	0.00000E+00	0.00000E+00	-8.89385E-04
9	1.98224E-01	6.67963E-01	0.00000E+00	0.00000E+00	0.00000E+00	-5.67489E-03
10	1.57530E-01	6.98979E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.64149E-03
11	6.72600E-02	6.99958E-01	0.00000E+00	0.00000E+00	0.00000E+00	8.88183E-04
14	-9.96941E-02	3.18772E-01	0.00000E+00	0.00000E+00	0.00000E+00	3.15125E-02
15	9.96941E-02	3.18771E-01	0.00000E+00	0.00000E+00	0.00000E+00	-3.15124E-02
16	4.75344E-10	7.00336E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.17516E-06
17	-1.98224E-01	6.67963E-01	0.00000E+00	0.00000E+00	0.00000E+00	5.67464E-03
18	-1.57530E-01	6.98978E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.64132E-03
19	-6.72600E-02	6.99952E-01	0.00000E+00	0.00000E+00	0.00000E+00	-8.89385E-04
20	1.98224E-01	6.67963E-01	0.00000E+00	0.00000E+00	0.00000E+00	-5.67489E-03
21	1.57530E-01	6.98979E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.64149E-03
22	6.72600E-02	6.99958E-01	0.00000E+00	0.00000E+00	0.00000E+00	8.88183E-04
24	-9.96941E-02	3.18772E-01	0.00000E+00	0.00000E+00	0.00000E+00	3.15125E-02
26	9.96941E-02	3.18771E-01	0.00000E+00	0.00000E+00	0.00000E+00	-3.15124E-02
27	-1.98224E-01	6.67963E-01	0.00000E+00	0.00000E+00	0.00000E+00	5.67464E-03
28	-1.57530E-01	6.98978E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.64132E-03
29	-6.72600E-02	6.99952E-01	0.00000E+00	0.00000E+00	0.00000E+00	-8.89385E-04
30	4.75344E-10	7.00336E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.17516E-06
31	1.98224E-01	6.67963E-01	0.00000E+00	0.00000E+00	0.00000E+00	-5.67489E-03
32	1.57530E-01	6.98979E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.64149E-03
33	6.72600E-02	6.99958E-01	0.00000E+00	0.00000E+00	0.00000E+00	8.88183E-04
35	-9.96941E-02	3.18772E-01	0.00000E+00	0.00000E+00	0.00000E+00	3.15125E-02

STAAD SPACE -- PAGE NO. 18

APPLIED JOINT EQUIVALENT LOADS

JOINT	FORCE-X	FORCE-Y	FORCE-Z	MOM-X	MOM-Y	MOM-Z
37	9.96941E-02	3.18771E-01	0.00000E+00	0.00000E+00	0.00000E+00	-3.15124E-02
38	-1.98224E-01	6.67963E-01	0.00000E+00	0.00000E+00	0.00000E+00	5.67464E-03
39	-1.57530E-01	6.98978E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.64132E-03
40	-6.72600E-02	6.99952E-01	0.00000E+00	0.00000E+00	0.00000E+00	-8.89385E-04
41	4.75344E-10	7.00336E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.17516E-06
42	1.98224E-01	6.67963E-01	0.00000E+00	0.00000E+00	0.00000E+00	-5.67489E-03
43	1.57530E-01	6.98979E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.64149E-03
44	6.72600E-02	6.99958E-01	0.00000E+00	0.00000E+00	0.00000E+00	8.88183E-04
46	-9.96941E-02	3.18772E-01	0.00000E+00	0.00000E+00	0.00000E+00	3.15125E-02
48	9.96941E-02	3.18771E-01	0.00000E+00	0.00000E+00	0.00000E+00	-3.15124E-02
49	-1.98224E-01	6.67963E-01	0.00000E+00	0.00000E+00	0.00000E+00	5.67464E-03
50	-1.39684E-01	5.93174E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.98930E-02
51	-2.61063E-02	4.55970E-01	0.00000E+00	0.00000E+00	0.00000E+00	3.14041E-02
52	4.75344E-10	7.00336E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.17516E-06
53	1.98224E-01	6.67963E-01	0.00000E+00	0.00000E+00	0.00000E+00	-5.67489E-03
54	1.39684E-01	5.93174E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.98932E-02
55	2.61063E-02	4.55976E-01	0.00000E+00	0.00000E+00	0.00000E+00	-3.14053E-02
60	-5.90000E-02	3.49787E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.40418E-02
61	5.90000E-02	3.49787E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.40418E-02

STATIC LOAD/REACTION/EQUILIBRIUM SUMMARY FOR CASE NO. 4
LOADTYPE NONE TITLE WL Z

CENTER OF FORCE BASED ON Y FORCES ONLY (METE).
(FORCES IN NON-GLOBAL DIRECTIONS WILL INVALIDATE RESULTS)

X = 0.236850501E+01
Y = 0.546256798E+00
Z = 0.825000019E+00

TOTAL APPLIED LOAD 4

***TOTAL APPLIED LOAD (KN METE) SUMMARY (LOADING 4)
SUMMATION FORCE-X = -0.00
SUMMATION FORCE-Y = 27.36
SUMMATION FORCE-Z = 0.00

SUMMATION OF MOMENTS AROUND THE ORIGIN-
MX= -22.57 MY= -0.00 MZ= 64.80

TOTAL REACTION LOAD 4

***TOTAL REACTION LOAD(KN METE) SUMMARY (LOADING 4)
SUMMATION FORCE-X = 0.00
SUMMATION FORCE-Y = -27.36
SUMMATION FORCE-Z = -0.00

SUMMATION OF MOMENTS AROUND THE ORIGIN-
MX= 22.57 MY= 0.00 MZ= -64.80

STAAD SPACE -- PAGE NO. 19

MAXIMUM DISPLACEMENTS (CM /RADIANS) (LOADING 4)

	MAXIMUMS	AT NODE
X =	-1.88090E-02	25
Y =	8.49196E-02	30
Z =	6.78672E-04	41
RX=	-1.09565E-04	1
RY=	-1.92162E-04	34
RZ=	4.18559E-04	27

EXTERNAL AND INTERNAL JOINT LOAD SUMMARY (KN METE)-

JT	EXT FX/ INT FX	EXT FY/ INT FY	EXT FZ/ INT FZ	EXT MX/ INT MX	EXT MY/ INT MY	EXT MZ/ INT MZ	
							SUPPORT=1
62	0.00	0.00	0.00	0.00	0.00	0.00	
	8.60	6.84	2.27	-0.00	-0.00	0.00	111000
63	0.00	0.00	0.00	0.00	0.00	0.00	
	-8.60	6.84	2.27	-0.00	0.00	0.00	111000
64	0.00	0.00	0.00	0.00	0.00	0.00	
	9.24	6.84	-2.27	-0.00	-0.00	-0.00	111000
65	0.00	0.00	0.00	0.00	0.00	0.00	
	-9.24	6.84	-2.27	-0.00	-0.00	-0.00	111000

FOR LOADING - 5
APPLIED JOINT EQUIVALENT LOADS

JOINT	FORCE-X	FORCE-Y	FORCE-Z	MOM-X	MOM-Y	MOM-Z
3	-1.21661E-01	3.89009E-01	0.00000E+00	0.00000E+00	0.00000E+00	3.84559E-02
4	-4.64676E-03	-1.48580E-02	0.00000E+00	0.00000E+00	0.00000E+00	1.46880E-03
5	6.34498E-11	8.54647E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.43443E-06
6	-2.41901E-01	8.15141E-01	0.00000E+00	0.00000E+00	0.00000E+00	6.92498E-03
7	-1.92240E-01	8.52991E-01	0.00000E+00	0.00000E+00	0.00000E+00	-2.00296E-03
8	-8.20800E-02	8.54179E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.08535E-03
9	-9.23926E-03	-3.11339E-02	0.00000E+00	0.00000E+00	0.00000E+00	2.64508E-04
10	6.74075E-02	4.10583E-01	0.00000E+00	0.00000E+00	0.00000E+00	-4.51112E-02
11	8.20800E-02	8.54186E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.08389E-03
14	-1.21661E-01	3.89009E-01	0.00000E+00	0.00000E+00	0.00000E+00	3.84559E-02
15	-4.64676E-03	-1.48580E-02	0.00000E+00	0.00000E+00	0.00000E+00	1.46880E-03
16	6.34498E-11	8.54647E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.43443E-06
17	-2.41901E-01	8.15141E-01	0.00000E+00	0.00000E+00	0.00000E+00	6.92498E-03
18	-1.92240E-01	8.52991E-01	0.00000E+00	0.00000E+00	0.00000E+00	-2.00296E-03
19	-8.20800E-02	8.54179E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.08535E-03
20	-9.23926E-03	-3.11339E-02	0.00000E+00	0.00000E+00	0.00000E+00	2.64508E-04
21	6.74075E-02	4.10583E-01	0.00000E+00	0.00000E+00	0.00000E+00	-4.51112E-02
22	8.20800E-02	8.54186E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.08389E-03
24	-1.21661E-01	3.89009E-01	0.00000E+00	0.00000E+00	0.00000E+00	3.84559E-02
26	-4.64676E-03	-1.48580E-02	0.00000E+00	0.00000E+00	0.00000E+00	1.46880E-03
27	-2.41901E-01	8.15141E-01	0.00000E+00	0.00000E+00	0.00000E+00	6.92498E-03
28	-1.92240E-01	8.52991E-01	0.00000E+00	0.00000E+00	0.00000E+00	-2.00296E-03
29	-8.20800E-02	8.54179E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.08535E-03
30	6.34498E-11	8.54647E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.43443E-06
31	-9.23926E-03	-3.11339E-02	0.00000E+00	0.00000E+00	0.00000E+00	2.64508E-04
32	6.74075E-02	4.10583E-01	0.00000E+00	0.00000E+00	0.00000E+00	-4.51112E-02
33	8.20800E-02	8.54186E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.08389E-03
35	-1.21661E-01	3.89009E-01	0.00000E+00	0.00000E+00	0.00000E+00	3.84559E-02

STAAD SPACE -- PAGE NO. 20

APPLIED JOINT EQUIVALENT LOADS

JOINT	FORCE-X	FORCE-Y	FORCE-Z	MOM-X	MOM-Y	MOM-Z
37	-4.64676E-03	-1.48580E-02	0.00000E+00	0.00000E+00	0.00000E+00	1.46880E-03
38	-2.41901E-01	8.15141E-01	0.00000E+00	0.00000E+00	0.00000E+00	6.92498E-03
39	-1.92240E-01	8.52991E-01	0.00000E+00	0.00000E+00	0.00000E+00	-2.00296E-03
40	-8.20800E-02	8.54179E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.08535E-03
41	6.34498E-11	8.54647E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.43443E-06
42	-9.23926E-03	-3.11339E-02	0.00000E+00	0.00000E+00	0.00000E+00	2.64508E-04
43	6.74075E-02	4.10583E-01	0.00000E+00	0.00000E+00	0.00000E+00	-4.51112E-02
44	8.20800E-02	8.54186E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.08389E-03
46	-1.21661E-01	3.89009E-01	0.00000E+00	0.00000E+00	0.00000E+00	3.84559E-02
48	-4.64676E-03	-1.48580E-02	0.00000E+00	0.00000E+00	0.00000E+00	1.46880E-03
49	-2.41901E-01	8.15141E-01	0.00000E+00	0.00000E+00	0.00000E+00	6.92498E-03
50	-1.70461E-01	7.23873E-01	0.00000E+00	0.00000E+00	0.00000E+00	-2.42762E-02
51	-3.18586E-02	5.56438E-01	0.00000E+00	0.00000E+00	0.00000E+00	3.83237E-02
52	6.34498E-11	8.54647E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.43443E-06
53	-9.23926E-03	-3.11339E-02	0.00000E+00	0.00000E+00	0.00000E+00	2.64508E-04
54	4.56289E-02	2.81466E-01	0.00000E+00	0.00000E+00	0.00000E+00	-2.28380E-02
55	3.18586E-02	5.56445E-01	0.00000E+00	0.00000E+00	0.00000E+00	-3.83251E-02
60	-7.20000E-02	4.26859E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.71358E-02
61	7.20000E-02	4.26859E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.71358E-02

STATIC LOAD/REACTION/EQUILIBRIUM SUMMARY FOR CASE NO. 5
LOADTYPE NONE TITLE WL-X

CENTER OF FORCE BASED ON Y FORCES ONLY (METE).
(FORCES IN NON-GLOBAL DIRECTIONS WILL INVALIDATE RESULTS)

X = 0.177347298E+01
Y = 0.588334609E+00
Z = 0.825000018E+00

TOTAL APPLIED LOAD 5

***TOTAL APPLIED LOAD (KN METE) SUMMARY (LOADING 5)
SUMMATION FORCE-X = -2.51
SUMMATION FORCE-Y = 24.92
SUMMATION FORCE-Z = 0.00

SUMMATION OF MOMENTS AROUND THE ORIGIN-
MX= -20.56 MY= -2.07 MZ= 45.25

TOTAL REACTION LOAD 5

***TOTAL REACTION LOAD(KN METE) SUMMARY (LOADING 5)
SUMMATION FORCE-X = 2.51
SUMMATION FORCE-Y = -24.92
SUMMATION FORCE-Z = 0.00

SUMMATION OF MOMENTS AROUND THE ORIGIN-
MX= 20.56 MY= 2.07 MZ= -45.25

STAAD SPACE -- PAGE NO. 21

MAXIMUM DISPLACEMENTS (CM /RADIANS) (LOADING 5)

	MAXIMUMS	AT NODE
X =	-2.26645E-02	26
Y =	9.13285E-02	30
Z =	6.58929E-04	19
RX=	1.26099E-04	34
RY=	-2.24771E-04	2
RZ=	5.21504E-04	27

EXTERNAL AND INTERNAL JOINT LOAD SUMMARY (KN METE)-

JT	EXT FX/ INT FX	EXT FY/ INT FY	EXT FZ/ INT FZ	EXT MX/ INT MX	EXT MY/ INT MY	EXT MZ/ INT MZ	
							SUPPORT=1
62	0.00	0.00	0.00	0.00	0.00	0.00	
	8.46	7.68	2.67	0.00	-0.00	0.00	111000
63	0.00	0.00	0.00	0.00	0.00	0.00	
	-9.72	4.78	1.44	-0.00	-0.00	0.00	111000
64	0.00	0.00	0.00	0.00	0.00	0.00	
	9.09	7.75	-2.67	-0.00	0.00	-0.00	111000
65	0.00	0.00	0.00	0.00	0.00	0.00	
	-10.35	4.71	-1.44	-0.00	0.00	0.00	111000

FOR LOADING - 6
APPLIED JOINT EQUIVALENT LOADS

JOINT	FORCE-X	FORCE-Y	FORCE-Z	MOM-X	MOM-Y	MOM-Z
3	-9.96941E-02	3.18772E-01	0.00000E+00	0.00000E+00	0.00000E+00	3.15125E-02
4	9.96941E-02	3.18771E-01	0.00000E+00	0.00000E+00	0.00000E+00	-3.15124E-02
5	4.75344E-10	7.00336E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.17516E-06
6	-1.98224E-01	6.67963E-01	0.00000E+00	0.00000E+00	0.00000E+00	5.67464E-03
7	-1.57530E-01	6.98978E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.64132E-03
8	-6.72600E-02	6.99952E-01	0.00000E+00	0.00000E+00	0.00000E+00	-8.89385E-04
9	1.98224E-01	6.67963E-01	0.00000E+00	0.00000E+00	0.00000E+00	-5.67489E-03
10	1.57530E-01	6.98979E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.64149E-03
11	6.72600E-02	6.99958E-01	0.00000E+00	0.00000E+00	0.00000E+00	8.88183E-04
14	-9.96941E-02	3.18772E-01	0.00000E+00	0.00000E+00	0.00000E+00	3.15125E-02
15	9.96941E-02	3.18771E-01	0.00000E+00	0.00000E+00	0.00000E+00	-3.15124E-02
16	4.75344E-10	7.00336E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.17516E-06
17	-1.98224E-01	6.67963E-01	0.00000E+00	0.00000E+00	0.00000E+00	5.67464E-03
18	-1.57530E-01	6.98978E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.64132E-03
19	-6.72600E-02	6.99952E-01	0.00000E+00	0.00000E+00	0.00000E+00	-8.89385E-04
20	1.98224E-01	6.67963E-01	0.00000E+00	0.00000E+00	0.00000E+00	-5.67489E-03
21	1.57530E-01	6.98979E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.64149E-03
22	6.72600E-02	6.99958E-01	0.00000E+00	0.00000E+00	0.00000E+00	8.88183E-04
24	-9.96941E-02	3.18772E-01	0.00000E+00	0.00000E+00	0.00000E+00	3.15125E-02
26	9.96941E-02	3.18771E-01	0.00000E+00	0.00000E+00	0.00000E+00	-3.15124E-02
27	-1.98224E-01	6.67963E-01	0.00000E+00	0.00000E+00	0.00000E+00	5.67464E-03
28	-1.57530E-01	6.98978E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.64132E-03
29	-6.72600E-02	6.99952E-01	0.00000E+00	0.00000E+00	0.00000E+00	-8.89385E-04
30	4.75344E-10	7.00336E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.17516E-06
31	1.98224E-01	6.67963E-01	0.00000E+00	0.00000E+00	0.00000E+00	-5.67489E-03
32	1.57530E-01	6.98979E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.64149E-03
33	6.72600E-02	6.99958E-01	0.00000E+00	0.00000E+00	0.00000E+00	8.88183E-04
35	-9.96941E-02	3.18772E-01	0.00000E+00	0.00000E+00	0.00000E+00	3.15125E-02

APPLIED JOINT EQUIVALENT LOADS

JOINT	FORCE-X	FORCE-Y	FORCE-Z	MOM-X	MOM-Y	MOM-Z
37	9.96941E-02	3.18771E-01	0.00000E+00	0.00000E+00	0.00000E+00	-3.15124E-02
38	-1.98224E-01	6.67963E-01	0.00000E+00	0.00000E+00	0.00000E+00	5.67464E-03
39	-1.57530E-01	6.98978E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.64132E-03
40	-6.72600E-02	6.99952E-01	0.00000E+00	0.00000E+00	0.00000E+00	-8.89385E-04
41	4.75344E-10	7.00336E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.17516E-06
42	1.98224E-01	6.67963E-01	0.00000E+00	0.00000E+00	0.00000E+00	-5.67489E-03
43	1.57530E-01	6.98979E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.64149E-03
44	6.72600E-02	6.99958E-01	0.00000E+00	0.00000E+00	0.00000E+00	8.88183E-04
46	-9.96941E-02	3.18772E-01	0.00000E+00	0.00000E+00	0.00000E+00	3.15125E-02
48	9.96941E-02	3.18771E-01	0.00000E+00	0.00000E+00	0.00000E+00	-3.15124E-02
49	-1.98224E-01	6.67963E-01	0.00000E+00	0.00000E+00	0.00000E+00	5.67464E-03
50	-1.39684E-01	5.93174E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.98930E-02
51	-2.61063E-02	4.55970E-01	0.00000E+00	0.00000E+00	0.00000E+00	3.14041E-02
52	4.75344E-10	7.00336E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.17516E-06
53	1.98224E-01	6.67963E-01	0.00000E+00	0.00000E+00	0.00000E+00	-5.67489E-03
54	1.39684E-01	5.93174E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.98932E-02
55	2.61063E-02	4.55976E-01	0.00000E+00	0.00000E+00	0.00000E+00	-3.14053E-02
60	-5.90000E-02	3.49787E-01	0.00000E+00	0.00000E+00	0.00000E+00	-1.40418E-02
61	5.90000E-02	3.49787E-01	0.00000E+00	0.00000E+00	0.00000E+00	1.40418E-02

STATIC LOAD/REACTION/EQUILIBRIUM SUMMARY FOR CASE NO. 6
LOADTYPE NONE TITLE WL-Z

CENTER OF FORCE BASED ON Y FORCES ONLY (METE).
(FORCES IN NON-GLOBAL DIRECTIONS WILL INVALIDATE RESULTS)

X = 0.236850501E+01
Y = 0.546256798E+00
Z = 0.825000019E+00

TOTAL APPLIED LOAD 6

***TOTAL APPLIED LOAD (KN METE) SUMMARY (LOADING 6)
SUMMATION FORCE-X = -0.00
SUMMATION FORCE-Y = 27.36
SUMMATION FORCE-Z = 0.00

SUMMATION OF MOMENTS AROUND THE ORIGIN-
MX= -22.57 MY= -0.00 MZ= 64.80

TOTAL REACTION LOAD 6

***TOTAL REACTION LOAD(KN METE) SUMMARY (LOADING 6)
SUMMATION FORCE-X = 0.00
SUMMATION FORCE-Y = -27.36
SUMMATION FORCE-Z = -0.00

SUMMATION OF MOMENTS AROUND THE ORIGIN-
MX= 22.57 MY= 0.00 MZ= -64.80

STAAD SPACE -- PAGE NO. 23

MAXIMUM DISPLACEMENTS (CM /RADIANS) (LOADING 6)

	MAXIMUMS	AT NODE
X =	-1.88090E-02	25
Y =	8.49196E-02	30
Z =	6.78672E-04	41
RX=	-1.09565E-04	1
RY=	-1.92162E-04	34
RZ=	4.18559E-04	27

EXTERNAL AND INTERNAL JOINT LOAD SUMMARY (KN METE)-

JT	EXT FX/ INT FX	EXT FY/ INT FY	EXT FZ/ INT FZ	EXT MX/ INT MX	EXT MY/ INT MY	EXT MZ/ INT MZ	
							SUPPORT=1
62	0.00	0.00	0.00	0.00	0.00	0.00	
	8.60	6.84	2.27	-0.00	-0.00	0.00	111000
63	0.00	0.00	0.00	0.00	0.00	0.00	
	-8.60	6.84	2.27	-0.00	0.00	0.00	111000
64	0.00	0.00	0.00	0.00	0.00	0.00	
	9.24	6.84	-2.27	-0.00	-0.00	-0.00	111000
65	0.00	0.00	0.00	0.00	0.00	0.00	
	-9.24	6.84	-2.27	-0.00	-0.00	-0.00	111000

LOAD COMBINATION NO. 101
1.5(DL+LL)

LOADING-	1.	2.
FACTOR -	1.50	1.50

LOAD COMBINATION NO. 102
1.5(DL+WLX)

LOADING-	1.	3.
FACTOR -	1.50	1.50

LOAD COMBINATION NO. 103
1.5(DL+WLZ)

LOADING-	1.	4.
FACTOR -	1.50	1.50

LOAD COMBINATION NO. 104
1.5(DL+WL-X)

LOADING-	1.	5.
FACTOR -	1.50	1.50

LOAD COMBINATION NO. 105
1.5(DL+WL-Z)

LOADING-	1.	6.
FACTOR -	1.50	1.50

LOAD COMBINATION NO. 201
DL + LL

LOADING-	1.	2.
FACTOR -	1.00	1.00

LOAD COMBINATION NO. 202
DL+WLX

LOADING-	1.	3.
FACTOR -	1.00	1.00

LOAD COMBINATION NO. 203
DL+WLZ

LOADING-	4.	1.
FACTOR -	1.00	1.00

LOAD COMBINATION NO. 204
DL+WL-X

LOADING-	1.	5.
FACTOR -	1.00	1.00

LOAD COMBINATION NO. 205
DL+WL-Z

LOADING-	6.	1.
FACTOR -	1.00	1.00

LOAD COMBINATION NO. 206
DL+0.8WLX

LOADING-	1.	3.
FACTOR -	1.00	0.80

LOAD COMBINATION NO. 207
DL+0.8WLZ

LOADING-	4.	1.
FACTOR -	0.80	1.00

LOAD COMBINATION NO. 208
DL+0.8WL-X

LOADING-	5.	1.
FACTOR -	0.80	1.00

LOAD COMBINATION NO. 209
DL+0.8WL-Z

LOADING-	6.	1.
FACTOR -	0.80	1.00

STAAD SPACE -- PAGE NO. 25

********** END OF DATA FROM INTERNAL STORAGE **********

136. PARAMETER 1
137. CODE IS800 LSD
138. FYLD 210000 ALL
139. CHECK CODE ALL
STEEL DESIGN

Member Number:	1				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.106	Critical Load Case:	102	Location:	0.25
Critical Condition: Sec. 8.2.1.2					

Member Number:	2				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.118	Critical Load Case:	102	Location:	0.00
Critical Condition: Sec. 8.2.1.2					

Member Number:	3				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.106	Critical Load Case:	102	Location:	0.00
Critical Condition: Sec. 8.2.1.2					

Member Number:	4				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.104	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)
****

Member Number:	5				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.102	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	6				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.100	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	7				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.108	Critical Load Case:	102	Location:	0.00
Critical Condition: Sec. 8.2.1.2					

Member Number:	8				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.104	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)

Member Number:	9				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.102	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	10				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.100	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	13				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	3	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	14				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	3	Location:	0.00
Critical Condition: Slenderness (Compression)					

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)

Member Number:	15				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	3	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	16				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	17				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	18				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	3	Location:	0.00
Critical Condition: Slenderness (Compression)					

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)
****

Member Number:	19				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	20				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	21				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	3	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	22				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.071	Critical Load Case:	102	Location:	0.25
Critical Condition: Sec. 8.2.1.2					

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)
****

Member Number: 23					
Member Section: ST TUBE	(INDIAN SECTIONS)				
Status: PASS	Ratio: 0.061	Critical Load Case: 102	Location:	0.25	
Critical Condition: Sec. 8.2.1.2					

Member Number: 24					
Member Section: ST TUBE	(INDIAN SECTIONS)				
Status: PASS	Ratio: 0.096	Critical Load Case: 1	Location:	0.00	
Critical Condition: Slenderness (Compression)					

Member Number: 25					
Member Section: ST TUBE	(INDIAN SECTIONS)				
Status: PASS	Ratio: 0.104	Critical Load Case: 1	Location:	0.00	
Critical Condition: Slenderness (Compression)					

Member Number: 26					
Member Section: ST TUBE	(INDIAN SECTIONS)				
Status: PASS	Ratio: 0.102	Critical Load Case: 1	Location:	0.00	
Critical Condition: Slenderness (Compression)					

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)
****

Member Number:	27				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.100	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	28				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.096	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	29				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.104	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	30				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.102	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)
****

Member Number:	31				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.100	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	32				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.129	Critical Load Case:	102	Location:	0.25
Critical Condition: Sec. 8.2.1.2					

Member Number:	33				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.130	Critical Load Case:	102	Location:	0.25
Critical Condition: Sec. 8.2.1.2					

Member Number:	34				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.132	Critical Load Case:	102	Location:	0.00
Critical Condition: Sec. 8.2.1.2					

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)
****

Member Number: 35					
Member Section: ST TUBE	(INDIAN SECTIONS)				
Status: PASS	Ratio: 0.104	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number: 36					
Member Section: ST TUBE	(INDIAN SECTIONS)				
Status: PASS	Ratio: 0.102	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number: 37					
Member Section: ST TUBE	(INDIAN SECTIONS)				
Status: PASS	Ratio: 0.115	Critical Load Case:	102	Location:	0.59
Critical Condition: Sec. 8.2.1.2					

Member Number: 38					
Member Section: ST TUBE	(INDIAN SECTIONS)				
Status: PASS	Ratio: 0.134	Critical Load Case:	102	Location:	0.00
Critical Condition: Sec. 8.2.1.2					

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)
****

Member Number:	39				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.104	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	40				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.112	Critical Load Case:	102	Location:	0.60
Critical Condition: Sec. 8.2.1.2					

Member Number:	41				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.115	Critical Load Case:	102	Location:	0.40
Critical Condition: Sec. 8.2.1.2					

Member Number:	42				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)
****

Member Number:	43				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	44				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	45				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	46				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	3	Location:	0.00
Critical Condition: Slenderness (Compression)					

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)
****

Member Number:	47				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	3	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	48				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	49				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	3	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	50				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	3	Location:	0.00
Critical Condition: Slenderness (Compression)					

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)
****

Member Number: 51					
Member Section: ST TUBE	(INDIAN SECTIONS)				
Status: PASS	Ratio: 0.093	Critical Load Case: 102	Location:	0.25	
Critical Condition: Sec. 8.2.1.2					

Member Number: 52					
Member Section: ST TUBE	(INDIAN SECTIONS)				
Status: PASS	Ratio: 0.115	Critical Load Case: 102	Location:	0.00	
Critical Condition: Sec. 8.2.1.2					

Member Number: 53					
Member Section: ST TUBE	(INDIAN SECTIONS)				
Status: PASS	Ratio: 0.096	Critical Load Case: 1	Location:	0.00	
Critical Condition: Slenderness (Compression)					

Member Number: 54					
Member Section: ST TUBE	(INDIAN SECTIONS)				
Status: PASS	Ratio: 0.104	Critical Load Case: 1	Location:	0.00	
Critical Condition: Slenderness (Compression)					

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)
****

Member Number:	55				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.102	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	56				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.100	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	57				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.108	Critical Load Case:	102	Location:	0.00
Critical Condition: Sec. 8.2.1.2					

Member Number:	58				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.104	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)
****

Member Number:	59				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.102	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	60				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.100	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	61				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	62				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)
****

Member Number:	63				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	64				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	65				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	3	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	66				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	3	Location:	0.00
Critical Condition: Slenderness (Compression)					

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)
****

Member Number: 67					
Member Section: ST	80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number: 68					
Member Section: ST	80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	3	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number: 69					
Member Section: ST	80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	3	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number: 70					
Member Section: ST	TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.042	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)

```
|-------------------------------------------------------------------------------|
|  Member Number:     71                                                        |
|  Member Section:  ST   TUBE                  (INDIAN SECTIONS)                |
|  Status: PASS  Ratio:   0.045  Critical Load Case:   102  Location:       0.00  |
|  Critical Condition: Sec. 8.2.1.2                                             |
|-------------------------------------------------------------------------------|

|-------------------------------------------------------------------------------|
|  Member Number:     72                                                        |
|  Member Section:  ST   TUBE                  (INDIAN SECTIONS)                |
|  Status: PASS  Ratio:   0.096  Critical Load Case:     1  Location:       0.00  |
|  Critical Condition: Slenderness (Compression)                                |
|-------------------------------------------------------------------------------|

|-------------------------------------------------------------------------------|
|  Member Number:     73                                                        |
|  Member Section:  ST   TUBE                  (INDIAN SECTIONS)                |
|  Status: PASS  Ratio:   0.104  Critical Load Case:     1  Location:       0.00  |
|  Critical Condition: Slenderness (Compression)                                |
|-------------------------------------------------------------------------------|

|-------------------------------------------------------------------------------|
|  Member Number:     74                                                        |
|  Member Section:  ST   TUBE                  (INDIAN SECTIONS)                |
|  Status: PASS  Ratio:   0.071  Critical Load Case:     1  Location:       0.00  |
|  Critical Condition: Slenderness (Compression)                                |
|-------------------------------------------------------------------------------|
```

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)
****

Member Number:	75				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.100	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	76				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.096	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	77				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.104	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	78				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.071	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)
****

Member Number:	79				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.100	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	80				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	3	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	81				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	3	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	82				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	3	Location:	0.00
Critical Condition: Slenderness (Compression)					

STAAD SPACE -- PAGE NO. 45

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)
****

Member Number:	83				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	4	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	84				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	85				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	3	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	86				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	4	Location:	0.00
Critical Condition: Slenderness (Compression)					

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)

Member Number:	87				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	88				
Member Section:	ST 80X80X2.9SHS	(APL APOLLOTUBE SECTIONS)			
Status: PASS	Ratio: 0.147	Critical Load Case:	3	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	89				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.262	Critical Load Case:	4	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number:	90				
Member Section:	ST TUBE	(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.262	Critical Load Case:	4	Location:	0.00
Critical Condition: Slenderness (Compression)					

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)
****

Member Number: 91					
Member Section: ST TUBE	(INDIAN SECTIONS)				
Status: PASS Ratio: 0.262	Critical Load Case:	4	Location:	0.00	
Critical Condition: Slenderness (Compression)					

Member Number: 92					
Member Section: ST TUBE	(INDIAN SECTIONS)				
Status: PASS Ratio: 0.111	Critical Load Case:	2	Location:	0.00	
Critical Condition: Slenderness (Compression)					

Member Number: 93					
Member Section: ST TUBE	(INDIAN SECTIONS)				
Status: PASS Ratio: 0.111	Critical Load Case:	2	Location:	0.00	
Critical Condition: Slenderness (Compression)					

Member Number: 94					
Member Section: ST TUBE	(INDIAN SECTIONS)				
Status: PASS Ratio: 0.031	Critical Load Case:	1	Location:	0.00	
Critical Condition: Slenderness (Compression)					

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)
****

Member Number: 95					
Member Section: ST TUBE	(INDIAN SECTIONS)				
Status: PASS	Ratio: 0.031	Critical Load Case:	1	Location:	0.00
Critical Condition: Slenderness (Compression)					

Member Number: 96					
Member Section: ST TUBE	(INDIAN SECTIONS)				
Status: PASS	Ratio: 0.125	Critical Load Case:	102	Location:	0.41
Critical Condition: Sec. 8.2.1.2					

Member Number: 97					
Member Section: ST TUBE	(INDIAN SECTIONS)				
Status: PASS	Ratio: 0.118	Critical Load Case:	102	Location:	0.41
Critical Condition: Sec. 8.2.1.2					

Member Number: 98					
Member Section: ST TUBE	(INDIAN SECTIONS)				
Status: PASS	Ratio: 0.114	Critical Load Case:	102	Location:	0.41
Critical Condition: Sec. 8.2.1.2					

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)
****

Member Number: 99					
Member Section: ST TUBE		(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.103	Critical Load Case: 102	Location:	0.00	
Critical Condition: Sec. 9.3.2.2					

Member Number: 100					
Member Section: ST TUBE		(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.102	Critical Load Case: 102	Location:	0.82	
Critical Condition: Sec. 9.3.2.2					

Member Number: 101					
Member Section: ST TUBE		(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.148	Critical Load Case: 102	Location:	0.41	
Critical Condition: Sec. 9.3.2.2					

Member Number: 102					
Member Section: ST TUBE		(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.146	Critical Load Case: 102	Location:	0.00	
Critical Condition: Sec. 9.3.2.2					

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)
****

Member Number: 103					
Member Section: ST TUBE		(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.144	Critical Load Case: 102	Location:	0.82	
Critical Condition: Sec. 9.3.2.2					

Member Number: 104					
Member Section: ST TUBE		(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.125	Critical Load Case: 102	Location:	0.00	
Critical Condition: Sec. 8.2.1.2					

Member Number: 105					
Member Section: ST TUBE		(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.149	Critical Load Case: 102	Location:	0.00	
Critical Condition: Sec. 9.3.2.2					

Member Number: 106					
Member Section: ST TUBE		(INDIAN SECTIONS)			
Status: PASS	Ratio: 0.114	Critical Load Case: 102	Location:	0.00	
Critical Condition: Sec. 8.2.1.2					

STAAD SPACE -- PAGE NO. 51

STAAD.PRO CODE CHECKING - IS-800-2007-LSD (V2.2)
****

|---|
| Member Number: 107 |
| Member Section: ST TUBE (INDIAN SECTIONS) |
| Status: PASS Ratio: 0.106 Critical Load Case: 102 Location: 0.00 |
| Critical Condition: Sec. 8.2.1.2 |

140. FINISH

********** END OF THE STAAD.Pro RUN **********

**** DATE= JUN 28,2025 TIME= 15: 3:55 ****

```
*************************************************************
*   For technical assistance on STAAD.Pro, please visit     *
*   http://www.bentley.com/en/support/                      *
*                                                           *
*   Details about additional assistance from                *
*   Bentley and Partners can be found at program menu       *
*   Help->Technical Support                                 *
*                                                           *
*           Copyright (c) Bentley Systems, Inc.             *
*                http://www.bentley.com                     *
*************************************************************
```