TECKENTRUP
DOOR SOLUTIONS

Teckentrup GmbH & Co. KG | post box 3113 | 33326 Gütersloh

NIHVA Technologies Pvt Ltd.
8/1 Coomant Housing Society,
411044 PUNE, MAHARASHTRA
INDIA

sales@nihva.com
Fon: 2066304033

Teckentrup GmbH & Co. KG
Industriestr. 50
33415 Verl-Sürenheide
info@teckentrup.biz
www.teckentrup.biz

administrator:
Claudia Jackwert
phone: +495246504377
fax: +495246504177
Claudia.Jackwert@teckentrup.biz

sales representative:
Atilla Özel
phone:
fax: +495246504177
atilla.oezel@teckentrup.biz

order confirmation – internal/copy 903364

number: 903364
date: 12.08.2021
reference document: ZAG 2000163286

building project: NVA 530 / IN
order no. / date: NVA 530 / 10-Aug-21
customer no.: 122532

consignee:

NIHVA Technologies Pvt Ltd.
8/1 Coomant Housing Society,
411044 PUNE, MAHARASHTRA
INDIA

invoice recipient:

NIHVA Technologies Pvt Ltd.
8/1 Coomant Housing Society,
411044 PUNE,
MAHARASHTRA
INDIA

time schedule details regarding your order:

plant	positions	delivery date	notifications reg. the status
Großzöberitz	1000		cancellation
Großzöberitz	2000, 3000, 4000, 5000	approx. 40 / 2021	

Subject to correct and timely self-delivery.

place of performance and jurisdication for payment and delivery is Gütersloh. Above items remain our property until they are completely paid. Payments towards the representative do not release you from your obligations to us. Delivery in consideration of our terms and conditions of trade.

Sparkasse Gütersloh: IBAN: DE37 4785 0065 0016 0001 01 BIC: WELADED1GTL | Volksbank Gütersloh: IBAN: DE55 4786 0125 0105 3753 00 BIC: GENODEM1GTL
Kreissparkasse Wiedenbrück: IBAN: DE64 4785 3520 0000 0535 61 BIC: WELADED1WDB | Commerzbank Gütersloh: IBAN: DE39 4784 0065 0150 2293 00 BIC: COBADEFF478
Deutsche Bank Gütersloh: IBAN: DE27 4807 0040 0340 6865 00 BIC: DEUTDE3B480

legal form: GmbH & Co. KG, commercial register Gütersloh A 4173. Head office Verl, personally liable partner: Teckentrup Metalltüren GmbH. Head office Verl, commercial register Gütersloh B 1628.
managing directors: Kai Teckentrup
value added tax identification no.: DE 209454739

number 903364 / 12.08.2021

pos.	material	description	quantity	unit price EUR	total price EUR

002000 153718 roller shutter Thermo Teck (C)

double-skinned Teckentrup roller shutter made from PU-foamed steel profiles.
outside of profiles micro-profiled, inner surface "smooth" w groove (curve).
For outer rollers the actual inside is visible on the outside!
Micro-profiling then inside.

net	2.00PC	4,771.15	9,542.29

roller d. curtain profile type	ThermoTeck steel filled with PU-foam
ordering size (b x h)	4.215 mm x 7.900 mm
roller door surface outside	galvanised with protective fil
door color inside / outside	uniformly
roller shutter type	outside roller with storm hooks
buffer drive side min./exist.	325 mm / 325 mm
buffer bear. side min./exist.	200 mm / 200 mm
lintel height min./existing	700 mm / 700 mm
insertion depth	932 mm
building structure	concrete
bottom profile	ET-1 for Teckentrup ThermoTeck
welding shaft	steel tube ø 159mm primed
guide rail	FS 110 steel
underlining size	60 mm
console drive/bearing side	console type 7.5 / console type 7.5
brush sealing type	BH - 50
drive type / -edition	direct mount drive TAR 3.50 KU 400V/3Ph AWG
.	12 U/min; IP54; 60% ED
drive mounted	outside right, standing
emergency drive operation	emergency hand crank
door operation	normal operation quantity
control unit	320I
.	with built-in triple button
.	CEE-plug with wire
control side	same as drive side
safety edge device	opto-sensors
control cable length	9.000 mm
external safety device	required for public areas
heat transmis. value [W/m2K]	3,36
wind load class	wind load resistance class 3

Serialnr.: 202140000001213037, 202140000001213038

legal form: GmbH & Co. KG, commercial register Gütersloh A 4173. Head office Verl, personally liable partner: Teckentrup Metalltüren GmbH. Head office Verl, commercial register Gütersloh B 1628.
managing directors: Kai Teckentrup
value added tax identification no.: DE 209454739

number 903364 / 12.08.2021

pos.	material	description	quantity	unit price EUR	total price EUR

003000 153718 roller shutter Thermo Teck (C)

double-skinned Teckentrup roller shutter made from PU-foamed steel profiles.
outside of profiles micro-profiled, inner surface "smooth" w groove (curve).
For outer rollers the actual inside is visible on the outside!
Micro-profiling then inside.

net	3.00PC	4,701.06	14,103.18

roller d. curtain profile type	ThermoTeck steel filled with PU-foam
ordering size (b x h)	4.215 mm x 7.700 mm
roller door surface outside	galvanised with protective fil
door color inside / outside	uniformly
roller shutter type	outside roller with storm hooks
buffer drive side min./exist.	325 mm / 325 mm
buffer bear. side min./exist.	200 mm / 200 mm
lintel height min./existing	700 mm / 700 mm
insertion depth	932 mm
building structure	concrete
bottom profile	ET-1 for Teckentrup ThermoTeck
welding shaft	steel tube ø 159mm primed
guide rail	FS 110 steel
underlining size	60 mm
console drive/bearing side	console type 7.5 / console type 7.5
brush sealing type	BH - 50
drive type / -edition	direct mount drive TAR 3.50 KU 400V/3Ph AWG
.	12 U/min; IP54; 60% ED
drive mounted	outside right, standing
emergency drive operation	emergency hand crank
door operation	normal operation quantity
control unit	320I
.	with built-in triple button
.	CEE-plug with wire
control side	same as drive side
safety edge device	opto-sensors
control cable length	9.000 mm
external safety device	required for public areas
heat transmis. value [W/m2K]	3,37
wind load class	wind load resistance class 3

Serialnr.: 202140000001213039 - 202140000001213041

004000 153718 roller shutter Thermo Teck (C)

legal form: GmbH & Co. KG, commercial register Gütersloh A 4173. Head office Verl, personally liable partner: Teckentrup Metalltüren GmbH. Head office Verl, commercial register Gütersloh B 1628.
managing directors: Kai Teckentrup
value added tax identification no.: DE 209454739

number 903364 / 12.08.2021

pos.	material	description	quantity	unit price EUR	total price EUR

double-skinned Teckentrup roller shutter made from PU-foamed steel profiles.
outside of profiles micro-profiled, inner surface "smooth" w groove (curve).
For outer rollers the actual inside is visible on the outside!
Micro-profiling then inside.

net	2.00PC	4,771.15	9,542.29

roller d. curtain profile type	ThermoTeck steel filled with PU-foam
ordering size (b x h)	4.180 mm x 7.900 mm
roller door surface outside	galvanised with protective fil
door color inside / outside	uniformly
roller shutter type	outside roller with storm hooks
buffer drive side min./exist.	325 mm / 325 mm
buffer bear. side min./exist.	200 mm / 200 mm
lintel height min./existing	700 mm / 700 mm
insertion depth	932 mm
building structure	concrete
bottom profile	ET-1 for Teckentrup ThermoTeck
welding shaft	steel tube ø 159mm primed
guide rail	FS 110 steel
underlining size	60 mm
console drive/bearing side	console type 7.5 / console type 7.5
brush sealing type	BH - 50
drive type / -edition	direct mount drive TAR 3.50 KU 400V/3Ph AWG
.	12 U/min; IP54; 60% ED
drive mounted	outside right, standing
emergency drive operation	emergency hand crank
door operation	normal operation quantity
control unit	320I
.	with built-in triple button
.	CEE-plug with wire
control side	same as drive side
safety edge device	opto-sensors
control cable length	9.000 mm
external safety device	required for public areas
heat transmis. value [W/m2K]	3,37
wind load class	wind load resistance class 3

Serialnr.: 202140000001213042, 202140000001213043

005000 153718 roller shutter Thermo Teck (C)

legal form: GmbH & Co. KG, commercial register Gütersloh A 4173. Head office Verl, personally liable partner: Teckentrup Metalltüren GmbH. Head office Verl, commercial register Gütersloh B 1628.
managing directors: Kai Teckentrup
value added tax identification no.: DE 209454739

TECKENTRUP
DOOR SOLUTIONS

number 903364 / 12.08.2021

pos.	material description	quantity	unit price EUR	total price EUR

double-skinned Teckentrup roller shutter made from PU-foamed steel profiles.
outside of profiles micro-profiled, inner surface "smooth" w groove (curve).
For outer rollers the actual inside is visible on the outside!
Micro-profiling then inside.

net	3.00PC	4,701.06	14,103.18

roller d. curtain profile type	ThermoTeck steel filled with PU-foam
ordering size (b x h)	4.180 mm x 7.700 mm
roller door surface outside	galvanised with protective fil
door color inside / outside	uniformly
roller shutter type	outside roller with storm hooks
buffer drive side min./exist.	325 mm / 325 mm
buffer bear. side min./exist.	200 mm / 200 mm
lintel height min./existing	700 mm / 700 mm
insertion depth	932 mm
building structure	concrete
bottom profile	ET-1 for Teckentrup ThermoTeck
welding shaft	steel tube ø 159mm primed
guide rail	FS 110 steel
underlining size	60 mm
console drive/bearing side	console type 7.5 / console type 7.5
brush sealing type	BH - 50
drive type / -edition	direct mount drive TAR 3.50 KU 400V/3Ph AWG 12 U/min; IP54; 60% ED
drive mounted	outside right, standing
emergency drive operation	emergency hand crank
door operation	normal operation quantity
control unit	320I with built-in triple button CEE-plug with wire
control side	same as drive side
safety edge device	opto-sensors
control cable length	9.000 mm
external safety device	required for public areas
heat transmis. value [W/m2K]	3,37
wind load class	wind load resistance class 3

Serialnr.: 202140000001213044 - 202140000001213046

positions amount		47,290.94
Output Tax	0.00%	0.00
total amount		47,290.94

payment conditions: 50% prepaym.,50% upon collect.

legal form: GmbH & Co. KG, commercial register Gütersloh A 4173. Head office Verl, personally liable partner: Teckentrup Metalltüren GmbH. Head office Verl, commercial register Gütersloh B 1628.
managing directors: Kai Teckentrup
value added tax identification no.: DE 209454739

number 903364 / 12.08.2021

pos.	material	description	quantity	unit price EUR	total price EUR

incoterm: EXW Ex Works

Please note:
Based on your inquiry the following notes regarding our particular products/positions result:

legal information
Teckentrup doors comply with the norm 13241-1.
Included under this is EN 12978 -this applies to the safety devices for power operated doors and gates.

- Doors with pulse control or "push to run" have to be equipped with a secondary safety feature- safety edge or photocells. This is mandatory for automatic closing doors and those using radio control.
  Roller doors and roller grilles less than 2500mm in door height need an additional light barrier as roll-up safety/finger pinch protection to satisfy entrapment regulations.

The maximal wind load is valid for the closed and does not ensure proper door opening.

Teckentrup sectional doors/ roller doors
For roller doors and sectional doors with more than 70 cycles a day or more than 20 cycles per hour we recommend using a motor with 100% rating.

- For doors with more than 10,000 cycles a year we recommend the use of reinforced torsion springs (increased load cycle).
- The lintel seal of sectional doors with low headroom (NSH/NSD) and a lintel of only 250mm may catch on the ceiling and may leave scuff marks.

Teckentrup aluminium roller door 4020
- The smooth version of the roller door 4020 can develop abrasive marks -this is due to technical reasons and will not entitle to warranty or replacement- therefore we recommend the stucco embossed material which conceales any abrasive marks.
- Doors with powder-coated surfaces can cause increased running noises and possibly abrasion marks. This is due to technical reasons and does not constitute grounds for complaint.

Galvanised surface with transparent protective paint
This is manufactured cold formed galvanised sheet, there is no paint coating.

Consider possible environmental influences (such as sea climate, aggressive vapours in the atmosphere, road salt, exposure to abrasive materials, increased wind loads). Where appropriate subsequent protective paints may be required.

To ensure there is sufficient water run-off in front of the door and on the frame parts a minimum fall away of 2-3° is suggested to prevent water standing and puddling (risk of corrosion)

We reserve the right to amend charges if measurements and technical specifications change.,

inspection and maintenance instructions
For power operated doors in a factory or public place the Machinery at Work Act denotes that a maintenance schedule must be in place with yearly safety inspections.

legal form: GmbH & Co. KG, commercial register Gütersloh A 4173. Head office Verl, personally liable partner: Teckentrup Metalltüren GmbH. Head office Verl, commercial register Gütersloh B 1628.
managing directors: Kai Teckentrup
value added tax identification no.: DE 209454739

We recommend that Teckentrup industrial doors with more than 50 cycles a day be inspected every 6 months, and doors with more than 100 cycles a day be tested every 3 months.

Non-compliance with the above mentioned tests can cause risk of injuries and danger of property damage and will invalidate warranty rights.

General Information:

At the moment our supply chains are stable, our plants can produce. Nevertheless, we would like to indicate that the viral disease Covid-19 may result in materials not being supplied, or production plants being closed by authorities and thus hindering our production process.
For these cases we exclude the takeover of costs resulting from delay in delivery or similar.

environmental product declaration:
"Teckentrup Türen und Tore" are declared by the ift Rosenheim - EPD (environmental product declaration).
Please find further information on **www.teckentrup.biz/downloadcenter**

legal form: GmbH & Co. KG, commercial register Gütersloh A 4173. Head office Verl, personally liable partner: Teckentrup Metalltüren GmbH. Head office Verl, commercial register Gütersloh B 1628.
managing directors: Kai Teckentrup
value added tax identification no.: DE 209454739