Preventive Maintenance Manufacturer's Specification

ASSA ABLOY

ASSA ABLOY Entrance Systems

The global leader in door opening solutions

Enhance the durability of your High Performance Door Albany RR450 / Albany RR450 EX

Key benefit

Safety

Cost-Savings

Just as a car's tires and oil must be changed regularly, your Albany High Performance Doors have key components that periodically need replacing. Whether it's a spring or a sprocket, changing them before they break is an integral part of Pro-Active Care.

We at ASSA ABLOY Entrance Systems believe in Pro-Active Care. Letting us replace components before they fail keeps your warranty valid and your equipment compliant with regulations. Even more importantly, it ensures the safety and functionality of your equipment, so that you can avoid accidents and losses in productivity.



Instructions for table usage:

Qualified person
The manufacturer's recommendation for exchange of components is subject to the findings of a qualified person. We strongly recommend that inspections are performed by a qualified person within the recommended service intervals (according to the user manual of the door).

Recommendations for exchange
The manufacturer's recommendations are based on a door with average size, installed under regular environmental conditions. Doors dimensioned close to maximum size of the door type or doors installed in harsh environmental conditions, need particular observation by a qualified person as the recommended intervals might be shorter.

Components specified as wear and tear related do not have a recommended exchange interval, indications for exchange or wear can be derived from the corresponding fact sheets.

Subject to technical modifications without notice. Errors and omissions excepted.

ASSA ABLOY ENTRANCE SYSTEMS
Maintenance & Modernization

Preventive Maintenance
Manufacturer's Specification

ASSA ABLOY

Albany RR450

Product group	Description	200.000 cycles	250.000 cycles	500.000 cycles	1.000.000 cycles	1.000.000 cycles or 5 years	4 years	5 years	10 years	wear / tear related
Actuators	Photocell transm./rec. with bracket								●	
	Safety photocell re/tr								●	
Cable chain	Cable chain, complete with cable and bracket			●						
Counterbalancing	Belt		●							
	Counterbalancing system			●						
	Rope d=7mm, L=15 Meters for new bal system (from 11-2009)		●							
	Rope pulley		●							
	Rope pulley AL, crash		●							
Curtain tension	Rope		●							
	Tension spring with deflection horse			●						
Curtain	Set of wind tabs			●						
	Curtain including top roll									●
Top roll	Pedestal bearing			●						
	Top roll aluminium with curtain			●						
Bottom profile	Rubber profile with contact strip							●		
Crash	Proximity switch								●	
	Sliding guidance for crash									●
	Swiveling roller			●						
	Tappet cpl			●						
Sliding/Guiding	Sliding guidance									●
Switch	Proximity switch rh/lh with bracket								●	
Drive unit	Drive unit - contactor control			●						
	Drive unit - frequency converter				●					
	Microswitch					●				
Chain drive	Chain drive unit					●				
	Chain wheel - frequency converter					●				
	Roller chain complete					●				
Brake	Brake - contactor control			●						
	Brake - frequency converter				●					
Encoder	Double Proximity switch								●	
	Encoder 50 pulses, only electronic part								●	
Junction box	Junction box								●	
Damper	Vibration absorber			●						

Albany RR450EX

Actuators	Safety photocell EX								●	
Counterbalancing	Belt	●								
	Counterbalancing system	●								
Bottom profile	Safety edge							●		
Switch	Proximity switch with bracket, EX								●	
Drive unit	Drive unit EX						●			
	Magnet switch EX - ACS80								●	
	Positional switch								●	
Encoder	Incremental shaft encoder MCC								●	
Damper	Vibration absorber			●						

≤150.000 cycles: ±10.000 cycles; >150.000 cycles: ±20.000 cycles
≤5 years: ±6 months; >5 years: ±1 year

© ASSA ABLOY Entrance Systems AB PL.MAN/RR450/DEU.EN-1.1/1504 / 64 100 482 Technical data subject to change without notice