A guide to preventative maintenance for Albany High Performance Doors

ASSA ABLOY

ASSA ABLOY Entrance Systems

The global leader in door opening solutions



Curtain

What is the function?

- To separate areas
- Handling wind load
- Reducing energy costs
- Protecting people
- Securing premises

What is the manufacturer's specification?

To make sure the manufacturer's specifications are observed, replace when showing the described wear pattern.

What is the risk of not replacing?

When not following the manufacturer's specifications the customer is taking the responsibility for unintended breakdown, e.g.:

- There may be reduced opacity, which increases the risk for injuries or accidents
- Reduced wind load capabilities
- Higher air leakage and higher energy costs
- A damaged curtain is also a security issue.

How do they wear?

During the lifetime of the curtain there will be wear and tear due to:

- Friction between curtain and side frame
- Winding on the top roll
- The wind load causing the wind tabs to wear out
- Crashes
- Sunlight / temperature changes causes aging of PVC / Acryl
- Cleaning agents can lead to opacity and hardening
- Color abrasion due to friction and aging

Can I also replace it earlier?

PVC / Top

- Yes, if there are rips in the curtain stripes (50% of visible area torn)
- If there is opacity due to mechanical abrasion
- If the wind tabs are worn out by 1 mm (asymmetric)

RollTex / NomaTex

- Windows similar to PVC/Top influences
- If the wind tabs create holes
- If there is any color abrasion on the doorblade (optical flaw)

Top reasons for preventive maintenance

- Keeps the warranty valid
- Prevents unexpected and expensive break-downs
- Prolongs lifetime
- Cost saving
- Minimises risk of personal injury
- Minimises energy loss
- Fulfills legal requirements
- Improves working environment

©ASSA ABLOY Entrance Systems AB/PL.MAP/DEU-EN-1.0/1504

ASSA ABLOY ENTRANCE SYSTEMS Maintenance & Modernization