Annexure A for PO NVA-719 Albany make Machine Protection Door RP300		
Sr. No	**Description**	**Albany make Machine Protection Door RP300**
1	**Door version:**	Vertical Rapid Roller Door for machine protection.
2	**Side Frames:**	Aluminum anodized two parts, to have easy access to switches and service.
3	**Door blade:**	Rolltex Plus Curtain
4	**Bottom beam**	Aluminium anodized.
5	**Drive unit:**	Drive unit IP 55, with control cable (standard length = height of door)
6	**Opening / closing speed:**	Approx. max. 2,4 / 1,7 m/s
7	**Control system:**	Control System MCC7110 Vector Control, incl Display and black mainswitch in combi box
8	**Power suppy:**	3L(N)PE 380/400/415/440/460 and 480 V, 50/60 Hz
9	**Safety limit switch:**	1 pc Schmersal magnet switch BNS 33-02z-2187 ST+magnet BPW 33-2326, mounted in side frame
10	**Window Type**	700 x 500 mm Anti UV Type
11	**Display (Remote)**	Display "Up-Stop-Down"
12	**Motor Position**	**Left Hand Side**
13	**Interface Card**	MCC without display unit, with combibox in plastic (175x250x150 mm) with interface card and main switch included in combibox, including power- and interface cable.
14	**Pre - running Photocell**	Bottom beam with pre-running photocell (without contact edge) with cable chain inside side frames (only available with MCC control); opening and closing speed up to 2,4 / 1,7 m/s - with door line photocell inside side frames
15	**RAL Code**	7035
16	**Accessories**	Top Cover & Motor Cover