ANNEXURE - II

FORMAT - TECHNICAL SPECIFICATION

For Fully automatic line.

(Capacity – 15,000 liters / day or 25,000 bottles / day @ 600ml / bottle) with all accessories

NIHVA

Sr.No.	Description (Column I)	Required specification (Column II)	Mention your firm Specifications without deviations for all parameters. Mention specifically if any deviations made (Column III)
1.01	***MIXING VESSEL – Working volume 3000 LTR, Gross Volume 3600LTR***		
a	**GENERAL**		
	Material Of Construction	SS 316 contact parts and SS 304 non contact parts.	Yes
	Vessel Type	Cylindrical Vertical with welded top / bottom dish end	Yes
b	**PROCESS DETAILS& OPERATIONAL DATA**		
	Specific Gravity	0.92gms /cc	Yes
	Operating Temperature	Ambient	Yes
c	**DESIGN DATA**		
	Working Volume	3000 Ltr.	Yes
	Gross Volume.	3600 Ltr ~~3000 LTR.~~ 2400 LTR.	Yes
d	**MATERIAL OF CONSTRUCTION**		
	Shell / Bottom / Top dish	Stainless Steel 316 Grade	Yes

TECHNOLOGIES PUNE

N. ENTERPRISES Pune

e	**DRIVE AND AGITATOR DATA**			
	Type of agitator	Baby Anchor with 2 Blade PBT	Yes	✓
	Mixing speed	60 minutes for 3000 liters	Yes	✓
	Motor HP Main Drive	15.0 HP/1440 RPM / Flange Mounted or equivalent	Yes	As per Digine.
f	**NOZZLES - TOP DISH**			
	Man Hole	450 mm with dished cover and 100 mm sight glass	Yes	✓
	Light Glass	100 MM Pad Type with FLP Vessel lamp	Yes	✓
g	**SHELL**			
	Temperature Sensor	½" BSP	Yes	✓
	Phase Inlet	40 mm with valve	Yes	✓
	Recirculation	50 mm with Valve	Yes	✓
h	**BOTTOM DISH**			
	Product Outlet	50 MM with ball valve	Yes	✓
	Filter	Suitable filter (<200 micron)	Yes	✓
i	**SURFACE FINISH**			
	Product Contact Parts	Polished to mirror finish. Surface roughness < 0.5 Ra	Yes	✓
	Product non-contact parts	Polished to matt finish. Surface roughness < 0.8 Ra	Yes	✓

N. ENTERPRISES Pune

	Filling Volume	600ml	Yes
	Electrical Specification		
	Main Machine	2.5 HP / 415 Volts / 50 Hz or equivalent for output of 60BPM	~~2.5 HP~~ Yes motor OR ~~Pneumatic~~ operated.
	Conveyor	1.5 HP / 415 Volts / 50 Hz or equivalent for output of 60BPM	Yes
	Storage tank	SS316 with the capacity of 100 liters	Yes
	SS conveyor belt made from the SS316 (Length as per the speed of bottles filling – 60BPM) Adjustable Conveyor height as per choice to align with another line machine.		Yes

NIHVA

B.N. ENTERPRISES Pune

NIHVA TECHNOLOGIES PVT. LTD.

NIHVA Technologies